

§ 25.225

(b) Paragraph (a) of this section does not apply to 17/24 GHz BSS telemetry earth stations. Those earth stations are subject to the antenna performance standards of §25.209(a) and (b) of this part.

[72 FR 50031, Aug. 29, 2007]

§ 25.225 Geographic Service Requirements for 17/24 GHz Broadcasting Satellite Service.

(a) Each operator of a 17/24 GHz BSS space station that is used to provide video programming directly to consumers in the 48 contiguous United States (CONUS) must provide comparable service to Alaska and Hawaii, unless such service is not technically feasible or not economically reasonable from the authorized orbital location.

(b) Each operator of a 17/24 GHz BSS space station subject to paragraph (a) of this section must design and configure its space station to be capable of providing service to Alaska and Hawaii, that is comparable to the service that such satellites will provide to CONUS subscribers, from any orbital location capable of providing service to either Alaska or Hawaii to which it may be located or relocated in the future.

(c) If an operator of a 17/24 GHz BSS space station that is used to provide video programming directly to consumers in the United States relocates or replaces a 17/24 GHz BSS space station at a location from which service to Alaska and Hawaii had been provided by another 17/24 GHz BSS space station, the operator must use a space station capable of providing at least the same level of service to Alaska and Hawaii as previously provided from that location.

[72 FR 50033, Aug. 29, 2007]

§§ 25.226–25.249 [Reserved]

§ 25.250 Sharing between NGSO MSS Feeder links Earth Stations in the 19.3–19.7 GHz and 29.1–29.5 GHz Bands.

(a) NGSO MSS applicants shall be licensed to operate in the 29.1–29.5 GHz band for Earth-to-space transmissions and 19.3–19.7 GHz for space-to-Earth transmissions from feeder link earth station complexes. A “feeder link earth

47 CFR Ch. I (10–1–07 Edition)

station complex” may include up to three (3) earth station groups, with each earth station group having up to four (4) antennas, located within a radius of 75 km of a given set of geographic coordinates provided by NGSO-MSS licensees or applicants.

(b) Licensees of NGSO MSS feeder link earth stations separated by 800 km or less are required to coordinate their operations, see §25.203. The results of the coordination shall be reported to the Commission.

[61 FR 44181, Aug. 28, 1996]

§ 25.251 Special requirements for coordination.

(a) The administrative aspects of the coordination process are set forth in §101.103 of this chapter in the case of coordination of terrestrial stations with earth stations, and in §25.203 in the case of coordination of earth stations with terrestrial stations.

(b) The technical aspects of coordination are based on Appendix S7 of the International Telecommunication Union Radio Regulations and certain recommendations of the ITU Radiocommunication Sector (available at the FCC’s Reference Information Center, Room CY-A257, 445 12th Street, SW., Washington, DC 20554).

[66 FR 10630, Feb. 16, 2001]

§ 25.252 Special requirements for ancillary terrestrial components operating in the 2000–2020 MHz/2180–2200 MHz bands.

(a) Applicants for an ancillary terrestrial component in these bands must demonstrate that ATC base stations shall not:

(1) Exceed an EIRP of –100.6 dBW/4 kHz for out-of-channel emissions at the edge of the MSS licensee’s selected assignment.

(2) Exceed a peak EIRP of 27 dBW in 1.23 MHz.

(3) Exceed an EIRP toward the physical horizon (not to include man-made structures) of 25.5 dBW in 1.23 MHz.

(4) Be located less than 190 meters from all airport runways and aircraft stand areas, including takeoff and landing paths.

(5) Exceed an aggregate power flux density of –51.8 dBW/m² in a 1.23 MHz bandwidth at all airport runways and