## §74.1284

(c) A translator station authorized under this subpart shall be identified by one of the following methods.

(1) By arranging for the primary station whose station is being rebroadcast to identify the translator station by call sign and location. Three such identifications shall be made during each day: once between 7 a.m. and 9 a.m., once between 12:55 p.m. and 1:05 p.m. and once between 4 p.m. and 6 p.m. Stations which do not begin their broadcast before 9 a.m. shall make their first identification at the beginning of their broadcast days. The licensee of an FM translator whose station identification is made by the primary station must arrange for the primary station licensee to keep in its file, and to make available to FCC personnel, the translator's call letters and location, giving the name, address and telephone number of the licensee or his service representative to be contacted in the event of malfunction of the translator. It shall be the responsibility of the translator licensee to furnish current information to the primary station licensee for this purpose.

(2) By transmitting the call sign in International Morse Code at least once each hour. Transmitters of FM broadcast translator stations of more than 1 watt transmitter output power must be equipped with an automatic keying device that will transmit the call sign at least once each hour, unless there is in effect a firm agreement with the translator's primary station as provided in \$74.1283(c)(1) of this section. Transmission of the call sign can be accomplished by:

(i) Frequency shifting key; the carrier shift shall not be less than 5 kHz nor greater than 25 kHz.

(ii) Amplitude modulation of the FM carrier of at least 30 percent modulation. The audio frequency tone use shall not be within 200 hertz of the Emergency Broadcast System Attention signal alerting frequencies.

(d) FM broadcast booster stations shall be identified by their primary stations, by the broadcasting of the primary station's call signs and location, in accordance with the provisions of 373.1201 of this chapter.

47 CFR Ch. I (10–1–07 Edition)

(e) The Commission may, in its discretion, specify other methods of identification.

[55 FR 50699, Dec. 10, 1990]

#### §74.1284 Rebroadcasts.

(a) The term *rebroadcast* means the reception by radio of the programs or other signals of a radio station and the simultaneous retransmission of such programs or signals for direct reception by the general public.

(b) The licensee of an FM translator shall not rebroadcast the programs of any FM broadcast station or other FM translator without obtaining prior consent of the primary station whose programs are proposed to be retransmitted. The Commission shall be notified of the call letters of each station rebroadcast and the licensee of the FM translator shall certify that written consent has been received from the licensee of the station whose programs are retransmitted.

(c) An FM translator is not authorized to rebroadcast the transmissions of any class of station other than an FM broadcast station or another FM translator.

#### §74.1290 FM translator and booster station information available on the Internet.

The Media Bureau's Audio Division provides information on the Internet regarding FM translator and booster stations, rules, and policies at *http:// www.fcc.gov/mb/audio.* 

# [67 FR 13234, Mar. 21, 2002]

### ALPHABETICAL INDEX-PART 74

A	
Additional orders by FCC (All Services)	74.28
Antenna, Directional (Aural STL/Relays)	74.536
Antenna location—	
LPTV/TV Translator	74.737
FM Translators/Boosters	74.1237
Antenna structure, marking and lighting (All Services).	74.30
Antenna structure, Use of common (All Serv- ices).	74.22
Antenna systems (TV Auxiliaries)	74.641
Antennas (ITFS)	74.937
Application Processing—ITFS	74.911
Application requirements of Part 73 applicable to ITFS.	74.910
Applications, Notification of filing (All Services)	74.12
Assignment, Frequency—	
Experimental Broadcast Station	74.103
Remote Pickup	74.402
Aural broadcast auxiliary stations	74.502
TV Auxiliaries	74.602