

**§ 17.47**

required level as construction progresses.

[32 FR 11273, Aug. 3, 1967, as amended at 39 FR 26157, July 17, 1974; 42 FR 54826, Oct. 11, 1977]

**§ 17.47 Inspection of antenna structure lights and associated control equipment.**

The owner of any antenna structure which is registered with the Commission and has been assigned lighting specifications referenced in this part:

(a)(1) Shall make an observation of the antenna structure's lights at least once each 24 hours either visually or by observing an automatic properly maintained indicator designed to register any failure of such lights, to insure that all such lights are functioning properly as required; or alternatively,

(2) Shall provide and properly maintain an automatic alarm system designed to detect any failure of such lights and to provide indication of such failure to the owner.

(b) Shall inspect at intervals not to exceed 3 months all automatic or mechanical control devices, indicators, and alarm systems associated with the antenna structure lighting to insure that such apparatus is functioning properly.

[61 FR 4363, Feb. 6, 1996]

**§ 17.48 Notification of extinguishment or improper functioning of lights.**

The owner of any antenna structure which is registered with the Commission and has been assigned lighting specifications referenced in this part:

(a) Shall report immediately by telephone or telegraph to the nearest Flight Service Station or office of the Federal Aviation Administration any observed or otherwise known extinguishment or improper functioning of any top steady burning light or any flashing obstruction light, regardless of its position on the antenna structure, not corrected within 30 minutes. Such reports shall set forth the condition of the light or lights, the circumstances which caused the failure, the probable date for restoration of service, the FCC Antenna Structure Registration Number, the height of the structure (AGL and AMSL if known) and the name, title, address, and telephone number of

**47 CFR Ch. I (10-1-08 Edition)**

the person making the report. Further notification by telephone or telegraph shall be given immediately upon resumption of normal operation of the light or lights.

(b) An extinguishment or improper functioning of a steady burning side intermediate light or lights, shall be corrected as soon as possible, but notification to the FAA of such extinguishment or improper functioning is not required.

[32 FR 11273, Aug. 3, 1967, as amended at 39 FR 26157, July 17, 1974; 40 FR 30267, July 18, 1975; 61 FR 4364, Feb. 6, 1996]

**§ 17.49 Recording of antenna structure light inspections in the owner record.**

The owner of each antenna structure which is registered with the Commission and has been assigned lighting specifications referenced in this part must maintain a record of any observed or otherwise known extinguishment or improper functioning of a structure light and include the following information for each such event:

(a) The nature of such extinguishment or improper functioning.

(b) The date and time the extinguishment or improper operation was observed or otherwise noted.

(c) Date and time of FAA notification, if applicable.

(d) The date, time and nature of adjustments, repairs, or replacements made.

[48 FR 38477, Aug. 24, 1983, as amended at 61 FR 4364, Feb. 6, 1996]

**§ 17.50 Cleaning and repainting.**

Antenna structures requiring painting under this part shall be cleaned or repainted as often as necessary to maintain good visibility.

[61 FR 4364, Feb. 6, 1996]

**§ 17.51 Time when lights should be exhibited.**

(a) All red obstruction lighting shall be exhibited from sunset to sunrise unless otherwise specified.

(b) All high intensity and medium intensity obstruction lighting shall be