

§ 23.12

(c) Controlling the transmission or reception of facsimile material.

[28 FR 13032, Dec. 5, 1963, as amended at 36 FR 2562, Feb. 6, 1971; 38 FR 22479, Aug. 21, 1973]

§ 23.12 Use of radiotelegraph emissions by radiotelephone stations.

The licensee of a point-to-point radiotelephone station may be authorized to use type N0N, A1A, A2A, F1B, or F2B emission for identification, for test purposes or for the exchange of service messages.

[49 FR 48701, Dec. 14, 1984]

§ 23.13 Types of emission.

Stations in the international fixed public radiocommunication services may be authorized to use any of the types of emission or combinations thereof, described in part 2 of this chapter, as well as new types which may be developed: *Provided*, That harmful interference to adjacent operations is not caused thereby, *And provided further*, That the intelligence to be transmitted will use the bandwidth requested to a degree of efficiency compatible with the current state of the art. A determination of the possibilities of interference will be made as outlined in § 23.20. In certain cases frequencies or emissions may be authorized on a temporary basis to determine if interference will occur. During normal operations, emissions shall be centered about an assigned frequency. Non-centered emissions may be employed for short periods of time as needed to avoid interfering signals or meet fluctuating traffic loading: *Provided*, That the occupied bandwidth of these emissions be contained within the authorized bandwidth, *And provided further*, That prior to any such use, the Commission be notified of the reference frequency or frequencies proposed to be used in lieu of the assigned frequency.

[38 FR 22479, Aug. 21, 1973]

§ 23.14 Emission, bandwidth, modulation and transmission characteristics.

In the services under this part emissions are designated by their classification and their necessary bandwidth in

47 CFR Ch. I (10-1-08 Edition)

accordance with the following procedures:

(a) *Designation of emissions in applications*. In applying for new frequency assignments for emissions not presently authorized, the emissions proposed to be used shall be described and their bandwidths specified as outlined in part 2 of this chapter.

(b) *Designation of emissions in authorizations*. The emission designations used in authorizations will indicate only the maximum value of the necessary bandwidth for each type of modulation authorized.

(c) *New types of emissions*. If application is made for a type of emission not covered by part 2 of this chapter, a full description of the emission must be provided and, if possible, measurements of its occupied bandwidth.

[38 FR 22479, Aug. 21, 1973, as amended at 49 FR 48701, Dec. 14, 1984]

§ 23.15 Emission limitations.

(a) For all transmitters placed into operation after September 19, 1973, and for all transmitters after September 19, 1975, which operate on frequencies below 30 MHz:

(1) The occupied bandwidth of emission shall be confined within the least possible spectrum space consistent with the state of the art and the required quality of transmission, and in no event shall be more than the authorized bandwidth.

(2) Spurious emissions of transmitters of mean power of 50 kilowatts or less shall be attenuated at least 40 decibels below the mean power of the fundamental without exceeding the power of 50 milliwatts.

(3) Spurious emissions of transmitters of mean power exceeding 50 kilowatts shall be attenuated at least 60 decibels below the mean power of the fundamental and every effort should be made to keep the level of spurious emissions below the power of 50 milliwatts.

(b) For all transmitters placed into operation after September 19, 1973, and for all transmitters after September 19, 1975, which operate on frequencies above 30 MHz, the mean powers of emissions shall be attenuated below