§24.129

(c) *Disaggregation*. Spectrum may be disaggregated in any amount.

(d) Combined partitioning and disaggregation. Licensees may apply for partial assignment of authorizations that propose combinations of partitioning and disaggregation.

(e) *License term.* The license term for a partitioned license area and for disaggregated spectrum shall be the remainder of the original licensee's license term as provided for in §1.955 of this chapter.

(f) Coverage requirements for partitioning. (1) Parties to a partitioning agreement must satisfy at least one of the following requirements:

(i) The partitionee must satisfy the applicable coverage requirements set forth in §24.103 for the partitioned license area; or

(ii) The original licensee must meet the coverage requirements set forth in \$24.103 for the entire geographic area. In this case, the partitionee must meet only the requirements for renewal of its authorization for the partitioned license area.

(2) Parties seeking authority to partition must submit with their partial assignment application a certification signed by both parties stating which of the options they select.

(3) Partitionees must submit supporting documents showing compliance with their coverage requirements as set forth in §24.103.

(4) Failure by any partitionee to meet its coverage requirements will result in automatic cancellation of the partitioned authorization without further Commission action.

(g) Coverage requirements for disaggregation. (1) Parties to a disaggregation agreement must satisfy at least one of the following requirements:

(i) Either the disaggregator or disaggregatee must satisfy the coverage requirements set forth in §24.103 for the entire license area; or

(ii) Parties must agree to share responsibility for meeting the coverage requirements set forth in §24.103 for the entire license area.

(2) Parties seeking authority to disaggregate must submit with their partial assignment application a certification signed by both parties stating which of the requirements they select.

(3) Disaggregatees must submit supporting documents showing compliance with their coverage requirements as set forth in §24.103.

(4) Parties that accept responsibility for meeting the coverage requirements and later fail to do so will be subject to automatic license cancellation without further Commission action.

[65 FR 35853, June 6, 2000]

EFFECTIVE DATE NOTE: At 65 FR 35853, June 6, 2000, §24.104 was added. This section contains information collection and recordkeeping requirements and will not become effective until approval has been given by the Office of Management and Budget.

§24.129 Frequencies.

The following frequencies are available for narrowband PCS:

(a) Eighteen frequencies are available for assignment on a nationwide basis as follows:

(1) Seven 50 kHz channels paired with 50 kHz channels:

Channel 1: 940.00-940.05 and 901.00-901.05 MHz;

- Channel 2: 940.05-940.10 and 901.05-901.10 MHz:
- Channel 3: 940.10-940.15 and 901.10-901.15 MHz;
- Channel 4: 940.15-940.20 and 901.15-901.20 MHz;
- Channel 5: 940.20–940.25 and 901.20–901.25 MHz; Channel 19: 930.50–930.55 and 901.30–901.35
- MHz; and Channel 20: 930.75–930.80 and 901.90–901.95
- MHz.

(2) Three 50 kHz channels paired with 12.5 kHz channels:

Channel 6: 930.40-930.45 and 901.7500-901.7625 MHz;

Channel 7: 930.45-930.50 and 901.7625-901.7750 MHz; and

Channel 8: 940.75–940.80 and 901.7750–901.7875 MHz;

(3) Two 50 kHz unpaired channels:

Channel 9: RESERVED;

Channel 10: 940.80–940.85 MHz; and

Channel 11: 940.85–940.90 MHz.

(4) One 100 kHz unpaired channel:

Channel 18: 940.65–940.75 MHz.

(5) Two 150 kHz channels paired with 50 kHz channels:

Channel 21: 930.00-930.15 and 901.50-901.55 MHz; and

Channel 22: 930.15–930.30 and 901.60–901.65 MHz.

Federal Communications Commission

(6) Three 100 kHz channels paired with 50 kHz channels:

Channel 23: 940.55–940.65 and 901.45–901.50 MHz;

Channel 24: 940.30–940.40 and 901.55–901.60 MHz; and

Channel 25: 940.45–940.55 and 901.85–901.90 MHz.

(b) Five frequencies are available for assignment on a regional basis as follows:

(1) One 50 kHz channel paired with 50 kHz channel:

Channel 12: 940.25–940.30 and 901.25–901.30 MHz.

Channel 13: RESERVED.

(2) Four 50 kHz channels paired with 12.5 kHz channels:

Channel 14: 930.55–930.60 and 901.7875–901.8000 MHz;

Channel 15: 930.60–930.65 and 901.8000–901.8125 $\rm MHz;$

Channel 16: 930.65-930.70 and 901.8125-901.8250 MHz; and

Channel 17: 930.70-930.75 and 901.8250-901.8375 MHz.

(c) Seven frequencies are available for assignment on an MTA basis as follows:

(1) Three 50 kHz unpaired channels:

Channel 26: 901.35-901.40 MHz;

Channel 27: 901.40-901.45 MHz; and

Channel 28: 940.40–940.45 MHz.

(2) One 50 kHz channel paired with 50 kHz channel:

Channel 29: 930.80–930.85 and 901.95–902.00 MHz.

(3) One 100 kHz channel paired with 50 kHz channel:

Channel 30: 930.30–930.40 and 901.65–901.70 MHz.

(4) One 150 kHz channel paired with 50 kHz channel:

Channel 31: 930.85–931.00 and 901.7–901.75 MHz.

(5) One 100 kHz channel paired with 12.5 kHz channel:

Channel 32: 940.90–941 and 901.8375–901.85 MHz.

NOTE TO §24.129: Operations in markets or portions of markets which border other countries, such as Canada and Mexico, will be subject to on-going coordination arrangements with neighboring countries.

[66 FR 29920, June 4, 2001]

§24.130 [Reserved]

§24.131 Authorized bandwidth.

The authorized bandwidth of narrowband PCS channels will be 10 kHz for 12.5 kHz channels and 45 kHz for 50 kHz channels. For aggregated adjacent channels, a maximum authorized bandwidth of 5 kHz less than the total aggregated channel width is permitted.

§24.132

§24.132 Power and antenna height limits.

(a) Stations transmitting in the 901– 902 MHz band are limited to 7 watts e.r.p.

(b) Mobile stations transmitting in the 930–931 MHz and 940–941 MHz bands are limited to 7 watts e.r.p.

(c) Base stations transmitting in the 930–931 MHz and 940–941 MHz bands are limited to 3500 watts e.r.p. per authorized channel and are unlimited in antenna height except as provided in paragraph (d) of this section.

(d)(1) MTA and regional base stations located between 200 kilometers (124 miles) and 80 kilometers (50 miles) from their licensed service area border are limited to the power levels in the following table:

Antenna HAAT in meters (feet) (see § 24.53 for HAAT HAAT calculation method) Effective radiated power (e.r.p.) (watts) 183 (600) and below 3500 183 (600) to 208 (682) 3500 to 2584 208 (682) to 236 (775) 2584 to 1883 236 (775) to 268 (880) 1883 to 1372 268 (880) to 305 (1000) 1372 to 1000 305 (1000) to 346 (1137) 1000 to 729 346 (1137) to 394 (1292) 729 to 531 394 (1292) to 447 (1468) 531 to 387 447 (1468) to 508 (1668) 387 to 282 508 (1668) to 578 (1895) 282 to 206 578 (1895) to 656 (2154) 206 to 150 656 (2154) to 746 (2447) 150 to 109 746 (2447) to 848 (2781) 109 to 80 848 (2781) to 963 (3160) 80 to 58 963 (3160) to 1094 (3590) 58 to 42 1094 (3590) to 1244 (4080) 42 to 31 1244 (4080) to 1413 (4636) 31 to 22 Above 1413 (4636) 16		
183 (600) to 208 (682) 3500 to 2584 208 (682) to 236 (775) 2584 to 1883 236 (775) to 268 (880) 1883 to 1372 268 (880) to 305 (1000) 1372 to 1000 305 (1000) to 346 (1137) 1000 to 729 346 (1137) to 394 (1292) 729 to 531 394 (1292) to 447 (1468) 531 to 387 447 (1468) to 508 (1668) 387 to 282 508 (1668) to 578 (1895) 282 to 206 578 (1895) to 656 (2154) 206 to 150 656 (2154) to 746 (2447) 150 to 109 746 (2447) to 848 (2781) 109 to 80 848 (2781) to 963 (3160) 80 to 58 963 (3160) to 1094 (3590) 58 to 42 1094 (3590) to 1244 (4080) 42 to 31 1224 (4080) to 1413 (4636) 31 to 22	§24.53 for HAAT HAAT calculation	
Above 1413 (4030)	183 (600) to 208 (682) 208 (682) to 236 (775) 236 (775) to 268 (880) 268 (880) to 305 (1000) 305 (1000) to 346 (1137) 346 (1137) to 394 (1292) 394 (1292) to 447 (1468) 447 (1468) to 508 (1668) 508 (1668) to 578 (1895) 578 (1895) to 656 (2154) 656 (2154) to 746 (2447) 746 (2447) to 848 (2781) 848 (2781) to 963 (3160) 963 (3160) to 1094 (3590) 1094 (3590) to 1244 (4080) 1244 (4080) to 1413 (4636)	3500 to 2584 2584 to 1883 1883 to 1372 1372 to 1000 1000 to 729 729 to 531 531 to 387 387 to 282 282 to 206 206 to 150 150 to 109 109 to 80 80 to 58 58 to 42 42 to 31 31 to 22

(2) For heights between the values listed in the table, linear interpolation shall be used to determine maximum e.r.p.

(e) MTA and regional base stations located less than 80 kilometers (50 miles) from the licensed service area