

Federal Communications Commission

§ 25.215

similar protection one year after notice to the mobile-satellite system licensees by issuance of a public notice by the Commission.

(2) Mobile-Satellite Service space stations transmitting in the 1613.8–1626.5 MHz band shall take whatever steps necessary to avoid causing harmful interference to the radio astronomy facilities listed in paragraphs (a)(1)(i) and (ii) of this section during periods of observation.

(3) Mobile-Satellite Service space stations operating in the 2483.5–2500 MHz frequency band shall limit spurious emission levels in the 4990–5000 MHz band so as not to exceed -241 dB (W/m²/Hz) at the surface of the Earth.

(4) The Radioastronomy Service shall avoid scheduling radio astronomy observations during peak MSS/RDSS traffic periods to the greatest extent practicable.

(b) If a Mobile-Satellite Service space station operator in the 2496–2500 MHz band intends to operate at powers levels that exceed the PFD limits in § 25.208(v), or if actual operations routinely exceed these PFD limits, we require the Mobile-Satellite Service operator to receive approval from each operational BRS system in the affected geographical region.

[59 FR 53329, Oct. 21, 1994, as amended at 61 FR 9945, Mar. 12, 1996; 67 FR 61816, Oct. 2, 2002; 71 FR 35188, June 19, 2006]

§ 25.214 Technical requirements for space stations in the satellite digital audio radio service.

(a) Definitions.

(1) *Allocated bandwidth.* The term “allocated bandwidth” refers to the entry in the Table of Frequency Allocations of a given frequency band for the purpose of its use by one or more terrestrial or space radiocommunication services under specified conditions. This term shall be applied to the 2310–2360 MHz band for satellite DARS.

(2) *Frequency Assignment.* The term “frequency assignment” refers to the authorization given by the Commission for a radio station to use a radio frequency or radio frequency channel under specified conditions. This term shall be applied to the two frequency

bands (A) 2320.0–2332.5 MHz and (B) 2332.5–2340.0 MHz for satellite DARS.

(b) Each system authorized under this section will be conditioned upon construction, launch and operation milestones as outlined in § 25.144(b). The failure to meet any of the milestones contained in an authorization will result in its cancellation, unless such failure is due to circumstances beyond the licensee’s control or unless otherwise determined by the Commission upon proper showing by the licensee in any particular case.

(c) Frequency assignments will be made for each satellite DARS system as follows:

(1) Exclusive satellite DARS licenses are limited to the 2320–2345 MHz band segment of the allocated bandwidth for satellite DARS;

(2) Two, 12.5 MHz frequency assignments are available for satellite DARS: 2320.0–2332.5 MHz and 2332.5–2345.0 MHz;

(3) Satellite DARS licensees may reduce their assigned bandwidth occupancy to provide telemetry beacons in their exclusive frequency assignments;

(4) Each licensee may employ cross polarization within its exclusive frequency assignment and/or may employ cross polarized transmissions in frequency assignments of other satellite DARS licensees under mutual agreement with those licensees. Licensees who come to mutual agreement to use cross-polarized transmissions shall apply to the Commission for approval of the agreement before coordination is initiated with other administrations by the licensee of the exclusive frequency assignment; and

(5) Feeder uplink networks are permitted in the following Fixed-Satellite Service frequency bands: 7025–7075 MHz and 6725–7025 MHz (101° W.L. orbital location only).

[62 FR 11106, Mar. 11, 1997]

§ 25.215 Technical requirements for space stations in the Direct Broadcast Satellite Service.

In addition to § 25.148(f), space station antennas operating in the Direct Broadcast Satellite Service must be designed to provide a cross-polarization isolation such that the ratio of the on-axis co-polar gain to the cross-polar