

§ 27.1217 Competitive bidding procedures for the Broadband Radio Service.

Mutually exclusive initial applications for BRS licenses in the 2500-2690 MHz band are subject to competitive bidding. The general competitive bidding procedures set forth in part 1, subpart Q of this chapter will apply unless otherwise provided in this subpart.

[73 FR 26041, May 8, 2008]

§ 27.1218 Designated entities.

(a) *Eligibility for small business provisions.* (1) A small business is an entity that, together with all attributed parties, has average gross revenues that are not more than \$40 million for the preceding three years.

(2) A very small business is an entity that, together with all attributed parties, has average gross revenues that are not more than \$15 million for the preceding three years.

(3) An entrepreneur is an entity that, together with all attributed parties, has average gross revenues that are not more than \$3 million for the preceding three years.

(b) *Bidding credits.* (1) A winning bidder that qualifies as a small business, as defined in this section, or a consortium of small businesses, may use a bidding credit of 15 percent, as specified in § 1.2110(f)(2)(iii) of this chapter, to lower the cost of its winning bid on any of the licenses in this subpart.

(2) A winning bidder that qualifies as a very small business, as defined in this section, or a consortium of very small businesses, may use a bidding credit of 25 percent, as specified in § 1.2110(f)(2)(ii) of this chapter, to lower the cost of its winning bid on any of the licenses in this subpart.

(3) A winning bidder that qualifies as an entrepreneur, as defined in this section, or a consortium of entrepreneurs, may use a bidding credit of 15 percent, as specified in § 1.2110(f)(2)(i) of this chapter, to lower the cost of its winning bid on any of the licenses in this subpart.

[73 FR 26041, May 8, 2008]

TECHNICAL STANDARDS

§ 27.1220 Transmission standards.

The width of a channel in the LBS and UBS is 5.5 MHz, with the exception of BRS channels 1 and 2 which are 6.0 MHz. The width of all channels in the MBS is 6 MHz. However, the licensee may subchannelize its authorized bandwidth, provided that digital modulation is employed and the aggregate power does not exceed the authorized power for the channel. The licensee may also, jointly with other licensees, transmit utilizing bandwidth in excess of its authorized bandwidth, provided that digital modulation is employed, all power spectral density requirements set forth in this part are met and the out-of-band emissions restrictions set forth in § 27.53 are met at the edges of the channels employed.

§ 27.1221 Interference protection.

(a) Interference protection will be afforded to BRS and EBS on a station-by-station basis based on the heights of the stations in the LBS and UBS and also on height benchmarking, although the heights of antennas utilized are not restricted.

(b) *Height Benchmarking.* Height benchmarking is defined for pairs of base stations, one in each of two proximate geographic service areas (GSAs). The height benchmark, which is defined in meters (hb_m) for a particular base station relative to a base station in another GSA, is equal to the distance, in kilometers, from the base station along a radial to the nearest point on the GSA boundary of the other base station squared (D_{km}^2) and then divided by 17. That is, $hb_m = D_{km}^2/17$. A base station antenna will be considered to be within its applicable height benchmark relative to another base station if the height in meters of its centerline of radiation above average elevation (HAAE) calculated along the straight line between the two base stations in accordance with §§ 24.53(b) and (c) of this chapter does not exceed the height benchmark (hb_m). A base station antenna will be considered to exceed its applicable height benchmark relative to another base station if the HAAE of its centerline of radiation calculated along the straight line between the two