

§ 27.1234

programming track on the MBS channels for each EBS video or data transmission track the licensee is transmitting on a simultaneous basis before the transition.

(i) To be eligible for migration, a program track must contain EBS programming that complies with § 27.1203 (b) and (c).

(ii) The proponent(s) must pay only the costs of migrating programming tracks being transmitted on December 31, 2002 or within six months prior thereto.

(2) The proponent(s) must migrate each eligible programming track to spectrum in the MBS that will be licensed to the affected licensee at the conclusion of the transition.

(3) After the transition, the desired-to-undesired signal level ratio at each of the receive sites securing a replacement downconverter must satisfy the following criteria:

(i) *Cochannel D/U Ratio.* (A) When the post-transition desired signal is transmitted using analog modulation, the actual cochannel D/U ratio measured at the output of the reception antenna must be at least the lesser of 45 dB or the actual pre-transmission D/U ratio less 1.5 dB.

(B) When the post-transition desired signal will be transmitted using digital modulation, the actual cochannel D/U ratio measured at the output of the reception antenna must be at least the lesser of 32 dB or the pre-transition D/U ratio less 1.5 dB.

(C) Where in implementing the Transition Plan, the proponent(s) deploys precise frequency offset in an analog system, the minimum cochannel D/U ratio is reduced to 38 dB, provided that the transmitters have or are upgraded pursuant to the Transition Plan to have the appropriate “plus,” “zero,” or “minus” 10,010 Hertz precision frequency offset with a ± 3 Hertz (or better) stability.

(ii) *Adjacent Channel D/U Ratio.* The actual adjacent channel D/U must equal or exceed the lesser of 0 dB or the actual pre-transmission D/U ratio. However, in the event that the receive site uses receivers or is upgraded by the proponent(s) as part of the Transition Plan to use receivers that can tolerate negative adjacent channel D/U

47 CFR Ch. I (10–1–08 Edition)

ratios, the actual adjacent channel D/U ratio at such receive site must equal or exceed -10 dB. Provided that the receive site receiver is not upgraded and cannot tolerate -10 dB, the adjacent channel D/U ratio would be 0dB.

[69 FR 72034, Dec. 10, 2004, as amended at 71 FR 35193, June 19, 2006]

§ 27.1234 Terminating existing operations in transitioned markets.

Licensees may discontinue operations during the transition.

§ 27.1235 Post-transition notification.

The proponent(s) must certify to the Commission at the Office of the Secretary, Washington, DC, that the Transition Plan has been fully implemented.

(a) The notification must provide the identification of the licensees that have transitioned to the band plan in § 27.5(i)(2) and the specific frequencies on which each licensee is operating.

(b) For each station in the MBS, the notification must provide the following information:

- (1) The station coordinates,
- (2) The make and model of each antenna,
- (3) The horizontal and vertical pattern of the antenna;
- (4) EIRP of the main lobe;
- (5) Orientation;
- (6) Height of antenna center of radiation;
- (7) Transmitter output power;
- (8) All line and combiner losses.

(c) The proponent(s) must provide copies of the post-transition notice to all parties of the transition.

(d) A BRS or EBS licensee must file any objection to the post-transition notification within 30 days from the date the post-transition notification is placed on Public Notice.

[69 FR 72034, Dec. 10, 2004, as amended at 71 FR 35193, June 19, 2006]

§ 27.1236 Self-transitions.

(a) If an Initiation Plan is not filed on or before January 21, 2009 for a BTA, BRS and EBS licensees in that BTA may self-transition by relocating to their default channel locations specified in § 27.5(i)(2) and complying with §§ 27.50(h), 27.53, 27.55 and 27.1221.