

(m) *PMT* means *program map table* as defined in International Standard ISO/IEC 13818-1:2000(E): “Information Technology—Generic Coding of Moving Pictures and Associated Audio Information: Systems” (incorporated by reference, see § 73.8000).

(n) *Robust method* means, with respect to the passing of unscreened content or marked content from one product to another, a content protection method that complies with § 73.9007.

(o) *Transitory image* means data that has been stored temporarily for the sole purpose of enabling a function not prohibited by this subpart but that (1) does not persist materially after such function has been performed and (2) is not stored in a way that permits copying or storing of such data for other purposes.

(p) *Unencrypted digital terrestrial broadcast content* means audiovisual content contained in the signal broadcast by a digital television station without encrypting or otherwise making the content available through a technical means of conditional access, and includes such content when retransmitted in unencrypted digital form.

(q) *Unscreened content* means, with respect to a covered demodulator product, unencrypted digital terrestrial broadcast content that such product either:

(1) Received and demodulated and for which such product has inspected neither the EIT nor the PMT for the broadcast flag; or

(2) Where such product is a peripheral TSP product, received via a robust method and accessed in usable form, and for which such product has inspected neither the EIT nor the PMT for the broadcast flag and has not determined through information robustly conveyed with such content another covered demodulator product had previously so screened such content and determined the broadcast flag to be present; provided, however, that, with respect to a covered demodulator product, unscreened content shall not include content that has been passed from such product pursuant to §§ 73.9003(a)(1), 73.9003(a)(2), 73.9003(a)(3), 73.9003(a)(4), 73.9003(a)(6), 73.9003(a)(7), or 73.9006(b).

(r) *User accessible bus* means a data bus that is designed for end user upgrades or access, such as an implementation of a smartcard interface, PCMCIA, Cardbus, or PCI that has standard sockets or otherwise readily facilitates end user access. A user accessible bus does not include memory buses, CPU buses, or similar portions of a device’s internal architecture that do not permit access to content in a form usable by end users.

[68 FR 67603, Dec. 3, 2003, as amended at 73 FR 5685, Jan. 30, 2008]

§ 73.9001 Redistribution control of digital television broadcasts.

Licensees of TV broadcast stations may utilize the redistribution control descriptor described in ATSC A/65B: “ATSC Standard: Program and System Information Protocol for Terrestrial Broadcast and Cable (Revision B),” (incorporated by reference, see § 73.8000) provided they do not transmit the optional additional redistribution control information.

§ 73.9002 Sale or distribution of demodulators, covered demodulator products, and peripheral TSP products.

(a) *Demodulators*. No party that manufactures or imports a demodulator shall sell or distribute in interstate commerce such Demodulator unless:

(1) At the time of such sale or distribution such demodulator is itself, or is incorporated into, a product that complies with the demodulator compliance requirements and was manufactured in accordance with the demodulator robustness requirements; or

(2) Such sale or distribution is to a party that has committed in writing pursuant to paragraph (d) of this section not to sell or distribute demodulators other than in accordance with paragraphs (a)(1) or (a)(2) of this section.

(b) *Covered demodulator products*. No party shall sell or distribute in interstate commerce a covered demodulator product that does not comply with the demodulator compliance requirements