Federal Communications Commission

- (iii) For any construction or alteration that would exceed the requirements of §17.7 of this chapter, licensees must notify the appropriate Regional Office of the Federal Aviation Administration (FAA Form 7460-1) and file a request for antenna height clearance and obstruction marking and lighting specifications (FCC Form 854) with the FCC, Attn: Information Processing Branch, 1270 Fairfield Rd., Gettysburg, PA 17325-7245.
- (iv) The transmitters must not have a significant environmental effect as defined by §§1.1301 through 1.1319 of this chapter.
- (d) Working frequencies in the Mississippi River System. The Mississippi River System includes the Mississippi River and connecting navigable waters other than the Great Lakes. The following simplex frequencies are available for assignment to public coast stations serving the Mississippi River System for radiotelephony communications. These simplex frequencies also are available for use by authorized ship stations within communication service range, whether or not the ship is operating within the confines of the Mississippi River System.

MISSISSIPPI RIVER SYSTEM WORKING FREQUENCIES; CARRIER FREQUENCIES (KHZ)

	ı				1
2086 ¹	4065	6209	8201	12362	16543
2782	4089	6212	8213	12365	16546
	4116	6510	8725		
	4408	6513	8737		

¹Limited to a maximum transmitter output of 150 watts (PEP).

(e) Canada/U.S.A. channeling arrangement frequencies. The VHF frequencies assignable to ship and coast stations in the State of washington and their usage limitations purusant to the Canada/U.S.A. channeling arrangement are described in subpart B of this part.

[51 FR 31213, Sept. 2, 1986, as amended at 52 FR 35245, Sept. 18, 1987; 52 FR 48439, Dec. 22, 1987; 56 FR 9894, Mar. 8, 1991; 57 FR 26779, June 16, 1992; 58 FR 44953, Aug. 25, 1993; 60 FR 35510, July 10, 1995; 62 FR 40307, July 28, 1997; 63 FR 40065, July 27, 1998; 64 FR 26887, May 18, 1999; 65 FR 77824, Dec. 13, 2000; 67 FR 48565, July 25, 2002; 69 FR 64674, Nov. 8, 2004; 71 FR 60074, Oct. 12, 2006; 72 FR 31194, June 6, 2007; 73 FR 4486, Jan. 25, 2008]

§80.373 Private communications frequencies.

This section describes the carrier frequencies assignable for ship-to-ship and ship-to-coast private communications.

- (a) Special requirements for private coast stations. Assignment to private coast stations of radiotelephony frequencies in the 2000–27500 kHz band are subject to the following:
- (1) Private coast stations must use J3E emission.
- (2) On 2182 kHz, private coast stations must be capable of receiving J3E and H3E emissions.
- (3) Except in the Mississippi River System and Great Lakes, private coast stations serving lakes or rivers are not authorized on the 2000–2850 kHz band.
- (4) Private coast stations may use DSC for calling on their assigned frequencies in the 2000–27500 kHz band and on those frequencies in the 156–162 MHz band which are allocated for maritime control, commercial and non-commercial communications.
- (b) Frequencies in the 2000–27500 kHz band for intership safety and other communications. This paragraph describes the geographic areas of operation and the frequencies and liminations in the band available for assignment for intership safety and operational simplex radiotelephone communications.

(1) Frequencies avaiable.

Carrier frequency (kHz)	Geographic area		
2003.0 2082.5 ^{1,2} 2093.0 ¹	Great Lakes only. All areas. All areas.		
2142.0	Pacific coast areas south of 42 degrees north on a day basis only.		
2203.0 ²	Gulf of Mexico.		
2214.01	All areas.		
2638.0 ¹	All areas.		
2670.0	All areas.		
2738.01	All areas except the Great Lakes.		
2830.0	Gulf of Mexico only.		

- ¹Limited to a peak envelope power of 150 watts. ²Available on a secondary basis for intership communications by ships involved in non-commercial fishing.
- (2) Except for 2093.0 kHz and 2214.0 kHz the frequencies shown in paragraph (b)(1) of this section are authorized primarily for intership safety communications in the indicated geographic area.
- (3) Except for the frequencies 2093.0 kHz, 2214.0 Khz and 2670.0 kHz the frequencies shown in paragraph (b)(1) of

§ 80.373

this section may be used on a non-interference basis to safety communications, for operational communications and in the case of commercial transport ships and ships of municipal and state governments, for business communications.

- (4) Ship stations may communicate with government coast stations on 2003.0 kHz about passage of vessels. Interference must not be caused to communications on the St. Lawrence Seaway and on the St. Mary's River.
- (5) Ship stations may use 2670.0 kHz for communications with coast and ship stations of the U.S. Coast Guard. When a ship is not equipped to transmit on 2670.0 kHz or in the band 156-162 MHz the frequency 2003.0 kHz may be used on the Great Lakes for communications must not cause harmful interference to intership safety, operational and business communications.
- (6) Navigational communications between ships and private coast stations may be exchanged on 2738.0 kHz and 2830.0 kHz. The frequencies 2214.0 kHz2738.0 kHz and 2830.0 kHz are assignable to private coast stations upon a showing that they need to communicate with commercial transport or Government ships. Private coast station applicants must show that public coast stations do not provide the required communications and harmful interference will not be caused to the

intership use of these frequencies. The transmitter power must not exceed 150 watts. If 2214.0 kHz is authorized for ships, intership communication is also authorized. The geographic limitations to the frequencies 2738.0 KHz and 2830.0 Khz do not prohibit intership communication of less than 320 km (200 statute miles) when only one of the ship stations is within a permitted use geographic area.

- (7) Private aircraft stations may communicate with ship stations on 2738.0 kHz and 2830.0 kHz if:
- (i) The communications are limited to business or operational needs of the vessel while it is engaged in commercial fishing activities in the open sea or adjacent waters:
- (ii) Harmful interference must not be caused to intership communications;
- (iii) The maximum output power used for such communication must not exceed 25 watts;
- (c) Frequencies in the 2000-27500~kHzbands for business and operational communications. (1) The following simplex frequencies in the 2000-27500 kHz band are available for assignment to private coast stations for business and operational radiotelephone communications. These simplex frequencies also are available for use by authorized ship stations for business and operational radiotelephone communications.

BUSINESS AND OPERATIONAL FREQUENCIES IN THE 2000-27500 KHZ BAND; CARRIER FREQUENCIES (KHZ)

2065.0 ^{1,3}	4146 4149	6224 6227	8294 8297	12353 12356	16528 16531	18840 18843	22159 22162	25115 25118
2096.51	41252	6230		12359 ⁶	16534		22165	
3023.04	44175	6516					22168	
	56804						22171	

Limited to peak envelope power of 150 watts.

- (2) Assignment of these frequencies is subject to the following general limitations:
- (i) These frequencies are shared and are not available for the exclusive use of any station. No more than one frequency from each of the frequency

bands will be authorized to a private station without justification;

(ii) The emissions must be J3E or J2D except that when DSC is used the emission must be F1B or J2B; and

The frequency 4125 kHz is also available for distress and safety, and calling and reply, see § 80.369 (b) and (d) of this part.

The frequencies 2065.0 kHz and 2079.0 kHz must be coordinated with Canada.

The frequencies 3023.0 kHz and 5680.0 kHz are available to private coast stations licensed to state and local governments. and any scene-of-action ships for the purpose of search and rescue scene-of-action coordination including communications with

and any scene-of-action strips for the purpose of sealor than 1995.

The frequency 6516 kHz is limited to daytime operations. The frequencies 4417 kHz and 6516 kHz are also available for calling and reply, see § 80.369(d) of this part.

The alternative carrier frequency 12359 kHz may be used by ship stations and coast stations for calling on a simplex basis, provided that the peak envelope power does not exceed 1 kW.

Federal Communications Commission

- (iii) Maximum transmitter output power is limited to 1 kW except as noted.
- (3) In addition to the frequencies shown in paragraph (c)(1) of this section, the following coast transmit frequencies listed in the table in §80.371(a) of this chapter are available for assignment to private coast stations and authorized ship stations for simplex business and operational radiotelephone communications: in the East Coast, West Coast, and Gulf Coast regions. 2482 kHz; in the Alaska region, 2309 kHz. These frequencies shall not be assigned to public coast stations before July 25, 2002. After that date, only the above frequencies in the above regions that have been assigned to at least one private coast station shall continue to be available for assignment to private coast stations. If, by that date, in any of the above regions, any of the above frequencies has not been assigned to a private coast station, that frequency in that region shall be available for assignment only to public coast stations.
- (d) Radioprinter frequencies. (1) The following table describes the bands available for radioprinter simplex communications between ship and private coast stations:

FREQUENCY BANDS (KHZ)

 $\begin{array}{cccc} 2107-2170 & 4750-4850 \\ 2194-2495 & 5060-5450 \\ 2505-2850 & 5700-5950 \\ 3155-3400 & 7300-8100 \\ 4438-4650 & \end{array}$

 $^1\mathrm{After}$ April 1, 2007, use of the sub-bands 5900–5950 kHz and 7300–7350 kHz shall be on the condition that harmful interference is not caused to HF broadcasting.

- (2) Ship stations may conduct radioprinter communications with private coast stations on frequencies within these bands which are assigned to their associated private coast stations;
- (3) Any alphanumeric code may be used; and
- (4) The bandwidth of radioprinter communications on frequencies within these bands must not exceed 300 Hz.
- (e) Frequencies in the 2000–27500 kHz band for medical advisory communications. (1) Private coast stations may be authorized to use any frequencies within the 2030–27500 kHz band that are allocated to Government and non-Government fixed or fixed and mobile radio services shown in the Commission's Table of Frequency Allocations contained in §2.106 of this chapter for communications with ship stations to provide medical treatment information or advice. Assignment of these frequencies is subject to the following limitations:
- (2) No protection is provided from harmful interference caused by foreign stations; and
- (3) A private coast station must cease operations on a frequency that causes harmful interference to a foreign station
- (f) Frequencies in the 156–162 MHz band. The following tables describe the carrier frequencies available in the 156–162 MHz band for radiotelephone communications between ship and private coast stations. (Note: the letter "A" following the channel designator indicates simplex operation on a channel designated internationally as a duplex channel.)

FREQUENCIES IN THE 156-162 MHz BAND

Channel designator	Carrier frequency (MHz) ship transmit	Carrier frequency (MHz) coast transmit	Points of communication (intership and between coast and ship unless otherwise indicated)				
Port Operations							
01A ¹	156.050	156.050					
63A ¹	156.175	156.175					
05A ²	156.250	156.250					
65A	156.275	156.275					
66A	156.325	156.325					
123	156.600	156.600					
73	156.675	156.675					
143	156.700	156.700					
74	156.725	156.725					
75 18	156.775	156.775					
76 18	156.825	156.825					
77 4	156.875		Intership only.				

47 CFR Ch. I (10-1-08 Edition)

FREQUENCIES IN THE 156-162 MHz BAND-Continued

Channel designator	Carrier frequency (MHz) ship transmit	Carrier frequency (MHz) coast transmit	Points of communication (intership and between coast and ship unless otherwise indicated)
20A 12	157.000		Intership only.
	Navigational (Br	idge-to-Bridge) ⁵	
136	156.650	156.650	
677	156.375	156.375	
	Comm	ercial	
01A ¹	156.050	156.050	
63A1	156.175	156.175	
07A	156.350	156.350	
677	156.375		Intership only.
08	156.400		Do.
09	156.450	156.450	20.
10	156.500	156.500	
113	156.550	156.550	
18A			
	156.900	156.900	
19A	156.950	156.950	
79A	156.975	156.975	
80A	157.025	157.025	
88A ⁸	157.425		Intership only.
72 14	156.625		Intership only.
	Digital Selec	tive Calling	
70 15	156.525	156.525	
	Noncom	mercial	
68 17	156.425	156.425	
09 16	156.450	156.450	
69	156.475	156.475	
71 ¹⁹	156.575	156.575	
72	156.625		Intership only.
78A		156.925	intership only.
	156.925		Creat Lakes only
79A	156.975	156.975	Great Lakes only.
80A	157.025	157.025	Do.
67 14	156.375		Intership only.
	Distress, Safe	ty and Calling	
16	156.800	156.800	
	Intership	Safety	
06	156.300		a. Intership, or b. For SAR: Ship and aircraft for the U.S. Coast Guard.
	Environ	mental	
15 13		156.750	Coast to ship only.
	Maritime	Control	
17 9,10	156.850	156.850	
Liaiso	on and Safety Broad		iuard
22A ¹¹	157.100	·	
2CA''	157.100	157.100	Ship, aircraft, and coast stations of the U.S. Coast Guard and at Lake Mead Nev., ship and coast stations of the National Park Service, U.S. Depart ment of the Interior.
1156 050 MHz and 156 175 MHz are ave	ilable for part aparet	ione and commercial	communications purposes when used only

^{1156.050} MHz and 156.175 MHz are available for port operations and commercial communications purposes when used only within the U.S. Coast Guard designated Vessel Traffic Services (VTS) area of New Orleans, on the lower Mississippi River from the various pass entrances in the Gulf of Mexico to Devil's Swamp Light at River Mile 242.4 above head of passes near Baton Rouge.

2 156.250 MHz is available for port operations communications use only within the U.S. Coast Guard designated VTS radio protection areas of New Orleans and Houston described in § 80.383. 156.250 MHz is available for intership port operations communications used only within the area of Los Angeles and Long Beach harbors, within a 25-nautical mile radius of Point Fermin, California.

3156.550 MHz, 156.600 MHz and 156.700 MHz are available in the U.S. Coast Guard designated port areas only for VTS ommunications and in the Great Lakes available primarily for communications relating to the movement of ships in sectors designated by the St. Lawrence Seaway Development Corporation or the U.S. Coast Guard. The use of these frequencies outside VTS and ship movement sector protected areas is permitted provided they cause no interference to VTS and ship movement communications in their respective designated sectors.

4 Use of 156.875 MHz is limited to communications with pilots regarding the movement and docking of ships. Normal output power must not exceed 1 watt.

5 156.375 MHz and 156.650 MHz are available primarily for intership navigational communications. These frequencies are available between coast and ship on a secondary hasis when used on or in the vicinity of locks or drawbridges. Normal output

power must not exceed 1 watt.

5 156.375 MHz and 156.650 MHz are available primarily for intership navigational communications. These frequencies are available between coast and ship on a secondary basis when used on or in the vicinity of locks or drawbridges. Normal output power must not exceed 1 watts for coast stations or 25 watts for ship stations.

On the Great Lakes, in addition to bridge-to-bridge communications, 156.650 MHz is available for vessels control purposes in established vessel traffic systems. 156.650 MHz is not available for use in the Mississippi River from South Pass Lighted Whistle Buoy or mile 242.4 above Head of Passes near Baton Rouge. Additionally it is not available for use in the Mississippi River-Gulf Outlet Canal, and the Inner Harbor Navigational Canal, except to aid the transition from these areas.

7 Use of 156.375 MHz is available for navigational communications only in the Mississippi River from South Pass Lighted Whistle Buoy "2" and Southwest Pass entrance Mid-channel Lighted Whistle Buoy to mile 242.4 above Head of Passes near Baton Rouge, and in addition over the full length of the Mississippi River-Gulf Outlet Canal from entrance to its junction with the Inner Harbor Navigational Canal, and over the full length of the Inner Harbor Navigational Canal from its junction with the Mississippi River to its entry to Lake Pontchartrain at the New Seabrook vehicular bridge.

§ Within 120 km (75 miles) of the United States/Canada border, in the area of the Puget Sound and the Strait of Juan de Fuca and its approaches, 157.425 MHz is half of the duplex pair designated as Channel 88. In this area, Channel 88 is available to ship stations for communications with public coast stations only. More than 120 km (75 miles) from the United States/Canada border, in the area of the Puget Sound and the Strait of Juan de Fuca, its approaches, the Great Lakes, and the St. Lawrence Seaway, 157.425 MHz is available to rintership and commercial communications. Outside Puget Sound area and its approa

tion with U.S. Coast Guard stations. Prior U.S. Coast Guard approved to September 12 The duplex pair for channel 20 (157.000/161.600 MHz) may be used for ship to coast station communications.

13 Available for assignment to coast stations, the use of which is in accord with an agreed program, for the broadcast of information to ship stations concerning the environmental conditions in which vessels operate, *i.e.*, weather; sea conditions; time signals; notices to mariners; and hazards to navigation.

14 Available only in the Puget Sound and the Strait of Juan de Fuca.

15 The frequency 156.525 MHz is to be used exclusively for distress, safety and calling using digital selective calling techniques. No other uses are permitted.

¹⁵ The frequency 156.525 MHz is to be used exclusively for distress, safety and calling using digital selective calling tecrniques. No other uses are permitted.
¹⁶ The frequency 156.450 MHz is available for intership, ship and coast general purpose calling by noncommercial vessels, such as recreational boats and private coast stations.
¹⁷ The frequency 156.425 MHz is assigned by rule to private coast stations in Alaska for facsimile transmissions as well as voice communications.
¹⁸ The frequencies 156.775 and 156.825 MHz are available for navigation-related port operations or ship movement only, and all precautions must be taken to avoid harmful interference to channel 16. Transmitter output power is limited to 1 watt for ship stations and 10 watts for coast stations. stations, and 10 watts for coast stations.

19 156.575 MHz is available for port operations communications use only within the U.S. Coast Guard designated VTS radio protection area of Seattle (Puget Sound) described in § 80.383. Normal output power must not exceed 1 watt. Maximum output power must not exceed 10 watts.

(g)(1) On-board communications: This section describes the carrier frequency pairs assignable for on-board mobile radiotelephony communications. The center of the on-board repeater antenna must not be located more than 3 meters (10 feet) above the ship's working deck. These frequencies are available on a shared basis with stations in the Industrial/Business Radio Pool.

(2) Where needed, equipment designed for 12.5 kHz channel spacing using the additional frequencies 457.5375 MHz, 457.5625 MHz, 467.5375 MHz, and 467.5625 MHz may be introduced for on-board communications.

(h) Repeater frequencies in Alaska. The following frequencies are assignable on a primary basis to public and on a secondary basis to private coast stations in Alaska for maritime repeater operations

Repeater receive: 157.275 MHz Repeater transmit: 161.875 MHz

(i) Frequencies in the 1600-5450 kHz band for private communications in Alas*ka*. The following simplex frequencies are available for assignment to private fixed stations located in the State of Alaska for radiotelephony communications with ship stations. These simplex frequencies are available for use by authorized ship stations radiotelephony communications with private fixed stations located in the State of Alaska.

PRIVATE COMMUNICATIONS IN ALASKA CARRIER ERECLIENCIES (KHZ)

FNEC	ROENCIES (KI IZ)	
1619.0 ³	2382.0	2563.0
1622.0 ³	2419.0	2566.0
1643 N ³	2422 0	2590.0

§ 80.374

PRIVATE COMMUNICATIONS IN ALASKA CARRIER FREQUENCIES (KHz)—Continued

	THEQUENCIES (INTIZ)	Continue	u
1646.0 ³	, ,	2427.0	2616.0
1649.0 ³		2430.0	3258.0
1652.0 ³		2447.0	13261.0
1705.0 ³		2450.0	4366.0
1709.0		2479.0	4369.0
1712.0		2482.0	4396.0
2003.0		2506.0	4402.0
2006.0		2509.0	4420.0
2115.0		2512.0	4423.0
2118.0		2535.0	² 5167.5
2379.0		2538.0	

¹ Ship stations must limit use of 3261.0 kHz to communica-

strip stations must limit use of 32-0. KHz.1 collimituates of 32-0. KHz.1 collimituates to so very distances which cannot be reached by the use of frequency below 2700 kHz or above 156.000 MHz.

2 The frequency 516.7.5 kHz is available for emergency communications in Alaska. Peak envelope power of stations operating on this frequency must not exceed 150 watts. When a station in Alaska is authorized to use 516.7.5 kHz, such station may also use this frequency for calling and listening for the number of establishing communications.

the purpose of establishing communications.

³Use of these frequencies is on a secondary basis to Region 2 broadcasting.

(j) Frequencies for portable ship stations. VHF frequencies authorized for stations authorized carrier frequencies in the 156.275 MHz to 157.450 MHz and 161.575 MHz to 162.025 MHz bands may also be authorized as marine utility stations. Marine-utility stations on shore must not cause interference to any Automatic Identification System, VHF or coast station, VHF or UHF land mobile base station, or U.S. Government station.

[51 FR 31213, Sept. 2, 1986; 51 FR 34984, Oct. 1, 1986, as amended at 52 FR 35245, Sept. 18, 1987; 53 FR 17052, May 13, 1988; 54 FR 8542, Mar. 1, 1989; 54 FR 40059, Sept. 29, 1989; 56 FR 9896, Mar. 8, 1991; 56 FR 34030, July 25, 1991; 57 FR 19552, May 7, 1992; 57 FR 26779, June 16, 1992; 58 FR 16504, Mar. 29, 1993; 58 FR 44953, Aug. 25, 1993; 60 FR 35510, July 10, 1995; 62 FR 40307, July 28, 1997; 65 FR 43715, July 14, 2000; 67 FR 48564, July 25, 2002; 68 FR 25540, May 13, 2003; 68 FR 46970, Aug. 7, 2003; 69 FR 76865, Dec. 23, 2004; 71 FR 60074, Oct. 12, 2006; 73 FR 4486, Jan. 25, 2008]

§80.374 Provisions for frequencies in the 4000–4063 and the 8100–8195 kHz bands shared with the fixed service.

Coast station assignments in the 4000-4063 kHz band deviate from international provisions. Coast station assignments in the 4000-4063 kHz band are permitted provided that such stations must not cause interference to, and must accept interference from, stations operated by other countries in accordance with the Radio Regulations.

(a) Frequencies in the 4000-4063 kHz band. (1) The frequencies in the 40004063 kHz bands are available to ship and public coast stations for:

- (i) Supplementary ship-to-shore duplex operations with coast stations assigned the frequencies described in §80.371(b) of this part;
- (ii) Intership simplex operations and cross-band operations;
- (iii) Ship-to-shore or shore-to-ship simplex operations; or
- (iv) Duplex operations with coast stations assigned in the band 4438-4650 kHz, as described in §80.373(d) of this part.
- (2) The following table describes the channelization of carrier frequencies in the 4000-4063 kHz band.

CARRIER FREQUENCIES (KHZ)

4000	4015	4030	4045
4003	4018	4033	4048
4006	4021	4036	4051
4009	4024	4039	4054
4012	4027	4042	4057

- (b) Frequencies in the 8100-8195 kHz band. (1) The frequencies in the 8100-8195 kHz bands are available to ship and public coast stations for:
- (i) Supplementary ship-to-shore duplex operations with coast stations assigned the frequencies described in §80.371(b) of this part;
- (ii) Intership simplex operations and cross-band operations; or
- (iii) Ship-to-shore or shore-to-ship simplex operations.
- (2) The following table describes the channelization of carrier frequencies in the 8100-8195 kHz band.

CARRIER FREQUENCIES (KHZ)

8101	8137	8167
8104	8140	8170
8107	8143	8173
8110	8146	8176
8116	8149	8179
8119	8152	8182
8122	8155	8185
8125	8158	8188
8131	8161	8191
8134	8164	

[56 FR 9896, Mar. 8, 1991, as amended at 65 FR 77826, Dec. 13, 2000; 68 FR 46970, Aug. 7, 2003]