

TABLE E-6—MAXIMUM ERP (WATTS) FOR CONTROL TRANSMITTERS (HAAT MORE THAN 152 METERS)—Continued

Distance to protected TV station in kilometers (miles)	Antenna height above average terrain in meters (feet)					
	152 (500)	305 (1000)	457 (1500)	610 (2000)	762 (2500)	914 (3000)
193 (120) .....	50	19	9	5	3	2

See § 22.627(b)(1)(iii). This table is for antenna heights of more than 152 meters (500 feet) above average terrain. For intermediate values of height and/or distance, use linear interpolation to obtain the maximum permitted ERP.

TABLE E-7—MAXIMUM ERP (WATTS) FOR CONTROL TRANSMITTERS

Distance to protected TV station in kilometers (miles)	Antenna height above average terrain in meters (feet)								
	30 (100)	46 (150)	61 (200)	76 (250)	91 (300)	107 (350)	122 (400)	137 (450)	152 (500)
108 (67) .....	1000	1000	1000	1000	1000	1000	1000	1000	1000
106 (66) .....	1000	1000	1000	1000	1000	1000	1000	1000	750
105 (65) .....	1000	1000	1000	1000	1000	1000	825	650	600
103 (64) .....	1000	1000	1000	1000	1000	775	625	500	400
101 (63) .....	1000	1000	1000	1000	440	400	350	320	300
100 (62) .....	1000	1000	1000	525	375	250	200	150	125
98 (61) .....	1000	700	450	250	200	125	100	75	50
97 (60) .....	1000	425	225	125	100	75	50	.....	.....

See § 22.627(b)(2). This table applies to control transmitters in the Boston, Chicago, Cleveland, Detroit, Los Angeles, New York-Northeastern New Jersey, Philadelphia, Pittsburgh and Washington, DC urban areas. This table is for antenna heights of 152 meters (500 feet) or less above average terrain. For antenna heights between those in the table, use the next higher antenna height. For distances between those in the table, use the next lower distance.

[59 FR 59507, Nov. 17, 1994; 60 FR 9890, Feb. 22, 1995; as amended at 63 FR 68946, Dec. 14, 1998]

470-512 MHz TRUNKED MOBILE OPERATION

§ 22.651 470-512 MHz channels for trunked mobile operation.

The following channels are allocated for assignment to transmitters providing trunked public mobile service within the specified urban areas. All channels have a bandwidth of 20 kHz and are designated by their center frequencies in MegaHertz.

Houston			
488.0125 .....	491.0125	488.0875 .....	491.0875
488.0375 .....	491.0375	488.1125 .....	491.1125
488.0625 .....	491.0625	488.1375 .....	491.1375
New York-Northern New Jersey			
473.0125 .....	479.0125	473.1625 .....	479.1625
473.0375 .....	479.0375	473.1875 .....	479.1875
473.0625 .....	479.0625	473.2125 .....	479.2125
473.0875 .....	479.0875	473.2375 .....	479.2375
473.1125 .....	479.1125	473.2625 .....	479.2625
473.1375 .....	479.1375	473.2875 .....	479.2875

[59 FR 59507, Nov. 17, 1994; 60 FR 9891, Feb. 22, 1995]

§ 22.653 Eligibility.

Only licensees already authorized to provide trunked mobile service or their successors in interest are eligible to apply for additional use of these channels for trunked mobile service, and

then only in the urban areas already authorized.

§ 22.657 Transmitter locations.

The purpose of the rules in paragraphs (a) and (b) of this section is to define the areas in which the 470-512 MHz channels are allocated for public mobile use. The purpose of the rules in paragraphs (c) through (f) of this section is to reduce the likelihood that interference to television reception from public mobile operations on these channels will occur. The protected TV station locations specified in paragraphs (d), (e)(1) and (f) of this section are the locations of record as of September 1974, and these do not change even though the TV stations may have been subsequently relocated.

(a) *Base transmitter locations.* Base transmitter locations must be within 80 kilometers (50 miles) of the designated locations in this paragraph. Mobile transmitters must not be operated at locations more than 129 kilometers (80 miles) from the designated locations in this paragraph. Note: All coordinates are referenced to North American Datum 1983 (NAD83).