

§ 22.853

area as another transmitter on any ground station channel listed in § 22.805 if it is located less than 350 kilometers (217 miles) from that transmitter.

(b) *Initial channel.* The FCC will not assign more than one ground station communication channel for new ground stations. Ground stations are considered to be new if there are no authorized ground station transmitters on any channel listed in § 22.805 controlled by the applicant in the same area.

(c) *Additional channel.* Applications for ground transmitters to be located in the same area as an authorized ground station controlled by the applicant, but to operate on a different ground station communication channel, are considered as requesting an additional channel for the authorized station.

(d) *Amendment of pending application.* If the FCC receives and accepts for filing an application for a ground station transmitter to be located in the same area as a ground station transmitter proposed in a pending application previously filed by the applicant, but on a different ground station communication channel, the subsequent application is treated as a major amendment to change the technical proposal of the prior application. The filing date of any application so amended is the date the FCC received the subsequent application.

(e) *Dismissal of premature applications for additional channel.* If the FCC receives an application requesting an additional ground station communication channel for an authorized ground station prior to receiving notification that the station is providing service to subscribers on the authorized channel(s), the FCC may dismiss that application without prejudice.

(f) *Dismissal of applications for seventh channel.* If the FCC receives an application requesting an additional ground station communication channel for an authorized ground station which would, if granted, result in that station being assigned more than six ground station communication channels in the same area, the FCC may dismiss that application without prejudice.

47 CFR Ch. I (10–1–09 Edition)

COMMERCIAL AVIATION AIR-GROUND SYSTEMS

§ 22.853 Eligibility to hold interest in licenses limited to 3 MHz of spectrum.

No individual or entity may hold, directly or indirectly, a controlling interest in licenses authorizing the use of more than three megahertz of spectrum (either shared or exclusive) in the 800 MHz commercial aviation Air-Ground Radiotelephone Service frequency bands (see § 22.857). Individuals and entities with either *de jure* or *de facto* control of a licensee in these bands will be considered to have a controlling interest in its license(s). For purposes of this rule, the definitions of “controlling interests” and “affiliate” set forth in paragraphs (c)(2) and (c)(5) of § 1.2110 of this chapter shall apply.

[70 FR 19310, Apr. 13, 2005]

§ 22.857 Channel plan for commercial aviation air-ground systems.

The 849–851 MHz and 894–896 MHz frequency bands are designated for paired nationwide exclusive assignment to the licensee or licensees of systems providing radio telecommunications service, including voice and/or data service, to persons on board aircraft. Air-ground systems operating in these frequency bands are referred to in this part as “commercial aviation” systems.

[70 FR 19310, Apr. 13, 2005]

§ 22.859 Incumbent commercial aviation air-ground systems.

This section contains rules concerning continued operation of commercial aviation air-ground systems that were originally authorized prior to January 1, 2004 to provide radiotelephone service using narrowband (6 kHz) channels, and that have been providing service continuously since the original commencement of service (hereinafter “incumbent systems”).

(a) An incumbent system may continue to operate under its authorization, for the remaining term of such authorization, subject to the terms and conditions attached thereto. Wherever

such technical and operational conditions differ from technical and operational rules in this subpart, those conditions shall govern its operations.

(b) Notwithstanding any other provision in this chapter, the licensee of an incumbent system shall not be entitled to an expectation of renewal of said authorization.

(c) During the period that an incumbent system continues to operate and provide service pursuant to paragraph (a) of this section, air-ground systems of licensees holding a new authorization for the spectrum within which the incumbent system operates must not cause interference to the incumbent system. Protection from interference requires that the signals of the new systems must not exceed a ground station received power of -130 dBm within a 6 kHz receive bandwidth, calculated assuming a 0 dBi vertically polarized receive antenna.

[70 FR 19310, Apr. 13, 2005]

§ 22.861 Emission limitations.

The rules in this section govern the spectral characteristics of emissions for commercial aviation systems in the Air-Ground Radiotelephone Service. Commercial aviation air-ground systems may use any type of emission or technology that complies with the technical rules in this subpart.

(a) *Out of band emissions.* The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.

(b) *Measurement procedure.* Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (*i.e.*, 100 kHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the

width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

(c) *Alternative out of band emission limit.* The licensee(s) of commercial aviation air-ground systems, together with affected licensees of Cellular Radiotelephone Service systems operating in the spectrum immediately below and adjacent to the commercial aviation air-ground bands, may establish an alternative out of band emission limit to be used at the 849 MHz and 894 MHz band edge(s) in specified geographical areas, in lieu of that set forth in this section, pursuant to a private contractual arrangement of all affected licensees and applicants. In this event, each party to such contract shall maintain a copy of the contract in their station files and disclose it to prospective assignees or transferees and, upon request, to the FCC.

(d) *Interference caused by out of band emissions.* If any emission from a transmitter operating in this service results in interference to users of another radio service, the FCC may require a greater attenuation of that emission than specified in this section.

[70 FR 19310, Apr. 13, 2005]

§ 22.863 Frequency stability.

The frequency stability of equipment used under this subpart shall be sufficient to ensure that, after accounting for Doppler frequency shifts, the occupied bandwidth of the fundamental emissions remains within the authorized frequency bands of operation.

[70 FR 19310, Apr. 13, 2005]

§ 22.867 Effective radiated power limits.

The effective radiated power (ERP) of ground and airborne stations operating on the frequency ranges listed in § 22.857 must not exceed the limits in this section.

(a) The peak ERP of airborne mobile station transmitters must not exceed 12 Watts.