

§ 25.219

47 CFR Ch. I (10–1–09 Edition)

geostationary satellite orbit as it appears at the particular earth station location:

15–10log ₁₀ (N)–25log ₁₀ θ	dBW/4 kHz	For	1.5° ≤ θ ≤ 7°
– 6–10log ₁₀ (N)	dBW/4 kHz	For	7° < θ ≤ 9.2°
18–10log ₁₀ (N)–25log ₁₀ θ	dBW/4 kHz	For	9.2° < θ ≤ 48°
– 24–10log ₁₀ (N)	dBW/4 kHz	For	48° < θ ≤ 180°

where θ and the plane of the geostationary satellite orbit are defined in paragraph (c)(1) of this section, and N is defined below. For the purposes of this section, the peak EIRP of an individual sidelobe may not exceed the envelope defined above for θ between 1.5° and 7.0°. For θ greater than 7.0°, the envelope may be exceeded by no more than 10% of the sidelobes, provided no individual sidelobe exceeds the envelope given above by more than 3 dB. For digital SCPC using frequency division multiple access (FDMA) or time divi-

sion multiple access (TDMA) technique, N is equal to one. For digital SCPC using code division multiple access (CDMA) technique, N is the maximum number of co-frequency simultaneously transmitting earth stations in the same satellite receiving beam.

(2) In all other directions, or in the plane of the horizon including any out-of-plane potential terrestrial interference paths:

18–10log ₁₀ (N)–25log ₁₀ θ	dBW/4 kHz	For	3° ≤ θ ≤ 48°
– 24–10log ₁₀ (N)	dBW/4 kHz	For	48° < θ ≤ 85°

where θ is defined in paragraph (c)(2) of this section and N is defined in paragraph (h)(1) of this section. For the purposes of this section, the envelope may be exceeded by no more than 10% of the sidelobes provided no individual sidelobe exceeds the envelope given above by more than 6 dB. The region of the main reflector spillover energy is to be interpreted as a single lobe and shall not exceed the envelope by more than 6 dB.

[73 FR 70902, Nov. 24, 2008]

EFFECTIVE DATE NOTE: At 74 FR 9962, Mar. 9, 2009, § 25.218, which contains information collection and recordkeeping requirements, became effective with approval by the Office of Management and Budget for a period of three years.

§ 25.219 [Reserved]

§ 25.220 Non-conforming transmit/receive earth station operations.

(a)(1) This section applies to earth station applications, other than ESV applications and 17/24 GHz BSS feeder link applications, in which the proposed earth station operations do not fall within the applicable off-axis EIRP envelope specified in Section 25.218 of this chapter.

(2) The requirements for petitions to deny applications filed pursuant to this section are set forth in § 25.154.

(b) If an antenna proposed for use by the applicant does not comply with the antenna performance standards contained in § 25.209(a) and (b), the applicant must provide, as an exhibit to its FCC Form 312 application, the antenna gain patterns specified in § 25.132(b).

(c) [Reserved]

(1) The applicant must provide in its Form 312, Schedule B, the power and power density levels that result by reducing the values stated in §§ 25.134, 25.211, or 25.212, whichever is applicable, by the number of decibels that the non-compliant antenna fails to meet the antenna performance standard of § 25.209(a) and (b), or

(2) The applicant will not be permitted to transmit to any satellite unless the applicant has provided the certifications listed in paragraph (e)(1) of this section from the operator of that satellite(s).

(3) The applicant will not receive protection from adjacent satellite interference from any satellite unless the applicant has provided the certifications listed in paragraph (d)(1) of this section from the operator of that satellite(s) from which it plans to receive.

(d)(1) The applicant must submit the certifications listed in paragraphs