

that it is capable of implementing a DoD required frequency change in accordance with a demonstration plan established by DoD and the NVNG licensee, upon the Commission's receipt of a written notification from NTIA describing such failure, the Commission shall impose additional conditions or requirements on the NVNG licensee's authorization as may be necessary to protect DoD operations in the 400.15–401 MHz downlink band until the Commission is notified by NTIA that the NVNG licensee has successfully demonstrated its ability to implement a DoD required frequency change. Such additional conditions or requirements may include, but are not limited to, requiring such NVNG licensee immediately to terminate its operations interfering with the DoD system.

[62 FR 59296, Nov. 3, 1997]

§ 25.261 Procedures for avoidance of in-line interference events for Non Geostationary Satellite Orbit (NGSO) Satellite Network Operations in the Fixed Satellite Service (FSS) Bands.

(a) *Applicable NGSO FSS Bands.* The coordination procedures in this section apply to non-Federal-Government NGSO FSS satellite networks operating in the following assigned frequency bands: The 28.6–29.1 GHz or 18.8–19.3 GHz frequency bands.

(b) *Definition of "In-line interference events."* For purposes of this section, an "in-line interference event" is defined as the interference associated with an occurrence of any physical alignment of space stations of two or more satellite networks with an operating Earth station of one of these networks in such a way that the angular separation between operational links of the two networks is less than 10° as measured at the Earth station.

(c) *Default procedure.* If no agreed coordination exists between two or more satellite networks, then the bands will be divided among the affected satellite networks involved in an in-line interference event in accordance with the following procedure:

(1) Each of *n* (number of) satellite networks involved in a particular in-line interference event shall select 1/*n* of the assigned spectrum available in

each frequency band for its home base spectrum. The selection order for each satellite network shall be determined by and be in accordance with the date that the first space station in each satellite network is launched and operating;

(2) The affected space station(s) of the respective satellite networks shall only operate in the selected (1/*n*) spectrum associated with its satellite network, its home base spectrum, for the duration of the in-line interference event;

(3) All affected space station(s) may resume operations throughout the assigned frequency bands once the angular separation between the affected space stations in the in-line interference event is again greater than 10°.

(d) *Coordination procedure.* Any coordination procedure agreed among the affected operating satellite networks, which allows operations of the satellite networks when each network's respective space stations are within the 10 degree avoidance angle associated with an in-line interference event, shall supersede the default procedure of paragraph (c) of this section. Coordination may be effected using information relating to the space stations and the parameters of one or more typical earth stations. All parties are required to coordinate in good faith.

[68 FR 59129, Oct. 14, 2003]

§ 25.262 Licensing and domestic coordination requirements for 17/24 GHz BSS space stations.

(a) Except as described in paragraphs (b), (c) or (e) of this section, applicants seeking to operate a space station in the 17/24 GHz BSS must locate that space station at one of the orbital positions described in Appendix F of the Report and Order adopted May 2, 2007, IB Docket No. 06–123, FCC 07–76.

(b) An applicant may be authorized to operate a 17/24 GHz BSS space station at an orbital location described in Appendix F as set forth in paragraph (a) of this section, or at a location with a geocentric angular separation of one degree or less from an Appendix F location, and may operate at the maximum power flux density limits defined in §§ 25.208(c) and (w) of this part, without

§ 25.271

47 CFR Ch. I (10–1–09 Edition)

coordinating its power flux density levels with adjacent licensed or permitted operators, only if there is no licensed 17/24 GHz BSS space station or prior-filed application at a location less than four degrees from the offset orbital location at which the applicant proposes to operate.

(c)(1) Notwithstanding the provisions of this section, licensees and permittees will be allowed to apply for a license or authorization for a replacement satellite that will be operated at the same power level and interference protection as the satellite to be replaced.

(2) In addition, applicants for licenses or authority for a satellite to be operated at an orbit location that was made available after a previous 17/24 GHz BSS license was cancelled or surrendered will be permitted to apply for authority to operate a satellite at the same power level and interference protection as the previous licensee at that orbit location, to the extent that their proposed operations are consistent with the provisions of this part. Such applications will be considered pursuant to the first-come, first-served procedures set forth in § 25.158 of this part.

(d) Any U.S. licensee or permittee using a 17/24 GHz BSS space station that is located less than four degrees away from a prior-authorized 17/24 GHz BSS space station that is authorized to operate in accordance with paragraph (b) of this section:

(1) may not cause any more interference to the adjacent satellite network than would be caused if the adjacent 17/24 GHz BSS space station were located four degrees away from the proposed space station; and

(2) must accept any increased interference that results from the adjacent space station network operating at the offset orbital location less than four degrees away.

(e) Any 17/24 GHz BSS U.S. licensee or permittee that is required to provide information in its application pursuant to §§ 25.140(b)(4)(ii) or (b)(4)(iii) of this part must accept any increased interference that may result from adjacent 17/24 GHz BSS space stations that are operating in compliance with the rules for this service.

(f) Any 17/24 GHz BSS U.S. licensee or permittee that does not comply with the power flux-density limits set forth in § 25.208(w) of this part shall bear the burden of coordinating with any future co-frequency licensees and permittees of a 17/24 GHz BSS network under the following circumstances:

(1) If the operator's space-to-Earth power flux-density levels exceed the power flux-density limits set forth in § 25.208(w) of this part by 3 dB or less, the operator shall bear the burden of coordinating with any future operators proposing a 17/24 GHz BSS space station in compliance with power flux-density limits set forth in § 25.208(w) of this part and located within ± 6 degrees of the operator's 17/24 GHz BSS space station.

(2) If the operator's space-to-Earth power flux-density levels exceed the power flux-density limits set forth in § 25.208(w) of this part by more than 3 dB, the operator shall bear the burden of coordinating with any future operators proposing a 17/24 GHz BSS space station in compliance with power flux-density limits set forth in § 25.208(w) of this part and located within ± 10 degrees of the operator's 17/24 GHz BSS space station.

(3) If no good faith agreement can be reached, the operator of the 17/24 GHz BSS satellite network that does not comply with § 25.208(w) of this part shall reduce its space-to-Earth power flux-density levels to be compliant with those specified in § 25.208(w) of this part.

[72 FR 60280, Oct. 24, 2007]

Subpart D—Technical Operations

SOURCE: 58 FR 13421, Mar. 11, 1993, unless otherwise noted.

§ 25.271 Control of transmitting stations.

(a) The licensee of a facility licensed under this part is responsible for the proper operation and maintenance of the station.

(b) The licensee of a transmitting earth station, other than an ESV, licensed under this part shall ensure that a trained operator is present on