

cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (*i.e.* 1 MHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power. With respect to television operations, measurements must be made of the separate visual and aural operating powers at sufficiently frequent intervals to ensure compliance with the rules.

(7) Alternative out of band emission limit. Licensees in this service may establish an alternative out of band emission limit to be used at specified band edge(s) in specified geographical areas, in lieu of that set forth in this section, pursuant to a private contractual arrangement of all affected licensees and applicants. In this event, each party to such contract shall maintain a copy of the contract in their station files and disclose it to prospective assignees or transferees and, upon request, to the FCC.

(n) When an emission outside of the authorized bandwidth causes harmful interference, the Commission may, at its discretion, require greater attenuation than specified in this section.

[62 FR 16497, Apr. 7, 1997, as amended at 65 FR 3147, Jan. 20, 2000; 65 FR 17602, Apr. 4, 2000; 65 FR 42883, July 12, 2000; 67 FR 5511, Feb. 6, 2002; 67 FR 41855, June 20, 2002; 69 FR 5715, Feb. 6, 2004; 69 FR 72033, Dec. 10, 2004; 69 FR 77950, Dec. 29, 2004; 70 FR 1190, Jan. 6, 2005; 70 FR 21664, Apr. 27, 2005; 71 FR 35190, June 19, 2006; 72 FR 48851, Aug. 24, 2007; 73 FR 26039, May 8, 2008]

§ 27.54 Frequency stability.

The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

§ 27.55 Power strength limits.

(a) *Field strength limits.* For the following bands, the predicted or measured median field strength at any location on the geographical border of a licensee's service area shall not exceed

the value specified unless the adjacent affected service area licensee(s) agree(s) to a different field strength. This value applies to both the initially offered service areas and to partitioned service areas.

(1) 2110–2155, 2305–2320 and 2345–2360 MHz bands: 47 dBμV/m.

(2) 698–758 and 775–787 MHz bands: 40 dBμV/m.

(3) The paired 1392–1395 MHz and 1432–1435 MHz bands and the unpaired 1390–1392 MHz band (1.4 GHz band): 47 dBμV/m.

(4) BRS and EBS: The predicted or measured median field strength at any location on the geographical border of a licensee's service area shall not exceed the value specified unless the adjacent affected service area licensee(s) agree(s) to a different field strength. This value applies to both the initially offered services areas and to partitioned services areas. Licensees may exceed this signal level where there is no affected licensee that is constructed and providing service. Once the affected licensee is providing service, the original licensee will be required to take whatever steps necessary to comply with the applicable power level at its GSA boundary, absent consent from the affected licensee.

(i) Prior to transition, the signal strength at any point along the licensee's GSA boundary does not exceed the greater of that permitted under the licensee's Commission authorizations as of January 10, 2005 or 47 dBμV/m.

(ii) Following transition, for stations in the LBS and UBS, the signal strength at any point along the licensee's GSA boundary must not exceed 47 dBμV/m. This field strength is to be measured at 1.5 meters above the ground over the channel bandwidth (*i.e.*, each 5.5 MHz channel for licensees that hold a full channel block, and for the 5.5 MHz channel for licensees that hold individual channels).

(iii) Following transition, for stations in the MBS, the signal strength at any point along the licensee's GSA boundary must not exceed the greater of $-73.0 + 10 \log(X/6)$ dBW/m², where X is the bandwidth in megahertz of the channel, or for facilities that are substantially similar to the licensee's pre-

transition facilities (including modifications that do not alter the fundamental nature or use of the transmissions), the signal strength at such point that resulted from the station's operations immediately prior to the transition, provided that such operations complied with paragraph (a)(4)(i) of this section.

(b) *Power flux density limit for stations operating in the 698–746 MHz bands.* For base and fixed stations operating in the 698–746 MHz band in accordance with the provisions of § 27.50(c)(6), the power flux density that would be produced by such stations through a combination of antenna height and vertical gain pattern must not exceed 3000 microwatts per square meter on the ground over the area extending to 1 km from the base of the antenna mounting structure.

(c) *Power flux density limit for stations operating in the 746–757 MHz, 758–763 MHz, 776–787 MHz, and 788–793 MHz bands.* For base and fixed stations operating in the 746–757 MHz, 758–763 MHz, 776–787 MHz, and 788–793 MHz bands in accordance with the provisions of § 27.50(b)(6), the power flux density that would be produced by such stations through a combination of antenna height and vertical gain pattern must not exceed 3000 microwatts per square meter on the ground over the area extending to 1 km from the base of the antenna mounting structure.

[69 FR 5715, Feb. 6, 2004, as amended at 69 FR 72034, Dec. 10, 2004; 72 FR 27712, May 16, 2007; 72 FR 48852, Aug. 24, 2007; 73 FR 26040, May 8, 2008]

§ 27.56 Antenna structures; air navigation safety.

A licensee that owns its antenna structure(s) must not allow such antenna structure(s) to become a hazard to air navigation. In general, antenna structure owners are responsible for registering antenna structures with the FCC if required by part 17 of this chapter, and for installing and maintaining any required marking and lighting. However, in the event of default of this responsibility by an antenna structure owner, the FCC permittee or licensee authorized to use an affected antenna structure will be held responsible by the FCC for ensuring

that the antenna structure continues to meet the requirements of part 17 of this chapter. See § 17.6 of this chapter.

(a) *Marking and lighting.* Antenna structures must be marked, lighted and maintained in accordance with part 17 of this chapter and all applicable rules and requirements of the Federal Aviation Administration. For any construction or alteration that would exceed the requirements of section 17.7 of this chapter, licensees must notify the appropriate Regional Office of the Federal Aviation Administration (FAA Form 7460–1) and file a request for antenna height clearance and obstruction marking and lighting specifications (FCC Form 854) with the FCC, WTB, 1270 Fairfield Road, Gettysburg, PA 17325.

(b) *Maintenance contracts.* Antenna structure owners (or licensees and permittees, in the event of default by an antenna structure owner) may enter into contracts with other entities to monitor and carry out necessary maintenance of antenna structures. Antenna structure owners (or licensees and permittees, in the event of default by an antenna structure owner) that make such contractual arrangements continue to be responsible for the maintenance of antenna structures in regard to air navigation safety.

§ 27.57 International coordination.

(a) WCS operations in the border areas shall be subject to coordination with those countries and provide protection to non-U.S. operations in the 2305–2320 and 2345–2360 MHz bands as appropriate. In addition, satellite DARS operations in WCS spectrum shall be subject to international satellite coordination procedures.

(b) Operation in the 698–763 MHz, 775–793 MHz, and 805–806 MHz bands is subject to international agreements between Mexico and Canada. Unless otherwise modified by international treaty, licenses must not cause interference to, and must accept harmful interference from, television broadcast operations in Mexico and Canada.

(c) Operation in the 1710–1755 MHz and 2110–2155 MHz bands is subject to