

Federal Communications Commission

§ 11.52

for the combined stations or systems with one EAS Encoder. The requirements of §11.32 must be met by the combined facility.

(m) EAS Participants are required to transmit all received EAS messages in which the header code contains the Event codes for Emergency Action Notification (EAN), Emergency Action Termination (EAT), and Required Monthly Test (RMT), and when the accompanying location codes include their State or State/county. These EAS messages shall be retransmitted unchanged except for the LLLLLLLL-code which identifies the EAS Participant retransmitting the message. See §11.31(c). If an EAS source originates an EAS message with the Event codes in this paragraph, it must include the location codes for the State and counties in its service area. When transmitting the required weekly test, EAS Participants shall use the event code RWT. The location codes are the state and county for the broadcast station city of license or system community or city. Other location codes may be included upon approval of station or system management. EAS messages may be transmitted automatically or manually.

(1) Automatic interrupt of programming and transmission of EAS messages are required when facilities are unattended. Automatic transmissions must include a permanent record that contains at a minimum the following information: Originator, Event, Location and valid time period of the message. The decoder performs the functions necessary to determine which EAS messages are automatically transmitted by the encoder.

(2) Manual interrupt of programming and transmission of EAS messages may be used. EAS messages with the EAN Event code must be transmitted immediately and Monthly EAS test messages within 60 minutes. All actions must be logged and include the minimum information required for EAS video messages.

(n) EAS Participants may employ a minimum delay feature, not to exceed 15 minutes, for automatic interruption of EAS codes. However, this may not be used for the EAN event which must be transmitted immediately. The delay

time for an RMT message may not exceed 60 minutes.

(o) Either manual or automatic operation of EAS equipment may be used by EAS Participants that use remote control. If manual operation is used, an EAS decoder must be located at the remote control location and it must directly monitor the signals of the two assigned EAS sources. If direct monitoring of the assigned EAS sources is not possible at the remote location, automatic operation is required. If automatic operation is used, the remote control location may be used to override the transmission of an EAS alert. EAS Participants may change back and forth between automatic and manual operation.

[70 FR 71035, Nov. 25, 2005, as amended at 71 FR 76220, Dec. 20, 2006; 72 FR 62135, Nov. 2, 2007; 71 FR 76220, Dec. 20, 2006; 72 FR 62135, Nov. 2, 2007]

§ 11.52 EAS code and Attention Signal Monitoring requirements.

(a) EAS Participants must be capable of receiving the Attention Signal required by §11.32(a)(9) and emergency messages of other broadcast stations during their hours of operation. EAS Participants must install and operate during their hours of operation, equipment capable of receiving and decoding, either automatically or manually, the EAS header codes, emergency messages and EOM code. EAS Participants must comply with these requirements by the dates set forth in §11.11.

NOTE TO PARAGRAPH (A): The two-tone Attention Signal will not be used to actuate two-tone decoders but will be used as an aural alert signal.

(b) If manual interrupt is used as authorized in §11.51(m)(2), decoders must be located so that operators at their normal duty stations can be alerted immediately when EAS messages are received.

(c) EAS Participants that are co-owned and co-located with a combined studio or control facility (such as an AM and FM licensed to the same entity and at the same location or a cable headend serving more than one system) may comply with the EAS monitoring requirements contained in this section for the combined station or system

with one EAS Decoder. The requirements of §11.33 must be met by the combined facility.

(d) EAS Participants must monitor two EAS sources. The monitoring assignments of each broadcast station and cable system and wireless cable system are specified in the State EAS Plan and FCC Mapbook. They are developed in accordance with FCC monitoring priorities.

(1) If the required EAS sources cannot be received, alternate arrangements or a waiver may be obtained by written request to the FCC's EAS office. In an emergency, a waiver may be issued over the telephone with a follow up letter to confirm temporary or permanent reassignment.

(2) The management of EAS Participants shall determine which header codes will automatically interrupt their programming for State and Local Area emergency situations affecting their audiences.

(e) EAS Participants are required to interrupt normal programming either automatically or manually when they receive an EAS message in which the header code contains the Event codes for Emergency Action Notification (EAN), Emergency Action Termination (EAT), and Required Monthly Test (RMT) for their State or State/county location.

(1) *Automatic* interrupt of programming is required when facilities are unattended. Automatic operation must provide a permanent record of the EAS message that contains at a minimum the following information: Originator, Event, Location and valid time period of the message.

(2) *Manual* interrupt of programming and transmission of EAS messages may be used. EAS messages with the EAN Event code must be transmitted immediately and Monthly EAS test messages within 60 minutes. All actions must be logged and recorded as specified in §§11.35(a) and 11.54(b)(13). Decoders must be programmed for the EAN and EAT Event header codes for National level emergencies and the RMT and RWT Event header codes for required monthly and weekly tests, with the appropriate accompanying State and State/county location codes.

[70 FR 71036, Nov. 25, 2005]

§ 11.53 Dissemination of Emergency Action Notification.

Initiation of the EAN by any one of the following sources is sufficient to begin the emergency actions in §11.54.

(a) *National Level.* The EAN is issued by the White House. The EAN message is sent from a government origination point to broadcast stations and other entities participating in the PEP system. It is then disseminated via EAS Participants.

(1) Radio and television broadcast stations.

(2) Cable systems and wireless cable systems.

(3) Other entities voluntarily participating in EAS.

(b) *State level and Local Area levels.* EAN dissemination arrangements at these levels originate from State and local governments in accordance with State and Local Area plans.

(c) Analog and digital broadcast stations must, prior to commencing routine operation or originating any emissions under program test, equipment test, experimental, or other authorizations, determine whether the EAS has been activated by monitoring the assigned EAS sources as specified in their State or Local plan.

[59 FR 67092, Dec. 28, 1994, as amended at 63 FR 29666, June 1, 1998; 65 FR 7640, Feb. 15, 2000; 65 FR 30001, May 10, 2000; 67 FR 18510, Apr. 16, 2002; 70 FR 71037, Nov. 25, 2005]

§ 11.54 EAS operation during a National Level emergency.

(a) The EAS Operating Handbook summarizes the procedures to be followed upon receipt of a National level EAN or EAT Message.

(b) Immediately upon receipt of an EAN message, EAS Participants must:

(1) Monitor the two EAS sources assigned in the State or Local Area plan or FCC Mapbook for any further instructions. SDARS licensees and DBS providers may choose their two EAS sources, one of which must be a PEP station.

(2) Discontinue normal programming and follow the transmission procedures in the appropriate section of the EAS Operating Handbook. Announcements may be made in the same language as the primary language of the EAS Participant.