

§ 20.18

carriers or comply with other reporting requirements, or with §§1.781 through 1.814 and 43.21 of this chapter; except that commercial radio service providers that offer broadband service, as described in §1.7001(a) of this chapter or mobile telephony are required to file reports pursuant to §§1.7000 and 43.11 of this chapter. For purposes of this section, *mobile telephony* is defined as real-time, two-way switched voice service that is interconnected with the public switched network utilizing an in-network switching facility that enables the provider to reuse frequencies and accomplish seamless handoff of subscriber calls.

(2) Seek authority for interlocking directors (section 212 of the Communications Act);

(3) Submit applications for new facilities or discontinuance of existing facilities (section 214 of the Communications Act).

(c) Commercial mobile radio service providers shall not file tariffs for international and interstate service to their customers, interstate access service, or international and interstate operator service. Sections 1.771 through 1.773 and part 61 of this chapter are not applicable to international and interstate services provided by commercial mobile radio service providers. Commercial mobile radio service providers shall cancel tariffs for international and interstate service to their customers, interstate access service, and international and interstate operator service.

(d) Except as specified as in paragraphs (d)(1) and (2), nothing in this section shall be construed to modify the Commission's rules and policies on the provision of international service under part 63 of this chapter.

(1) Notwithstanding the provisions of §63.21(c) of this chapter, a commercial mobile radio service provider is not required to comply with §42.10 of this chapter.

(2) A commercial mobile radio service (CMRS) provider that is classified as dominant under §63.10 of this chapter due to an affiliation with a foreign carrier is required to comply with §42.11 of this chapter if the affiliated foreign carrier collects settlement payments from U.S. carriers for termi-

47 CFR Ch. I (10–1–10 Edition)

nating U.S. international switched traffic at the foreign end of the route. Such a CMRS provider is not required to comply with §42.11, however, if it provides service on the affiliated route solely through the resale of an unaffiliated facilities-based provider's international switched services.

(3) For purposes of paragraphs (d)(1) and (2) of this section, *affiliated* and *foreign carrier* are defined in §63.09 of this Chapter.

(e) For obligations of commercial mobile radio service providers to provide local number portability, see §52.1 of this chapter.

[59 FR 18495, Apr. 19, 1994, as amended at 61 FR 38637, July 25, 1996; 63 FR 43040, Aug. 11, 1998; 65 FR 19685, Apr. 12, 2000; 65 FR 24654, Apr. 27, 2000; 66 FR 16879, Mar. 28, 2001; 69 FR 77938, Dec. 29, 2004]

§ 20.18 911 Service.

(a) *Scope of section.* The following requirements are only applicable to CMRS providers, excluding mobile satellite service (MSS) operators, to the extent that they:

(1) Offer real-time, two way switched voice service that is interconnected with the public switched network; and

(2) Utilize an in-network switching facility that enables the provider to reuse frequencies and accomplish seamless hand-offs of subscriber calls. These requirements are applicable to entities that offer voice service to consumers by purchasing airtime or capacity at wholesale rates from CMRS licensees.

(b) *Basic 911 Service.* CMRS providers subject to this section must transmit all wireless 911 calls without respect to their call validation process to a Public Safety Answering Point, or, where no Public Safety Answering Point has been designated, to a designated statewide default answering point or appropriate local emergency authority pursuant to §64.3001 of this chapter, provided that "all wireless 911 calls" is defined as "any call initiated by a wireless user dialing 911 on a phone using a compliant radio frequency protocol of the serving carrier."

(c) *TTY Access to 911 Services.* CMRS providers subject to this section must be capable of transmitting 911 calls

from individuals with speech or hearing disabilities through means other than mobile radio handsets, *e.g.*, through the use of Text Telephone Devices (TTY).

(d) *Phase I enhanced 911 services.* (1) As of April 1, 1998, or within six months of a request by the designated Public Safety Answering Point as set forth in paragraph (j) of this section, whichever is later, licensees subject to this section must provide the telephone number of the originator of a 911 call and the location of the cell site or base station receiving a 911 call from any mobile handset accessing their systems to the designated Public Safety Answering Point through the use of ANI and Pseudo-ANI.

(2) When the directory number of the handset used to originate a 911 call is not available to the serving carrier, such carrier's obligations under the paragraph (d)(1) of this section extend only to delivering 911 calls and available call party information, including that prescribed in paragraph (1) of this section, to the designated Public Safety Answering Point.

NOTE TO PARAGRAPH (d): With respect to 911 calls accessing their systems through the use of TTYS, licensees subject to this section must comply with the requirements in paragraphs (d)(1) and (d)(2) of this section, as to calls made using a digital wireless system, as of October 1, 1998.

(e) *Phase II enhanced 911 service.* Licensees subject to this section must provide to the designated Public Safety Answering Point Phase II enhanced 911 service, *i.e.*, the location of all 911 calls by longitude and latitude in conformance with Phase II accuracy requirements (*see* paragraph (h) of this section).

(f) *Phase-in for network-based location technologies.* Licensees subject to this section who employ a network-based location technology shall provide Phase II 911 enhanced service to at least 50 percent of their coverage area or 50 percent of their population beginning October 1, 2001, or within 6 months of a PSAP request, whichever is later; and to 100 percent of their coverage area or 100 percent of their population within 18 months of such a request or by October 1, 2002, whichever is later.

(g) *Phase-in for handset-based location technologies.* Licensees subject to this section who employ a handset-based location technology may phase in deployment of Phase II enhanced 911 service, subject to the following requirements:

(1) Without respect to any PSAP request for deployment of Phase II 911 enhanced service, the licensee shall:

(i) Begin selling and activating location-capable handsets no later than October 1, 2001;

(ii) Ensure that at least 25 percent of all new handsets activated are location-capable no later than December 31, 2001;

(iii) Ensure that at least 50 percent of all new handsets activated are location-capable no later than June 30, 2002; and

(iv) Ensure that 100 percent of all new digital handsets activated are location-capable no later than December 31, 2002, and thereafter.

(v) By December 31, 2005, achieve 95 percent penetration of location-capable handsets among its subscribers.

(vi) Licensees that meet the enhanced 911 compliance obligations through GPS-enabled handsets and have commercial agreements with resellers will not be required to include the resellers' handset counts in their compliance percentages.

(2) Once a PSAP request is received, the licensee shall, in the area served by the PSAP, within six months or by October 1, 2001, whichever is later:

(i) Install any hardware and/or software in the CMRS network and/or other fixed infrastructure, as needed, to enable the provision of Phase II enhanced 911 service; and

(ii) Begin delivering Phase II enhanced 911 service to the PSAP.

(3) For all 911 calls from portable or mobile phones that do not contain the hardware and/or software needed to enable the licensee to provide Phase II enhanced 911 service, the licensee shall, after a PSAP request is received, support, in the area served by the PSAP, Phase I location for 911 calls or other available best practice method of providing the location of the portable or mobile phone to the PSAP.

§ 20.18

47 CFR Ch. I (10–1–10 Edition)

(4) Licensees employing handset-based location technologies shall ensure that location-capable portable or mobile phones shall conform to industry interoperability standards designed to enable the location of such phones by multiple licensees.

(h) *Phase II accuracy.* (1) By September 11, 2012, licensees subject to this section shall comply with the following standards for Phase II location accuracy and reliability, to be tested and measured at the PSAP service area geographic level:

(i) For network-based technologies: 100 meters for 67 percent of calls, 300 meters for 95 percent of calls;

(ii) For handset-based technologies: 50 meters for 67 percent of calls, 150 meters for 95 percent of calls.

(iii) For the remaining 5 percent of calls, location attempts must be made and a location estimate must be provided to the appropriate PSAP.

(2) By the dates specified in this paragraph, carriers must satisfy the following requirements:

(i) By September 11, 2008, carriers must satisfy the location accuracy standards in paragraph (h)(1) of this section within each Economic Area (EA) in which that carrier operates;

(ii) By September 11, 2009, carriers must file with the Commission a report describing the status of their ongoing efforts to comply with § 20.18(h);

(iii) By September 11, 2010, carriers must:

(A) Satisfy the location accuracy standards in paragraph (h)(1) of this section within each Metropolitan Statistical Area (MSA) and Rural Service Area (RSA) in which that carrier operates;

(B) Demonstrate PSAP-level compliance with the location accuracy standards in paragraph (h)(1) of this section within at least 75% of the PSAPs the carrier serves; and

(C) Demonstrate accuracy in all PSAP service areas within at least 50% of the applicable location accuracy standard (*i.e.*, a carrier subject to the location accuracy standards in paragraph (h)(1)(ii) of this section must achieve location accuracy of 75 meters for 67 percent of calls in all PSAPs).

(iv) By September 11, 2011, carriers must file with the Commission a report

describing the status of their ongoing efforts to comply with § 20.18(h).

(v) By September 11, 2012, carriers must be in full compliance with § 20.18(h) at the PSAP service area level.

(3) In assessing their compliance with the requirements of this section, carriers must include only those PSAPs that are capable of receiving Phase II location data.

(i) *Reports on Phase II plans.* Licensees subject to this section shall report to the Commission their plans for implementing Phase II enhanced 911 service, including the location-determination technology they plan to employ and the procedure they intend to use to verify conformance with the Phase II accuracy requirements by November 9, 2000. Licensees are required to update these plans within thirty days of the adoption of any change. These reports and updates may be filed electronically in a manner to be designated by the Commission.

(j) *Conditions for enhanced 911 services—(1) Generally.* The requirements set forth in paragraphs (d) through (h) of this section shall be applicable only if the administrator of the designated Public Safety Answering Point has requested the services required under those paragraphs and the Public Safety Answering Point is capable of receiving and utilizing the data elements associated with the service and a mechanism for recovering the Public Safety Answering Point's costs of the enhanced 911 service is in place.

(2) *Commencement of six-month period.*

(i) Except as provided in paragraph (ii) of this section, for purposes of commencing the six-month period for carrier implementation specified in paragraphs (d), (f) and (g) of this section, a PSAP will be deemed capable of receiving and utilizing the data elements associated with the service requested, if it can demonstrate that it has:

(A) Ordered the necessary equipment and has commitments from suppliers to have it installed and operational within such six-month period; and

(B) Made a timely request to the appropriate local exchange carrier for the necessary trunking, upgrades, and other facilities.

(ii) For purposes of commencing the six-month period for carrier implementation specified in paragraphs (f) and (g) of this section, a PSAP that is Phase I-capable using a Non-Call Path Associated Signaling (NCAS) technology will be deemed capable of receiving and utilizing the data elements associated with Phase II service if it can demonstrate that it has made a timely request to the appropriate local exchange carrier for the ALI database upgrade necessary to receive the Phase II information.

(3) *Tolling of six-month period.* Where a wireless carrier has served a written request for documentation on the PSAP within 15 days of receiving the PSAP's request for Phase I or Phase II enhanced 911 service, and the PSAP fails to respond to such request within 15 days of such service, the six-month period for carrier implementation specified in paragraphs (d), (f), and (g) of this section will be tolled until the PSAP provides the carrier with such documentation.

(4) *Carrier certification regarding PSAP readiness issues.* At the end of the six-month period for carrier implementation specified in paragraphs (d), (f) and (g) of this section, a wireless carrier that believes that the PSAP is not capable of receiving and utilizing the data elements associated with the service requested may file a certification with the Commission. Upon filing and service of such certification, the carrier may suspend further implementation efforts, except as provided in paragraph (j)(4)(x) of this section.

(i) As a prerequisite to filing such certification, no later than 21 days prior to such filing, the wireless carrier must notify the affected PSAP, in writing, of its intent to file such certification. Any response that the carrier receives from the PSAP must be included with the carrier's certification filing.

(ii) The certification process shall be subject to the procedural requirements set forth in sections 1.45 and 1.47 of this chapter.

(iii) The certification must be in the form of an affidavit signed by a director or officer of the carrier, documenting:

(A) The basis for the carrier's determination that the PSAP will not be ready;

(B) Each of the specific steps the carrier has taken to provide the E911 service requested;

(C) The reasons why further implementation efforts cannot be made until the PSAP becomes capable of receiving and utilizing the data elements associated with the E911 service requested; and

(D) The specific steps that remain to be completed by the wireless carrier and, to the extent known, the PSAP or other parties before the carrier can provide the E911 service requested.

(iv) All affidavits must be correct. The carrier must ensure that its affidavit is correct, and the certifying director or officer has the duty to personally determine that the affidavit is correct.

(v) A carrier may not engage in a practice of filing inadequate or incomplete certifications for the purpose of delaying its responsibilities.

(vi) To be eligible to make a certification, the wireless carrier must have completed all necessary steps toward E911 implementation that are not dependent on PSAP readiness.

(vii) A copy of the certification must be served on the PSAP in accordance with §1.47 of this chapter. The PSAP may challenge in writing the accuracy of the carrier's certification and shall serve a copy of such challenge on the carrier. *See* §§1.45 and 1.47 and §§1.720 through 1.736 of this chapter.

(viii) If a wireless carrier's certification is facially inadequate, the six-month implementation period specified in paragraphs (d), (f) and (g) of this section will not be suspended as provided for in paragraph (j)(4) of this section.

(ix) If a wireless carrier's certification is inaccurate, the wireless carrier will be liable for noncompliance as if the certification had not been filed.

(x) A carrier that files a certification under paragraph (j)(4) of this section shall have 90 days from receipt of the PSAP's written notice that it is capable of receiving and utilizing the data elements associated with the service requested to provide such service in accordance with the requirements of

paragraphs (d) through (h) of this section.

(5) *Modification of deadlines by agreement.* Nothing in this section shall prevent Public Safety Answering Points and carriers from establishing, by mutual consent, deadlines different from those imposed for carrier and PSAP compliance in paragraphs (d), (f), and (g)(2) of this section.

(k) *Dispatch service.* A service provider covered by this section who offers dispatch service to customers may meet the requirements of this section with respect to customers who utilize dispatch service either by complying with the requirements set forth in paragraphs (b) through (e) of this section, or by routing the customer's emergency calls through a dispatcher. If the service provider chooses the latter alternative, it must make every reasonable effort to explicitly notify its current and potential dispatch customers and their users that they are not able to directly reach a PSAP by calling 911 and that, in the event of an emergency, the dispatcher should be contacted.

(l) *Non-service-initialized handsets.* (1) Licensees subject to this section that donate a non-service-initialized handset for purposes of providing access to 911 services are required to:

(i) Program each handset with 911 plus the decimal representation of the seven least significant digits of the Electronic Serial Number, International Mobile Equipment Identifier, or any other identifier unique to that handset;

(ii) Affix to each handset a label which is designed to withstand the length of service expected for a non-service-initialized phone, and which notifies the user that the handset can only be used to dial 911, that the 911 operator will not be able to call the user back, and that the user should convey the exact location of the emergency as soon as possible; and

(iii) Institute a public education program to provide the users of such handsets with information regarding the limitations of non-service-initialized handsets.

(2) Manufacturers of 911-only handsets that are manufactured on or after May 3, 2004, are required to:

(i) Program each handset with 911 plus the decimal representation of the seven least significant digits of the Electronic Serial Number, International Mobile Equipment Identifier, or any other identifier unique to that handset;

(ii) Affix to each handset a label which is designed to withstand the length of service expected for a non-service-initialized phone, and which notifies the user that the handset can only be used to dial 911, that the 911 operator will not be able to call the user back, and that the user should convey the exact location of the emergency as soon as possible; and

(iii) Institute a public education program to provide the users of such handsets with information regarding the limitations of 911-only handsets.

(3) *Definitions.* The following definitions apply for purposes of this paragraph.

(i) *Non-service-initialized handset.* A handset for which there is no valid service contract with a provider of the services enumerated in paragraph (a) of this section.

(ii) *911-only handset.* A non-service-initialized handset that is manufactured with the capability of dialing 911 only and that cannot receive incoming calls.

(m) *Reseller obligation.* (1) Beginning December 31, 2006, resellers have an obligation, independent of the underlying licensee, to provide access to basic and enhanced 911 service to the extent that the underlying licensee of the facilities the reseller uses to provide access to the public switched network complies with sections 20.18(d)–(g).

(2) Resellers have an independent obligation to ensure that all handsets or other devices offered to their customers for voice communications and sold after December 31, 2006 are capable of transmitting enhanced 911 information to the appropriate PSAP, in accordance with the accuracy requirements of section 20.18(i).

[63 FR 2637, Jan. 16, 1998, as amended at 64 FR 60130, Nov. 4, 1999; 64 FR 72956, Dec. 29, 1999; 65 FR 58661, Oct. 2, 2000; 65 FR 82295, Dec. 28, 2000; 66 FR 55623, Nov. 2, 2001; 67 FR 1648, Jan. 14, 2002; 67 FR 36117, May 23, 2002; 68 FR 2918, Jan. 22, 2003; 69 FR 2519, Jan. 16, 2004; 69 FR 6581, Feb. 11, 2004; 72 FR 27708, May 16, 2007; 73 FR 8625, Feb. 14, 2008]

EFFECTIVE DATE NOTES: 1. At 68 FR 2918, Jan. 22, 2003, § 20.18, paragraph (j) was revised. Paragraphs (j)(4) and (5) contain information collection and recordkeeping requirements and will not become effective until approval has been given by the Office of Management and Budget.

2. At 72 FR 27708, May 16, 2007, § 20.18, paragraph (a) was revised. The paragraph contains information collection and recordkeeping requirements and will not become effective until approval has been given by the Office of Management and Budget.

3. At 73 FR 8625, Feb. 14, 2008, § 20.18, paragraph (h) was revised. Paragraph (h) contains information collection and recordkeeping requirements and will not become effective until approval has been given by the Office of Management and Budget.

§ 20.19 Hearing aid-compatible mobile handsets.

(a) Scope of section; definitions. (1) The hearing aid compatibility requirements of this section apply to providers of digital CMRS in the United States to the extent that they offer real-time, two-way switched voice or data service that is interconnected with the public switched network and utilizes an in-network switching facility that enables the provider to reuse frequencies and accomplish seamless hand-offs of subscriber calls, and such service is provided over frequencies in the 800–950 MHz or 1.6–2.5 GHz bands using any air interface for which technical standards are stated in the standard document “American National Standard Methods of Measurement of Compatibility Between Wireless Communication Devices and Hearing Aids,” American National Standards Institute (ANSI) C63.19–2007 (June 8, 2007).

(2) The requirements of this section also apply to the manufacturers of the wireless handsets that are used in delivery of the services specified in paragraph (a)(1) of this section.

(3) *Definitions.* For purposes of this section:

(i) *Manufacturer* refers to a wireless handset manufacturer to which the requirements of this section apply.

(ii) *Model* refers to a wireless handset device that a manufacturer has designated as a distinct device model, consistent with its own marketing practices. However, if a manufacturer assigns different model device designations solely to distinguish units sold to

different carriers, or to signify other distinctions that do not relate to either form, features, or capabilities, such designations shall not count as distinct models for purposes of this section.

(iii) *Service provider* refers to a provider of digital CMRS to which the requirements of this section apply.

(iv) *Tier I carrier* refers to a CMRS provider that offers such service nationwide.

(b) *Hearing aid compatibility; technical standards.* A wireless handset used for digital CMRS only over the frequency bands and air interfaces referenced in paragraph (a)(1) of this section is hearing aid-compatible with regard to radio frequency interference or inductive coupling if it meets the applicable technical standard(s) set forth in paragraphs (b)(1) and (b)(2) of this section for all frequency bands and air interfaces over which it operates, and the handset has been certified as compliant with the test requirements for the applicable standard pursuant to § 2.1033(d) of this chapter. A wireless handset that incorporates a Wi-Fi air interface is hearing aid-compatible if the handset otherwise satisfies the requirements of this paragraph.

(1) For radio frequency interference.

(i) *Applicable technical standards prior to 2010.* Beginning June 6, 2008 and until January 1, 2010, a wireless handset submitted for equipment certification or for a permissive change relating to hearing aid compatibility must meet, at a minimum, the M3 rating associated with the technical standard set forth in either the standard document “American National Standard Methods of Measurement of Compatibility Between Wireless Communication Devices and Hearing Aids,” ANSI C63.19–2006 (June 12, 2006) or ANSI C63.19–2007 (June 8, 2007)—each available for purchase from the American National Standards Institute. Any grants of certification issued before June 6, 2008 under previous versions of ANSI C63.19 remain valid for hearing aid compatibility purposes.

(ii) *Applicable technical standards beginning in 2010.* On or after January 1, 2010, a wireless handset submitted for equipment certification or for a permissive change relating to hearing aid