

**Federal Communications Commission**

**§ 24.237**

NOTE TO §24.232: Height above average terrain (HAAT) is to be calculated using the method set forth in §24.53 of this part.

[73 FR 24183, May 2, 2008]

**§ 24.235 Frequency stability.**

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

**§ 24.236 Field strength limits.**

The predicted or measured median field strength at any location on the border of the PCS service area shall not exceed 47 dBuV/m unless the parties agree to a higher field strength.

**§ 24.237 Interference protection.**

(a) All licensees are required to coordinate their frequency usage with the co-channel or adjacent channel incumbent fixed microwave licensees in the 1850–1990 MHz band. Coordination must occur before initiating operations from any base station. Problems that arise during the coordination process are to be resolved by the parties to the coordination. Licensees are required to coordinate with all users possibly affected, as determined by appendix I to this subpart E (Appendix E of the Memorandum Opinion and Order, GEN Docket No. 90–314, FCC 94–144; TIA Telecommunications Systems Bulletin 10–F, “Interference Criteria for Micro-

wave Systems,” May 1994, (TSB10–F)); or an alternative method agreed to by the parties.

(b) The results of the coordination process need to be reported to the Commission only if the parties fail to agree. Because broadband PCS licensees are required to protect fixed microwave licensees in the 1850–1990 MHz band, the Commission will be involved in the coordination process only upon complaint of interference from a fixed microwave licensee. In such a case, the Commission will resolve the issues.

(c) In all other respects, coordination procedures are to follow the requirements of §101.103(d) of this chapter to the extent that these requirements are not inconsistent with those specified in this part.

(d) The licensee must perform an engineering analysis to assure that the proposed facilities will not cause interference to existing OFS stations within the coordination distance specified in Table 3 of a magnitude greater than that specified in the criteria set forth in paragraphs (e) and (f) of this section, unless there is prior agreement with the affected OFS licensee. Interference calculations shall be based on the sum of the power received at the terminals of each microwave receiver from all of the applicant’s current and proposed PCS operations.

TABLE 3—COORDINATION DISTANCES IN KILOMETERS

EIRP(W)	PCS Base Station Antenna HAAT in Meters												
	5	10	20	50	100	150	200	250	300	500	1000	1500	2000
0.1 .....	90	93	99	110	122	131	139	146	152	173	210	239	263
0.5 .....	96	100	105	116	128	137	145	152	158	179	216	245	269
1 .....	99	103	108	119	131	140	148	155	161	182	219	248	272
2 .....	120	122	126	133	142	148	154	159	164	184	222	250	274
5 .....	154	157	161	168	177	183	189	194	198	213	241	263	282
10 .....	180	183	187	194	203	210	215	220	225	240	268	291	310
20 .....	206	209	213	221	229	236	242	247	251	267	296	318	337
50 .....	241	244	248	255	264	271	277	282	287	302	331	354	374
100 .....	267	270	274	282	291	297	303	308	313	329	358	382	401
200 .....	293	296	300	308	317	324	330	335	340	356	386	409	436
500 .....	328	331	335	343	352	359	365	370	375	391	421	440	
1000 .....	354	357	361	369	378	385	391	397	402	418			
1200 .....	361	364	368	376	385	392	398	404	409	425			
1640 .....	372	375	379	388	397	404	410	416	421	437			
2400 .....	384	387	391	399	408	415	423	427	431				
3280 .....	396	399	403	412	419	427	435	439	446				

(e) For microwave paths of 25 kilometers or less, interference determinations shall be based on the C/I criteria

set forth in TIA Telecommunications Systems Bulletin 10–F, “Interference