### § 25.255

#### § 25.255 Procedures for resolving harmful interference related to operation of ancillary terrestrial components operating in the 1.5./1.6 GHz, 1.6/2.4 GHz and 2 GHz bands.

If harmful interference is caused to other services by ancillary MSS ATC operations, either from ATC base stations or mobile terminals, the MSS ATC operator must resolve any such interference. If the MSS ATC operator claims to have resolved the interference and other operators claim that interference has not been resolved, then the parties to the dispute may petition the Commission for a resolution of their claims.

[68 FR 33653, June 5, 2003]

### § 25.256 Special Requirements for operations in the 3.65–3.7 GHz band.

Upon request from a terrestrial licensee authorized under Subpart Z, Part 90 that seeks to place base and fixed stations in operation within 150 km of a primary earth station, licensees of earth stations operating on a primary basis in the fixed satellite service in the 3.65–3.7 GHz band must negotiate in good faith with that terrestrial licensee to arrive at mutually agreeable operating parameters to prevent unacceptable interference.

 $[70~{\rm FR}~24725,~{\rm May}~11,~2005]$ 

## § 25.257 Special requirements for operations in the band 29.1–29.25 GHz between NGSO MSS and LMDS.

- (a) Non-geostationary mobile satellite service (NGSO MSS) operators shall be licensed to use the 29.1–29.25 GHz band for Earth-to-space transmissions from feeder link earth station complexes. A "feeder link earth station complex" may include up to three (3) earth station groups, with each earth station group having up to four (4) antennas, located within a radius of 75 km of a given set of geographic coordinates provided by a NGSO MSS licensees or applicants pursuant to §101.147.
- (b) A maximum of seven (7) feeder link earth station complexes in the contiguous United States, Alaska and Hawaii may be placed into operation, in the largest 100 MSAs, in the band 29.1–29.25 GHz in accordance with §25.203 and §101.147 of this chapter.

- (c) One of the NGSO MSS operators licensed to use the 29.1–29.25 GHz band may specify geographic coordinates for a maximum of eight feeder link earth station complexes that transmit in the 29.1–29.25 GHz band. The other NGSO MSS operator licensed to use the 29.1–29.25 GHz band may specify geographic coordinates for a maximum of two feeder link earth station complexes that transmit in the 29.1–29.25 GHz band.
- (d) Additional NGSO MSS operators may be licensed in this band if the additional NGSO MSS operator shows that its system can share with the existing NGSO MSS systems.
- (e) All NGSO MSS operators shall cooperate fully and make reasonable efforts to identify mutually acceptable locations for feeder link earth station complexes. In this connection, any single NGSO MSS operator shall only identify one feeder link earth station complex protection zone in each category identified in §101.147(c)(2) of this chapter until the other NGSO MSS operator has been given an opportunity to select a location from the same category.

[61 FR 44181, Aug. 28, 1996]

### § 25.258 Sharing between NGSO MSS Feeder links Stations and GSO FSS services in the 29.25-29.5 GHz

- (a) Operators of NGSO MSS feeder link earth stations and GSO FSS earth stations in the band 29.25 to 29.5 GHz where both services have a co-primary allocation shall cooperate fully in order to coordinate their systems. During the coordination process both service operators shall exchange the necessary technical parameters required for coordination.
- (b) Licensed GSO FSS systems shall, to the maximum extent possible, operate with frequency/polarization selections, in the vicinity of operational or planned NGSO MSS feeder link earth station complexes, that will minimize instances of unacceptable interference to the GSO FSS space stations. Earth station licensees operating with GSO FSS systems shall be capable of providing earth station locations to support coordination of NGSO MSS feeder link stations under paragraphs (a) and

(c) of this section. Operation of ubiquitously deployed GSO FSS earth stations in the 29.25–29.5 GHz frequency band shall conform to the rules contained in §25.138.

(c) Applicants for authority to use the 29.25–29.5 GHz band for NGSO MSS feeder uplinks will have to demonstrate that their systems can share with GSO FSS and NGSO MSS systems that have been authorized for operation in that band.

[67 FR 37336, May 29, 2002, as amended at 68 FR 16967, Apr. 8, 2003]

# § 25.259 Time sharing between NOAA meteorological satellite systems and non-voice, non-geostationary satellite systems in the 137-138 MHz band.

(a) A non-voice, non-geostationary mobile-satellite service system licensee ("NVNG licensee") time-sharing spectrum in the 137-138 MHz frequency band shall not transmit signals into the "protection areas" of National Oceanic and Atmospheric Administration ("NOAA") satellite systems. When calculating the protection areas for a NOAA satellite in the 137.333-137.367 MHz, 137.485-137.515 MHz, 137.605-137.635 MHz and 137.753-137.787 MHz bands, a NVNG licensee shall use an earth station elevation angle of five degrees towards the NOAA satellite and will cease its transmissions prior to the NVNG licensee's service area, based on an elevation angle of zero degrees towards the NVNG licensee's satellite, overlapping the NOAA protection area. When calculating the protection areas for a NOAA satellite in the 137.025-137.175 MHz and 137.825-138 MHz bands, a NVNG licensee shall use an earth station elevation angle of zero degrees, or less if reasonably necessary, towards the NOAA satellite and will cease its transmissions prior to the NVNG licensee's service area, based on an elevation angle of zero degrees towards the NVNG licensee's satellite, overlapping the NOAA protection area. A NVNG licensee is responsible for obtaining the necessary ephemeris data. This information shall be updated system-wide on at least a weekly basis. A NVNG licensee shall use an orbital propagator algorithm with an accuracy

equal to or greater than the NORAD propagator used by NOAA.

(b) A NVNG licensee time sharing spectrum in the 137-138 MHz band shall establish a 24-hour per day contact person and telephone number so that claims of harmful interference into NOAA earth station users and other operational issues can be reported and resolved expeditiously. This contact information shall be made available to NOAA or its designee. If the National Telecommunications and Information Administration ("NTIA") notifies the Commission that NOAA is receiving unacceptable interference from a NVNG licensee, the Commission will require such NVNG licensee to terminate its interfering operations immediately unless it demonstrates to the Commission's reasonable satisfaction, and that of NTIA, that it is not responsible for causing harmful interference into the worldwide NOAA system. A NVNG licensee assumes the risk of any liability or damage that it and its directors, officers, employees, affiliates, agents and subcontractors may incur or suffer in connection with an interruption of its non-voice, non-geostationary mobile-satellite service, in whole or in part, arising from or relating to its compliance or noncompliance with the requirements of this paragraph (b). The Commission will not hesitate to impose sanctions on a NVNG licensee time-sharing spectrum in the 137-138 MHz band with NOAA, including monetary forfeitures and license revocations, when appropriate.

(c) Each satellite in a NVNG licensee's system time-sharing spectrum with NOAA in the 137–138 MHz band shall automatically turn off and cease satellite transmissions if, after 72 consecutive hours, no reset signal is received from the NVNG licensee's gateway earth station and verified by the satellite. All satellites in such NVNG licensee's system shall be capable of instantaneous shutdown on any sub-band upon command from such NVNG licensee's gateway earth station.

[62 FR 59296, Nov. 3, 1997]