

the mobiles within TV Channel 67, in which case TV Channels 61, 62, 63, 66, 67 and 68 must be protected). Control, fixed, and mobile stations shall keep a minimum distance of 96.5 kilometers (60 miles) from all adjacent channel TV/DTV stations. Since mobiles and portables are able to move and communicate with each other, licensees must determine the areas where the mobiles can and cannot roam in order to protect the TV/DTV stations.

NOTE TO § 27.60: The 88.5 km (55mi) Grade B service contour (64 dBuV/m) is based on a hypothetical TV station operating at an effective radiated power of one megawatt, a transmitting antenna height above average terrain of 610 meters (2000 feet) and the Commission's R-6602 F(50,50) curves. See § 73.699 of this chapter. Maximum facilities for TV stations operating in the UHF band are 5 megawatts effective radiated power at an antenna HAAT of 610 meters (2,000 feet). See § 73.614 of this chapter. The equivalent contour for DTV stations is based on a 41 dBuV/m signal strength and the distance to the F(50,90) curve. See § 73.625 of this chapter.

[72 FR 48852, Aug. 24, 2007]

§§ 27.61–27.62 [Reserved]

§ 27.63 Disturbance of AM broadcast station antenna patterns.

AWS and WCS licensees that construct or modify towers in the immediate vicinity of AM broadcast stations are responsible for measures necessary to correct disturbance of the AM station antenna pattern which causes operation outside of the radiation parameters specified by the FCC for the AM station, if the disturbance occurred as a result of such construction or modification.

(a) *Non-directional AM stations.* If tower construction or modification is planned within 1 kilometer (0.6 mile) of a non-directional AM broadcast station tower, the AWS or WCS licensee must notify the licensee of the AM broadcast station in advance of the planned construction or modification. Measurements must be made to determine whether the construction or modification would affect the AM station antenna pattern. The AWS or WCS licensee is responsible for the installation and continued maintenance of any detuning apparatus necessary to re-

store proper non-directional performance of the AM station tower.

(b) *Directional AM stations.* If tower construction or modification is planned within 3 kilometers (1.9 miles) of a directional AM broadcast station array, the AWS or WCS licensee must notify the licensee of the AM broadcast station in advance of the planned construction or modification. Measurements must be made to determine whether the construction or modification would affect the AM station antenna pattern. The AWS or WCS licensee is responsible for the installation and continued maintenance of any detuning apparatus necessary to restore proper performance of the AM station array.

[69 FR 5715, Feb. 6, 2004]

§ 27.64 Protection from interference.

Wireless Communications Service (WCS) stations operating in full accordance with applicable FCC rules and the terms and conditions of their authorizations are normally considered to be non-interfering. If the FCC determines, however, that interference which significantly interrupts or degrades a radio service is being caused, it may, after notice and an opportunity for a hearing, require modifications to any WCS station as necessary to eliminate such interference.

(a) *Failure to operate as authorized.* Any licensee causing interference to the service of other stations by failing to operate its station in full accordance with its authorization and applicable FCC rules shall discontinue all transmissions, except those necessary for the immediate safety of life or property, until it can bring its station into full compliance with the authorization and rules.

(b) *Intermodulation interference.* Licensees should attempt to resolve such interference by technical means.

(c) *Situations in which no protection is afforded.* Except as provided elsewhere in this part, no protection from interference is afforded in the following situations:

(1) *Interference to base receivers from base or fixed transmitters.* Licensees should attempt to resolve such interference by technical means or operating arrangements.