§ 74.791

- (2) For the origination of programming and commercial matter as defined in §74.701(1).
- (3) Whenever operating, a digital LPTV station must transmit an overthe-air video program signal at no direct charge to viewers at least comparable in resolution to that of its associated analog (NTSC) LPTV station or, in the case of an on-channel digital conversion, that of its former analog LPTV station.
- (4) A digital LPTV station may dynamically alter the bit stream of its signal to transmit one or more video program services in any established DTV video format.
- (h) A digital LPTV station is not subject to minimum required hours of operation and may operate in either of the two modes described in paragraph (g) of this section for any number of hours.
- (i) Upon transmitting a signal that meets the requirements of paragraph (g)(3) of this section, a digital LPTV station may offer services of any nature, consistent with the public interest, convenience, and necessity, on an ancillary or supplementary basis in accordance with the provisions of §73.624(c) and (g) of this chapter.
- (j) A digital LPTV station may not be operated solely for the purpose of relaying signals to one or more fixed receiving points for retransmission, distribution or relaying.
- (k) A digital LPTV station may receive input signals for transmission or retransmission by any technical means, including those specified in paragraph (b) of this section.

[69 FR 69334, Nov. 29, 2004]

§74.791 Digital call signs.

- (a) Digital low power stations. Call signs for digital low power stations will be made up of a prefix consisting of the initial letter K or W followed by the channel number assigned to the station and two additional letters and a suffix consisting of the letters -D.
- (b) Digital television translator stations. Call signs for digital television translator stations will be made up of a prefix consisting of the initial letter K or W followed by the channel number assigned to the station and two addi-

tional letters and a suffix consisting of the letter -D.

(c) Digital low power television stations and Class A television and Class A television stations. Digital low power television and Class A television stations may be assigned a call sign with a four-letter prefix pursuant to §73.3550 of the Commission's rules. Digital low power stations with four-letter prefixes will be assigned the suffix -LD and digital Class A stations with four-letter prefixes will be assigned the suffix -CD.

[69 FR 69335, Nov. 29, 2004]

§ 74.792 Digital low power TV and TV translator station protected contour

- (a) A digital low power TV or TV translator will be protected from interference from other low power TV, TV translator, Class A TV or TV booster stations or digital low power TV, TV translator or Class A TV stations within the following predicted contours:
- (1) 43 dBu for stations on Channels 2 through 6;
- (2) 48 dBu for stations on Channels 7 through 13; and
- (3) 51 dBu for stations on Channels 14 through 69.
- (b) The digital low power TV or TV translator protected contour is calculated from the authorized effective radiated power and antenna height above average terrain, using the F(50,90) signal propagation method specified in §73.625(b)(1) of this chapter.

 $[69 \; FR \; 69335, \; Nov. \; 29, \; 2004]$

§ 74.793 Digital low power TV and TV translator station protection of broadcast stations.

- (a) An application to construct a new digital low power TV or TV translator station or change the facilities of an existing station will not be accepted if it fails to meet the interference protection requirements in this section.
- (b) Except as provided in this section, interference prediction analysis is based on the interference thresholds (D/U signal strength ratios) and other criteria and methods specified in \$73.623(c)(2) through (c)(4) of this chapter. Predictions of interference to cochannel DTV broadcast, digital Class A