

**§ 80.955**

Operator's Certificate, or a First Class Radiotelegraph Operator's Certificate. Additionally, the technician must not be the vessel's owner, operator, master, or an employee of any of them. The results of the inspection must be recorded in the ship's radiotelephone log and include:

- (1) The date the inspection was conducted;
  - (2) The date by which the next inspection needs to be completed;
  - (3) The inspector's printed name, address, class of FCC license (including the serial number);
  - (4) The results of the inspection, including any repairs made; and
  - (5) The inspector's signed and dated certification that the vessel meets the requirements of the Great Lakes Agreement and the Bridge-to-Bridge Act contained in subparts T and U of this part and has successfully passed the inspection.
- (c) The vessel owner, operator, or ship's master must certify that the inspection required by paragraph (b) was satisfactory.
- (d) The ship's log must be retained on-board the vessel for at least two years from the date of the inspection.

[61 FR 25807, May 23, 1996]

**§ 80.955 Radiotelephone installation.**

- (a) Each U.S. flag vessel of less than 38 meters (124 feet) in length while subject to the Great Lakes Agreement must have a radiotelephone meeting the provisions of this subpart in addition to the other rules in this part governing ship stations using telephony.
- (b) Each U.S. flag vessel of 38 meters (124 feet) or more in length while subject to the Great Lakes Agreement must have a minimum of two VHF radiotelephone installations in operating condition meeting the provisions of this subpart. The second VHF installation must be electrically separate from the first VHF installation. However, both may be connected to the main power supply provided one installation can be operated from a separate power supply located as high as practicable on the vessel.
- (c) This paragraph does not require or prohibit the use of other frequencies for use by the same "radiotelephone in-

**47 CFR Ch. I (10-1-10 Edition)**

stallation" for communication authorized by this part.

**§ 80.956 Required frequencies and uses.**

- (a) Each VHF radiotelephone installation must be capable of transmitting and receiving G3E emission as follows:
    - (1) Channel 16—156.800 MHz—Distress, Safety and Calling; and
    - (2) Channel 6—156.300 MHz—Primary intership.
  - (b) The radiotelephone station must have additional frequencies as follows:
    - (1) Those ship movement frequencies appropriate to the vessel's area of operation: Channel 11—156.550 MHz, Channel 12—156.600 MHz, or Channel 14—156.700 MHz.
    - (2) The navigational bridge-to-bridge frequency, 156.650 MHz (channel 13).
    - (3) Such other frequencies as required for the vessel's service.
    - (4) One channel for receiving marine navigational warnings for the area of operation.
  - (c) Every radiotelephone station must include one or more transmitters, one or more receivers, one or more sources of energy and associated antennas and control equipment. The radiotelephone station, exclusive of the antennas and source of energy, must be located as high as practicable on the vessel, preferably on the bridge, and protected from water, temperature, and electrical and mechanical noise.
- [51 FR 31213, Sept. 2, 1986, as amended at 53 FR 17052, May 13, 1988]
- § 80.957 Principal operating position.**
- (a) The principal operating position of the radiotelephone installation must be on the bridge, convenient to the conning position.
  - (b) When the radiotelephone station is not located on the bridge, operational control of the equipment must be provided at the location of the radiotelephone station and at the bridge operating position. Complete control of the equipment at the bridge operating position must be provided.
- § 80.959 Radiotelephone transmitter.**
- (a) The transmitter must be capable of transmission of G3E emission on the required frequencies.