§87.301 Supplemental eligibility.

- (a) The following entities are eligible for flight test station licenses:
- (1) Manufacturers of aircraft or major aircraft components;
- (2) A parent corporation or its subsidiary if either corporation is a manufacturer of aircraft or major aircraft components: or
- (3) Educational institutions and persons primarily engaged in the design, development, modification, and flight test evaluation of aircraft or major aircraft components.
- (b) Each application must include a certification sufficient to establish the applicant's eligibility under the criteria in paragraph (a) of this section.

[53 FR 28940, Aug. 1, 1988, as amended at 63 FR 68957, Dec. 14, 1998]

§87.303 Frequencies.

(a) These frequencies are available for assignment to flight test land and aircraft stations:

(b) These additional frequencies are available for assignment only to flight test stations of aircraft manufacturers:

123.125 ²	123.275^{3}	S123.4253	123.550 ³
123.150 ²	123.325^{3}	S123.4753	123.575 ²
123.250^{3}	123.350^{3}	S123.5253	

¹When R3E, H3E or J3E emission is used, the assigned frequency will be 3282.4 kHz (3281.0 kHz car-

rier frequency). 2 This frequency is available only to itinerant stations that have a requirement to be periodically transferred to various locations. 3 Mobile station operations on these frequencies are limited to an area within \$20 km (200 mi) of an area with the power of the control of t

associated flight test land station.

(c) These frequencies are available for equipment test, emergency and backup use with aircraft beyond the range of VHF propagation. Either H2B, J3E, J7B or J9W emission may be used. Frequencies (carrier) available kHz:

	кНz
2851.0	8822.0
3004.0	10045.0
3443.0	11288.0
5451.0	11306.0
5469.0	13312.0
5571.0	17964.0
6550 O	21021 0

(d)(1) Frequencies in the bands 1435-1525 MHz and 2360-2395 MHz are assigned in the mobile service primarily for aeronautical telemetry and associ-

ated telecommand operations for flight testing of aircraft and missiles, or their major components. The bands 2310-2320 MHz and 2345-2360 MHz are also available for these purposes on a secondary basis. Permissible uses of these bands include telemetry and associated telecommand operations associated with the launching and reentry into the Earth's atmosphere, as well as any incidental orbiting prior to reentry, of objects undergoing flight tests. In the band 1435-1525 MHz, the following frequencies are shared with flight telemetry mobile stations: 1444.5, 1453.5, 1501.5, 1515.5, and 1524.5 MHz. In the band 2360-2395 MHz, the following frequencies may be assigned for telemetry and associated telecommand operations of expendable and re-usable launch vehicles, whether or not such operations involve flight testing: 2364.5, 2370.5 and 2382.5 MHz. In the band 2360-2395 MHz, all other mobile telemetry uses shall not cause harmful interference to, or claim protection from interference from, the above uses

(2) The authorized bandwidths for stations operating in the bands 1435.0-1525.0 MHz, 1525.0-1535.0 MHz and 2310.0-2390.0 MHz are normally 1, 3 or 5 MHz. Applications for greater bandwidths will be considered in accordance with the provisions of §87.135. Each assignment will be centered on a frequency between 1435.5 MHz and 1534.5 MHz or between 2310.5 MHz and 2389.5 MHz, with 1 MHz channel spacing.

(e) 121.500 MHz: Emergency and distress only

[53 FR 28940, Aug. 1, 1988, as amended at 55 FR 4175, Feb. 7, 1990; 58 FR 44954, Aug. 25, 1993; 58 FR 67696, Dec. 22, 1993; 60 FR 37829, July 24, 1995; 62 FR 11107, Mar. 11, 1997; 68 FR 74388, Dec. 23, 2003; 69 FR 77950, Dec. 29, 2004; 71 FR 29818, May 24, 2006]

§87.305 Frequency coordination.

(a)(1) Each application for a new station license, renewal or modification of an existing license concerning flight test frequencies, except as provided in paragraph (b) of this section, must be accompanied by a statement from a frequency advisory committee. The committee must comment on the frequencies requested or the proposed changes in the authorized station and the probable interference to existing