public communications facilities. Entities not meeting these eligibility criteria may also be licensed in the Public Safety Radio Pool solely to provide service to eligibles on one-way paging-only frequencies below 800 MHz, *i.e.*, those frequencies with the assignment limitations appearing at §90.20(d)(13) or (d)(60). Private carrier systems licensed on other channels prior to June 1, 1990, may continue to provide radio communications service to eligibles. Rules as to eligibility for licensing, frequencies available, permissible communications and classes and number of stations, and any special requirements are set forth in the following sections.

§ 90.16 Public Safety National Plan.

The Commission has established a National Plan which specifies special policies and procedures governing the Public Safety Pool (formally Public Safety Radio Services and the Special Emergency Radio Service). The National Plan is contained in the Report and Order in General Docket No. 87-112. The principal spectrum resource for the National Plan is the 806-809 MHz and the 851-854 MHz bands at locations farther then 110 km (68.4 miles) from the U.S./Mexico border and 140 km (87 miles) from the U.S./Canadian border ("border regions"). In the border regions, the principal spectrum for the National Plan may be different. The National plan establishes planning regions covering all parts of the United States, Puerto Rico, and the U.S. Virgin Islands. No assignments will be made in the spectrum designated for the National Plan until a regional plan for the area has been accepted by the Commission.

[69 FR 67837, Nov. 22, 2004]

§ 90.18 Public Safety 700 MHz Nationwide Broadband Network.

The 763-768/793-798 MHz band is dedicated to a broadband public safety communications system with a nation-wide level of interoperability. A nationwide license for this spectrum is held by a single entity, the Public Safety Broadband Licensee, which must enter into the 700 MHz Public/Private Partnership with the licensee of the adjacent Upper 700 MHz D Block license, pursuant to a Network Sharing

Agreement and such other agreements as the Commission may require. The specific provisions relating to the 700 MHz Public/Private Partnership are set forth in subpart AA of this part and subpart N of part 27. The Public Safety 700 MHz Nationwide Broadband Network is established in the Second Report and Order in PS Docket No. 06–229.

[72 FR 48859, Aug. 24, 2007]

§ 90.20 Public Safety Pool.

- (a) *Eligibility*. The following are eligible to hold authorizations in the Public Safety Pool.
- (1) Any territory, possession, state, city, county, town or similar governmental entity is eligible to hold authorizations in the Public Safety Pool to operate radio stations for transmission of communications essential to official activities of the licensee, including:
 - (i) A district and an authority;
- (ii) A governmental institution authorized by law to provide its own police protection;
- (iii) Persons or entities engaged in the provision of basic or advanced life support services on an ongoing basis are eligible to hold authorization to operate stations for transmission of communications essential for the delivery or rendition of emergency medical services for the provision of basic or advanced life support. Applications submitted by persons or organizations (governmental or otherwise) other than the governmental body having jurisdiction over the state's emergency medical service plans must be accompanied by a statement prepared by the governmental body having jurisdiction over the state's emergency medical services plan indicating that the applicant is included in the state's emergency plan or otherwise supporting the application;
- (iv) Governmental entities and governmental agencies for their own medical activities; and
- (v) Governmental entities and governmental agencies for providing medical services communications to other eligible persons through direct participation in and direct operational control of the system, such as through central dispatch service.

- (2) Persons or organizations other than governmental entities are eligible to hold authorizations in the Public Safety Pool to operate radio stations for transmission of communications, as listed below. When requesting frequencies not designated by a "PS" in the coordinator column of the frequency table in paragraph (c)(3) of this section, applications must be accompanied by a statement from the governmental entity having legal jurisdiction over the area to be served, supporting the request:
- (i) Persons or organizations charged with specific fire protection activities;
- (ii) Persons or organizations charged with specific forestry-conservation activities;
- (iii) Persons or organizations, listed below, engaged in the delivery or rendition of medical services to the public and on a secondary basis, for transmission of messages related to the efficient administration of organizations and facilities engaged in medical services operations:
- (A) Hospital establishments that offer services, facilities, and beds for use beyond 24 hours in rendering medical treatment;
- (B) Institutions and organizations regularly engaged in providing medical services through clinics, public health facilities, and similar establishments;
- (C) Ambulance companies regularly engaged in providing medical ambulance services;
- (D) Rescue organizations for the limited purpose of participation in providing medical services;
- (E) Associations comprised of two or more of the organizations eligible under paragraph (a)(2)(iii) (A), (B), (C), and (D) of this section, for the purpose of active participation in and direct operational control of the medical services communication activities of such organizations; or
- (F) Physicians, schools of medicine, oral surgeons, and associations of physicians or oral surgeons;
- (iv) Persons or organizations operating a rescue squad for transmission of messages pertaining to the safety of life or property and urgent messages necessary for the rendition of an efficient emergency rescue service.

- (A) Each rescue squad will normally be authorized to operate one base station, and a number of mobile units (excluding hand carried mobile units) not exceeding the number of vehicles actually used in emergency rescue operations.
- (B) In addition, each rescue squad will be authorized to operate a number of hand carried mobile units not exceeding two such units for each radio equipped vehicle actually used in emergency rescue operations.
- (v) Persons with disabilities. The initial application from a person claiming eligibility under this paragraph shall be accompanied by a statement from a physician attesting to the condition of the applicant or the applicant's child (or ward in case of guardianship).
- (A) Any person having a hearing deficiency such that average hearing threshold levels are 90 dB above ANSI (American National Standards Institute) 1969 or ISO (International Standards Organization) 1964 levels and such other persons who submit medical certification of similar hearing deficiency.
- (B) Any person having visual acuity corrected to no better than 20/200 in the better eye or having a field of vision of less than 20 degrees.
- (C) Any person, who, through loss of limbs or motor function, is confined to a wheelchair, or is non-ambulatory.
- (D) Any person actively awaiting an organ transplant.
- (E) Parents or guardians of persons under 18 years eligible under paragraphs (a)(2)(v)(A), (a)(2)(v)(B), (a)(2)(v)(C) of this section, or institutions devoted to the care or training of those persons.
- (vi) A veterinarian, veterinary clinic, or a school of veterinary medicine for the transmission of messages pertaining to the care and treatment of animals. Each licensee may be authorized to operate one base station and two mobile units. Additional base stations or mobile units will be authorized only on a showing of need.
- (vii) Organizations established for disaster relief purposes having an emergency radio communications plan for the transmission of communications relating to the safety of life or property, the establishment and maintenance of temporary relief facilities,

and the alleviation of the emergency situation during periods of actual or impending emergency, or disaster, and until substantially normal conditions are restored. In addition, the stations may be used for training exercises, incidental to the emergency communications plan, and for operational communications of the disaster relief organization or its chapter affiliates. The initial application from a disaster relief organization shall be accompanied by a copy of the charter or other authority under which the organization was established and a copy of its communications plan. The plan shall fully describe the operation of the radio facilities and describe the method of integration into other communications facilities which normally would be available to assist in the alleviation of the emergency condition.

(viii) Persons or organizations operating school buses on a regular basis over regular routes for the transmission of messages pertaining to either the efficient operation of the school bus service or the safety or general welfare of the students they are engaged in transporting. Each school bus operator may be authorized to operate one base station and a number of mobile units not in excess of the total of the number of buses and maintenance vehicles regularly engaged in the school bus operation. Additional base stations or mobile units will be authorized only in exceptional circumstances when the applicant can show a specific need.

(ix) Persons or organizations operating beach patrols having responsibility for life-saving activities for the transmission of messages required for the safety of life or property.

(x) Persons or organizations maintaining establishment in isolated areas where public communications facilities are not available and where the use of radio is the only feasible means of establishing communication with a center of population, or other point from which emergency assistance might be obtained if needed, for the transmission of messages only during an actual or impending emergency endangering life, health or property for the transmission of essential communications arising from the emergency. The

transmission of routine or non-emergency communications is strictly prohibited.

(A) Special eligibility showing. The initial application requesting a station authorization for an establishment in an isolated area shall be accompanied by a statement describing the status of public communication facilities in the area of the applicant's establishment; the results of any attempts the applicant may have made to obtain public communication service, and; in the event radio communications service is to be furnished under paragraph (a)(2)(x)(C)(2) of this section, a copy of the agreement involved must be submitted.

(B) Class and number of stations available. Persons or organizations in this category may be authorized to operate not more than one fixed station at any isolated establishment and not more than one fixed station in a center of population.

(C) Communication service rendered and received. (1) The licensee of a station at any establishment in an isolated area shall make the communication facilities of such station available at no charge to any person desiring the transmission of any communication permitted by paragraph (a) of this section.

(2) For the purpose of providing the communications link desired the licensee of a station at an establishment in an isolated area either may be the licensee of a similar station at another location or may obtain communication service under a mutual agreement from the licensee of any station in the Public Safety Pool or any other station which is authorized to communicate with the fixed station.

(xi) A communications common carrier operating communications circuits that normally carry essential communication of such a nature that their disruption would endanger life or public property is eligible to hold authorizations for standby radio facilities for the transmission of messages only during periods when the normal circuits are inoperative due to circumstances beyond the control of the user. During such periods the radio facilities may be used to transmit any communication which would be carried by the regular

circuit. Initial applications for authorization to operate a standby radio facility must include a statement describing radio communication facilities desired, the proposed method of operation, a description of the messages normally being carried, and an explanation of how their disruption will endanger life or public property.

(xii) Communications common carriers for radio facilities to be used in effecting expeditious repairs to interruption of public communications facilities where such interruptions have resulted in disabling intercity circuits or service to a multiplicity of subscribers in a general area. Stations authorized under this section may be used only when no other means of communication is readily available, for the transmission of messages relating to the safety of life and property and messages which are necessary for the efficient restoration of the public communication facilities which have been disrupted.

(xiii) Persons or entities engaged in the provision of basic or advanced life support services on an ongoing basis are eligible to hold authorization to operate stations for transmission of communications essential for the delivery or rendition of emergency medical services for the provision of basic or advanced life support. Applications submitted by persons or organizations (governmental or otherwise) other than the governmental body having jurisdiction over the state's emergency medical service plans must be accompanied by a statement prepared by the governmental body having jurisdiction over the state's emergency medical services plan indicating that the applicant is included in the state's emergency plan or otherwise supporting the application.

(b) International police radiocommunication. Police licensees which are located in close proximity to the borders of the United States may be authorized to communicate internationally. Request for such authority shall be written and signed and submitted in duplicate. The request shall include information as to the station with which communication will be conducted, and the frequency, power, emission, etc., that will be used. If authorized, such international communication must be conducted in accordance with Article 5 of the Inter-American Radio Agreement, Washington, DC, 1949, which reads as follows:

Article 5. *Police radio stations.* When the American countries authorize their police radio stations to exchange emergency information by radio with similar stations of another country, the following rules shall be applied.

- (a) Only police radio stations located close to the boundaries of contiguous countries shall be allowed to exchange this information.
- (b) In general, only important police messages shall be handled, such as those which would lose their value, because of slowness and time limitations if sent on other communication systems.
- (c) Frequencies used for radiotelephone communications with mobile police units shall not be used for radiotelegraph communications.
- (d) Radiotelephone communications shall be conducted only on frequencies assigned for radiotelephony.
- (e) Radiotelegraph communications shall be conducted on the following frequencies: 2804 kHz calling, 2808 kHz working, 2812 kHz working, 5195 kHz day calling, 5185 kHz day working, 5140 kHz day working.

(f) The characteristics of police radio stations authorized to exchange information shall be notified to the International Telecommunication Union, Geneva, Switzerland.

(g) The abbreviations contained in Appendix 9 of the Atlantic City Radio Regulations shall be used to the greatest possible extent. Service indications are as follows: "P", priority, for messages that are to be sent immediately, regardless of the number of other messages on file. If no service indication is given, the messages are to be transmitted in the order of receipt.

(h) The message shall contain the preamble, address, text and signature, as follows:

Preamble. The preamble of the message shall consist of the following: The serial number preceded by the letters "NR", service indications, as appropriate; the group count according to standard cable count system; the letters "CK", followed by numerals indicating the number of words contained in the text of the message: Office and country of origin (not abbreviations): Day, month, and hour of filing;

Address. The address must be as complete as possible and shall include the name of the addressee with any supplementary particulars necessary for immediate delivery of the message;

Text. The text may be either in plain language or code;

Limitations

Coordi-

§ 90.20

Signature. The signature shall include the name and title of the person originating the message.

(c) Public Safety frequencies. (1) The following table indicates frequencies available for assignment to Public Safety stations, together with the class of station(s) to which they are normally assigned, the specific assignment limitations which are explained in paragraph (d) of this section, and the certified frequency coordinator for each frequency:

(2)(i) The letter symbol(s) listed in the Coordinator column of the frequency table in paragraph (c)(3) of this section specifies the frequency coordinator(s) for each frequency as follows:

PF—Fire Coordinator
PH—Highway Maintenance Coordinator
PM—Emergency Medical Coordinator
PO—Forestry-Conservation Coordinator
PP—Police Coordinator
PS—Special Emergency Coordinator
PX—Any Public Safety Coordinator, except
the Special Emergency Coordinator

(ii) Frequencies without any coordinator specified may be coordinated by any coordinator certified in the Public Safety Pool.

(3) Frequencies.

PUBLIC SAFETY POOL FREQUENCY TABLE

Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
	Kilohertz		
530 to 1700	Base (T.I.S.) Base (T.I.S.)	1	PX PX PP PP PP PO PO PO PO PP PP PP PP PP PP
30.86 30.90 30.94	Base or mobiledodo	7 7 7	PO PO PO

PUBLIC SAFETY POOL FREQUENCY TABLE— Continued

Class of station(s)

Frequency or band

band	tion(s)		nator
00.00	d.	-	PO
30.98	do	7	
31.02	do	7	PO
31.06	do	7, 8, 9	PO
31.10	do	7, 8, 9	PO
31.14	do	7, 8, 9	PO
31.18	do	8, 9	PO
31.22	do	8, 9	PO
31.26	do	8, 9	PO
31.30	do	8, 9	PO
31.34	do	8, 9	PO
31.38	do	8, 9	PO
31.42	do	8, 9	PO
31.46	do	8, 9	PO
31.50	do	8, 9	PO
31.54	do	8, 9	PO
31.58	do	8, 9	PO
31.62	do	8, 9	PO
31.66	do	8, 9	PO
31.70	do	8, 9	PO
31.74	do	8, 9	PO
31.78	do	8, 9	PO
31.82	do	8, 9	PO
31.86	do	8, 9	PO
31.90	do	8, 9	PO
31.94	do	8, 9	PO
31.98	do	8, 9	PO
33.02	do	10	PH, PS
33.04	do		PS
33.06	do	10	PH, PS
33.08	do		PS
33.10	do	10	PH, PS
33.42	Mobile or fixed	11	PF
33.44	Base or mobile		PF
33.46	Mobile		PF
33.48	Base or mobile		PF
33.50	Mobile		PF
33.52	Base or mobile		PF PF
33.54	Mobile		PF PF
33.56	Base or mobile		PF
33.58	Mobile		PF
33.60 33.62	Base or mobile		PF PF
	Mobile Base or mobile		PF
33.64			PF
33.66	Mobile Base or mobile		PF
33.68	do		PF
33.70 33.72	do		PF
33.74	do		PF
33.76	do		PF
33.78	do		PF
33.80	do		PF
33.82	do		PF
	do		PF
33.84 33.86	do		PF
33.88	do		PF
33.90	do		PF
33.92	do		PF
33.94	do		PF
33.96	do		PF
33.98	do		PF
35.02	Mobile	12, 78	PS
35.64	Base	13	PS
35.68	do	13	PS
37.02	Mobile	13	PP
37.04	Base or mobile		PP
37.06	do		PP
37.08	do		PP
37.10	do		PX
37.12	do		PP
37.14	do		PP
J1.17			

PUBLIC SAFETY POOL FREQUENCY TABLE— Continued

PUBLIC SAFETY POOL FREQUENCY TABLE— Continued

Continued				Oontinaca				
Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	
37.16	do		PP	42.06	do	2, 3, 16	PP	
37.18	do		PX	42.08	do	2, 3, 16	PP	
37.20	do		PP	42.10	do	2, 3, 16	PP	
37.22	do		PP	42.12	do	2, 3, 16	PP	
37.24	do		PP	42.14	do	2, 3, 16	PP	
37.26	do		PX	42.16	do	2, 3, 16	PP	
37.28	do		PP	42.18	Mobile	2, 16	PP	
37.30	do		PP	42.20	do	2, 16	PP	
37.32	do		PP	42.22	do	2, 16	PP	
37.34	Mobile		PP	42.24	do	2, 16	PP	
37.36	Base or mobile		PP	42.26	do	2, 16	PP	
37.38	Mobile		PP	42.28	do	2, 16	PP	
37.40	Base or mobile		PP	42.30	do	2, 16	PP	
37.42	Mobile		PP DU DC	42.32	Base or mobile	2, 3, 16	PP	
37.90 37.92	Base or mobile	10	PH, PS PH	42.34 42.36	dodo	2, 3, 16	PP PP	
37.94	do	10	PH, PS	42.38	do	2, 3, 16	PP	
37.96	do		PH	42.40	do	2, 3, 16,	PP	
37.98	do	10	PH, PS	72.70		17.	' '	
39.02	do		PP	42.42	do	2, 3, 16	PP	
39.04	do		PP	42.44	do	2, 3, 16	PP	
39.06	do	14	PX	42.46	do	2, 3, 16	PP	
39.08	do		PP	42.48	do	2, 3, 16	PP	
39.10	do		PX	42.50	do	2, 3, 16	PP	
39.12	do		PP	42.52	do	2, 3, 16	PP	
39.14	do		PP	42.54	do	2, 3, 16	PP	
39.16	do		PP	42.56	do	2, 3, 16	PP	
39.18	do		PX	42.58	do	2, 3, 16	PP	
39.20	do		PP	42.60	do	2, 3, 16	PP	
39.22	do		PP	42.62	do	2, 3, 16	PP	
39.24	do		PP	42.64	do	2, 3, 16	PP	
39.26	Mobile		PP	42.66	Mobile	2, 16	PP	
39.28	Base or mobile		PP PP	42.68	do	2, 16	PP PP	
39.30 39.32	Mobile Base or mobile		PP	42.70	do	2, 16	PP	
39.34	Mobile		PP	42.72	do	2, 16	PP	
39.36	Base or mobile		PP	42.74 42.76	dodo	2, 16 2, 16	PP	
39.38	Mobile		PP	42.78	do	2, 16	PP	
39.40	Base or mobile		PP	42.80	Base or mobile	13	PP	
39.42	do		PP	42.82	do	2, 3, 16	PP	
39.44	do		PP	42.84	do	2, 3, 16	PP	
39.46	do	15	PP	42.86	do	2, 3, 16	PP	
39.48	do		PP	42.88	do	2, 3, 16	PP	
39.50	do		PX	42.90	do	2, 3, 16	PP	
39.52	do		PP	42.92	do	2, 3, 16	PP	
39.54	do		PP	42.94	do	2, 3, 16	PP	
39.56	do		PP	43.64	Base	13, 18	PS	
39.58	do		PX	43.68	do	13	PS	
39.60	do		PP	44.62	Base or mobile	2, 3, 16	PP	
39.62	do		PP	44.64	do		PO	
39.64	do		PP PP	44.66	do	2, 3, 16	PP	
39.66	Mobile		PP PP	44.68	do	2 2 16	PO PP	
39.68	Base or mobile		PP	44.70	do	2, 3, 16	PO	
39.70 39.72	Mobile Base or mobile		PP	44.72 44.74	do	2, 3, 16	PP	
39.74	Mobile		PP	44.76	do	2, 3, 10	PO	
39.76	Base or mobile		PP	44.78	Mobile	2, 16	PP	
39.78	Mobile		PP	44.80	Base or mobile	2, 10	PO	
39.80	Base or mobile		PP	44.82	Mobile	2, 16	PP	
39.82	do		PX	44.84	Base or mobile	2, 10	PO	
39.84	do		PP	44.86	Mobile	2, 16	PP	
39.86	do		PP	44.88	Base or mobile	2, 10	PO	
39.88	do		PP	44.90	Mobile	2, 16	PP	
39.90	do		PX	44.92	Base or mobile	2, 10	PO	
39.92	do		PP	44.94	do	2, 3, 16	PP	
39.94	do		PP	44.96	do		PO	
39.96	do		PP	44.98	do	2, 3, 16	PP	
39.98	do		PX	45.00	do		PO	
42.02	do	2, 3, 16	PP	45.02	do	2, 3, 16	PP	
42.04	do	2, 3, 16	PP	45.04	do	l	PO	

PUBLIC SAFETY POOL FREQUENCY TABLE— Continued

PUBLIC SAFETY POOL FREQUENCY TABLE— Continued

	Continue	·u						
Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	
45.06	do	2, 3, 16	PP	46.46	do		PF	
45.08	do		PX	46.48	do		PF	
45.10	do		PP	46.50	do		PF	
45.12	do		PX	46.52	do		PX	
45.14	do		PP	46.54	do		PX	
45.16	do		PX	46.56	do		PX	
45.18	do		PP PX	46.58	do		PX PH	
45.20 45.22	do		PP	47.02 47.04	dodo	21, 22	PH	
45.24	do		PX	47.06	do	21, 22	PH	
45.26	Mobile		PP	47.08	do	21, 22	PH	
45.28	Base or mobile		PX	47.10	do	21, 22	PH	
45.30	Mobile		PP	47.12	do	21, 22	PH	
45.32	Base or mobile		PX	47.14	do	21, 22	PH	
45.34	Mobile		PP	47.16	do	21, 22	PH	
45.36	Base or mobile		PX	47.18	do	21, 22	PH	
45.38	Mobile		PP	47.20	do	21, 22	PH	
45.40 45.42	Base or mobile		PX PP	47.22 47.24	do	21, 22	PH PH	
45.44	do		PX	47.26	do	21, 22	PH	
45.46	do		PP	47.28	do	21, 22	PH	
45.48	do		PX	47.30	do	21, 22	PH	
45.50	do		PP	47.32	do	21, 22	PH	
45.52	do		PX	47.34	do	21, 22	PH	
45.54	do		PP	47.36	do	21, 22	PH	
45.56	do		PX	47.38	do	21, 22	PH	
45.58	do		PP	47.40	do	21, 22	PH	
45.60 45.62	dodo		PX PP	47.42 47.46	dodo	10, 23	PS PS	
45.64	do		PX	47.50	do	10	PS	
45.66	do		PP	47.54	do	10	PS	
45.68	do		PH	47.58	do	10	PS	
45.70	do		PP	47.62	do	10	PS	
45.72	do		PH	47.66	do	10	PS	
45.74	Mobile		PP	72.00 to 76.00	Operational	24		
45.76	Base or mobile		PH		fixed.			
45.78	Mobile		PP	72.44	Mobile	25	PF	
45.80	Base or mobile		PH PP	72.48	do	25	PF	
45.82 45.84	Mobile Base or mobile		PH	72.52 72.56	dodo	25 25	PF PF	
45.86	do	15	PP	72.6	do	25	PF	
45.88	do	19	PF	75.44	do	25	PF	
45.90	do	20	PP	75.48	do	25	PF	
45.92	do	10	PS	75.52	do	25	PF	
45.94	do		PP	75.56	do	25	PF	
45.96	do	10	PS	75.6	do	25	PF	
45.98	do		PP	150 to 170	Base or mobile	26		
46.00	do	10	PS	150.775	Mobile	87	PM.	
46.02	do		PP PS	150.7825	do	88	PM	
46.04	dodo	10	PS	150.790 150.7975	dodo	87	PM. PM.	
46.06 46.08	do		PF	150.7975	do	88	PM. PM	
46.10	do		PF	150.995	Base or mobile	28	PH	
46.12	do		PF	151.0025	do	27, 28	PH	
46.14	do		PF	151.010	do	28	PH	
46.16	do		PF	151.0175	do	28	PH	
46.18	do		PF	151.025	do	28	PH	
46.20	do		PF	151.0325	do	27, 28	PH	
46.22	Mobile		PF	151.040	do	28	PH	
46.24	do		PF	151.0475	do	27, 28	PH	
46.26	do		PF	151.055	do	28	PH	
46.28	do	11	PF PF	151.0625	do	27, 28	PH PH	
46.30	i woone of fixed	11		151.070 151.0775	do	28	PH	
46.30		l					L CTT	
46.32	Mobile		PF PF				PH	
46.32 46.34	Mobiledo		PF	151.085	do	28	PH PH	
46.32 46.34 46.36	MobiledoBase or mobile			151.085 151.0925	dodo	28 27, 28	PH	
46.32 46.34	Mobiledo		PF PF	151.085 151.0925 151.100	do	28		
46.32 46.34 46.36 46.38	MobiledoBase or mobiledo		PF PF	151.085 151.0925	dodododo	28 27, 28 28	PH PH	

Federal Communications Commission

PUBLIC SAFETY POOL FREQUENCY TABLE— Continued

PUBLIC SAFETY POOL FREQUENCY TABLE— Continued

Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
151.130	do	28, 81	PH	153.8825	do	27	PX
151.1375	do	27, 28, 80	PH	153.890	do		PF
151.145	do	28, 81	PO	153.8975	do	27	PF
151.1525	do	27, 28	PO	153.905	do		PX
151.160	do	28	PO	153.9125	do	27	PX
151.1675	do	27, 28	PO	153.920	do		PX
151.175	do	28	PO	153.9275	do	27	PX
151.1825	do	27, 28	PO	153.935	do		PX
151.190	do	28	PO	153.9425	do	27	PX
151.1975	do	27, 28	PO	153.950	do		PF
151.205	do	28	PO	153.9575	do	27	PF
151.2125	do	27, 28	PO	153.965	do		PX
151.220	do	28	PO	153.9725	do	27	PX
151.2275	do	27, 28	PO	153.980	do		PX
151.235	do	28	PO	153.9875	do	27	PX
151.2425	do	27, 28	PO	153.995	do		PX
151.250	do	28	PO	154.0025	do	27	PX
151.2575	do	27, 28	PO	154.010	do		PF
151.265	do	28	PO	154.0175	do	27	PF
151.2725	do	27, 28	PO	154.025	Base or mobile		PX
151.280	do	28	PO	154.0325	do	27	PX
151.2875	do	27, 28	PO	154.040	do	28	PX
151.295	do	28	PO	154.0475	do	27, 28	PX
151.3025	do	27, 28	PO	154.055	do	28	PX
151.310	do	28	PO	154.0625	do	27, 28	PX
151.3175	do	27, 28	PO	154.070	Mobile	28	PF
151.325	do	28	PO	154.0775	do	27, 28	PF
151.3325	do	27, 28	PO	154.085	Base or mobile	28	PX
151.340	do	28	PO	154.0925	do	2728	PX
151.3475	do	27, 28	PO	154.100	do	28	PX
151.355	do	28	PO	154.1075	do	27, 28	PX
151.3625	do	27, 28	PO	154.115	do	28	PX
151.370	do	28	PO	154.1225	do	27, 28	PX
151.3775	do	2728	PO	154.130	do	28	PF
151.385	do	28	PO	154.1375	do	27, 28	PF
151.3925	do	27, 28	PO	154.145	do	28	PF
151.400	do	28	PO	154.1525	do	27, 28	PF
151.4075	do	27, 28	PO	154.160	do	28	PF
151.415	do	28	PO	154.1675	do	27, 28	PF
151.4225	do	27, 28	PO	154.175	do	28	PF
151.430	do	28	PO	154.1825	do	27, 28	PF
151.4375	do	27, 28	PO	154.190	do	28	PF
151.445	do	28	PO	154.1975	do	27, 28	PF
151.4525	do	27, 28	PO	154.205	do	28	PF
151.460	do	28	PO	154.2125	do	27, 28	PF
151.4675	do	27, 28	PO	154.220	do	28	PF
151.475	do	28	PO	154.2275	do	27, 28	PF
151.4825	do	27, 28	PO	154.235	do	28	PF
151.490	do	7, 28	PO	154.2425	do	27. 28	PF
151.4975	do	7, 27, 28	PO	154.250	do	28	PF
152.0075	Base	13, 29, 30	PS	154.2575	do	27, 28	PF
153.740	Mobile		PX	154.265	do	19, 28	PF
153.7475	do	27	PX	154.2725	do	19, 27, 28	PF
153.755	do		PX	154.280	do	19, 28	PF
153.7625	do	27	PX	154.2875	do	19, 27, 28	PF
153.770	do		PF	154.295	do	19, 28	PF
153.7775	do	27	PF	154.3025	do	19, 27, 28	PF
153.785	do		PX	154.310	do	28	PF
153.7925	do	27	PX	154.3175	do	27, 28	PF
153.800	do		PX	154.325	do	28	PF
153.8075	do	27	PX	154.3325	do	27, 28	PF
153.815	do		PX	154.340	do	28	PF
153.8225	do	27	PX	154.3475	do	27, 28	PF
153.830	do	31	PF	154.355	do	28	PF
153.8375	do	27, 31	PF	154.3625	do	27, 28	PF
153.845	do		PX	154.370	do	28	PF
153.8525	do		PX	154.3775	do	27, 28	PF
153.860	dodo	27	PX	154.385	do		PF
		27	PX	154.3925		28	PF
153.8675	dodo	27	PX	154.400	dodo	27, 28	PF
153.875							

PUBLIC SAFETY POOL FREQUENCY TABLE— Continued

PUBLIC SAFETY POOL FREQUENCY TABLE— Continued

154.415	Class of station(s) do	Limitations 27, 28	PF P	Frequency or band 155.0625	Class of station(s) do	27	Coordinator PX PP PP PP PX PX PX PX PX PX PX PX PX
154.415	do	28	PF PF PF PF PF PX PX PX PX PP PP PP PP PP PP PP PP PP	155.070 155.0775 155.085 155.0925 155.1075 155.115 155.125 155.1370 155.1525 155.1560 155.1560 155.1675 155.175 155.175 155.175 155.175 155.175 155.175 155.175 155.175 155.175 155.175 155.175 155.175 155.175 155.175 155.175	do	27	PP PP PP PX PX PX PX PX PX PX PX PP PP P
154.4225	do	27, 28	PF PF PF PF PF PX PX PX PX PP PP PP PP PP PP PP PP	155.0775 155.085	do	27	PP PX PX PX PX PX PX PX PX PP PP PP PP P
154.430	do	28	PF PF PF PF PX PX PX PX PP PP PP PP PP PP PP PP PP	155.085	do	27	PX PX PX PX PX PP PP PP PX PX PS PS PS PS PP PP PP
154.4375	do	27, 28 28, 81 27, 28, 80. 32, 33, 34, 35, 36, 37. 33, 34, 35, 36. 36. 37. 37. 27. 16. 16. 16. 16. 16. 27 16. 27	PF PF PF PX PX PX PX PP PP PP PP PP PP PP	155.0925	do	27	PX PX PX PX PP PP PX PS PS PS PP PP PS
154.445	do	28, 81	PF PF PX PX PX PP PP PP PP PP PP	155.100 155.1075 155.115 155.1225 155.1375 155.145 155.1525 155.160 155.1675 155.175 155.175 155.175 155.175 155.175 155.175 155.175 155.175 155.175 155.175 155.175 155.175	do	27	PX PX PX PP PP PX PS PS PS PP PP PS
154.4525	do Fixed or mobiledo	27, 28, 80. 32, 33, 34, 35, 36, 37. 33, 34, 35, 36, 37. 37. 27	PF PX PX PX PX PP PP PP PP PP PP	155.1075 155.115 155.1225 155.130 155.1375 155.145 155.145 155.160 155.1675 155.1675 155.1825 155.190 155.1975 155.205 155.205	do	27	PX PX PX PP PP PX PX PS PS PS PP PP PS
154.45625 F 154.46375	Fixed or mobile do	32, 33, 34, 35, 36, 37, 33, 34, 35, 36, 37, 36, 37, 36, 37, 37, 37, 37, 37, 37, 37, 37, 37, 37	PX PX PX PP P	155.115 155.1225 	do	27	PX PX PP PP PX PX PS PS PS PS PS PP PP PS
154.46375	do	35, 33, 34, 35, 36, 37, 33, 34, 35, 36, 33, 34, 35, 37,	PX PX PX PP P	155.1225	do	27	PX PP PP PX PX PS PS PS PP PP PP PP
154.47125	do	33, 34, 35, 36, 37. 33, 34, 35, 36. 33, 34, 35, 37	PX PP	155.130 155.1375 155.145 155.1525 155.160 155.1675 155.175 155.1825 155.190 155.1975 155.205 155.205	do	27	PP PP PX PX PS PS PS PP PP PP
154.47125	do	36, 37, 33, 34, 35, 36, 33, 34, 35, 37	PX PP	155.1375	do	27	PP PX PX PS PS PS PS PP PP PP
154.47875	Mobile	33, 34, 35, 36. 33, 34, 35, 37	PX PP PP PP PP PP PP PP PP	155.145	do	27	PX PX PS PS PS PS PP PP
154.47875	Mobile	36, 33, 34, 35, 37	PX PP PP PP PP PP PP PP PP	155.1525	do	27	PX PS PS PS PS PP PP
154.650	Mobile	33, 34, 35, 37. 27	PP PP PP PP PP PP	155.160	do	10	PS PS PS PS PP PP
154.650	Mobile	37	PP PP PP PP PP PP	155.1675 155.175 155.1825 155.190 155.1975 155.205	do .	10, 27 10 10, 27 27 10	PS PS PS PP PP PS
154.6875 B 154.6725 B 154.6875 C 154.680 C 154.6875 C 154.7025 C 154.715 C 154.715 C 154.725 C 154.7475 C 154.	do Base or mobile do do do do do do do Base or mobile do	27	PP PP PP PP PP PP	155.175 155.1825 155.190 155.1975 155.205 155.2125	do	10 10, 27 27 10	PS PS PP PP PS
154.6875 B 154.6725 B 154.6875 C 154.680 C 154.6875 C 154.7025 C 154.715 C 154.715 C 154.725 C 154.7475 C 154.	do Base or mobile do do do do do do do Base or mobile do	27	PP PP PP PP PP PP	155.1825 155.190 155.1975 155.205 155.2125	do	10, 27 27 10	PS PP PP PS
154.665 B 154.6725	Base or mobile	16	PP PP PP PP PP	155.190 155.1975 155.205 155.2125	dododododododo	27	PP PP PS
154.6725	do	16, 27 16 16, 27 16 16, 27 27	PP PP PP PP	155.1975 155.205 155.2125	dodododo	27	PP PS
154.680	do	16 16, 27 16 16, 27 27	PP PP PP PP	155.205 155.2125	dodo	10	PS
154.6875	do	16 16, 27 16 16, 27 27	PP PP PP	155.2125	do	10	
154.6875	do	16, 27 16 16, 27 27	PP PP			10, 27	l PS
154.695	do	16 16, 27 27	PP			,	
154.7025	do	16, 27 27	PP		do	10	PS
154.710 N 154.7175 S 154.725 S 154.7325 S 154.740 S 154.7475 S 154.7475 S 154.7625 S 154.770 N 154.775 S 154.785 S 154.78	MobiledoBase or mobiledodododododododo	27	PP	155.2275	do	10, 27	PS
154.7175 B 154.725 B 154.7325 154.740 154.7475 154.7455 154.7625 154.770 N 154.775 B 154.785 B 154.7925 154.800 154.8075	doBase or mobiledodo	27		155.235	do	10	PS
154.725	Base or mobile dodo		PP	155.2425	do	10, 27	PS
154.7325	dodo		PP	155.250	do		PP
154.740	do	27	PP	155.2575	do	27	PP
154.7475			PP	155.265	do	10	PS
154.755		27	PP	155.2725	do	10, 27	PS
154.7625	do		PP	155.280	do	10	PS
154.770	do	27	PP	155.2875	do	10, 27	PS
154.7775	Mobile		PP	155.295	do	10	PS
154.785 B 154.7925 154.800 154.8075	do	27	PP	155.3025	do	10, 27	PS
154.7925	do		PP	155.310	do	10, 27	PP
154.800 154.8075	Base or mobile		PP	155.3175	do	27	PP
154.8075	do	27	PP				PM
	do			155.325	do	10, 39	
	do	27	PP	155.3325	do	27, 10, 39	PM
	do		PP	155.340	do	39, 40	PM
	do	27	PP	155.3475	do	27, 39, 40	PM
	Mobile		PP	155.355	do	10, 39	PM
	do	27	PP	155.3625	do	27, 10, 39	PM
	Base or mobile		PP	155.370	do		PP
	do	27	PP	155.3775	do	27	PP
	do		PP	155.385	do	10, 39	PM
154.8675	do	27	PP	155.3925	do	27, 10, 39	PM
154.875	do		PP	155.400	do	10, 39	PM
154.8825	do	27	PP	155.4075	do	27, 10, 39	PM
154.890 N	Mobile		PP	155.415	do		PP
	do	27	PP	155.4225	do	27	PP
	Base or mobile	16	PP	155.430	do		PP
	do	16	PP	155.4375	do	27	PP
	do	16	PP	155.445	do	16	PP
154.9275	do	16, 27	PP	155.4525	do	16, 27	PP
	do	16	PP	155.460	do	16	PP
	do	16, 27	PP	155.4675	do	16, 27	PP
	Mobile		PP	155.475	do	41	PP
	do		PP	155.4825	do	27, 41	PP
		27	PX		uo		PP
	Base or mobile			155.490	do		
	do	27	PX	155.4975	do	27	PP
	do		PX	155.505	do	16	PP
	do	27	PX	155.5125	do	16, 27	PP
154.995	do		PX	155.520	do		PP
155.0025	do	27	PX	155.5275	do	27	PP
155.010	do		PP	155.535	do		PP
155.0175	do	27	PP	155.5425	do	27	PP
155.025	do		PX	155.550	do		PP
155.0325	do	27	PX	155.5575	do	27	PP
155.040	do		PX	155.565	do		PP
155.0475	do	27	PX	155.5725	do	27	PP
155.055			PX	155.580	do		PP

Federal Communications Commission

PUBLIC SAFETY POOL FREQUENCY TABLE— Continued

PUBLIC SAFETY POOL FREQUENCY TABLE— Continued

Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coord nator
55.5875	do	27	PP PP	156.1125	do	27	PH PH
55.595	do	27	PP	156.120	do	27	PH
55.6025	do	27	PP	156.1275	do	27	PH
55.610	do	0.7	PP	156.135 156.1425	do		PH
55.6175 55.625	dodo	27	PP	156.150	do Mobile	27	PP
			PP				PP
55.6325 55.640	do	27	PP	156.1575 156.165	do Base or mobile	42	PH
	do	27	PP			27, 42	PH
55.6475	do	27	PP	156.1725	do	42	PH
55.655	do	27	PP	156.180	do		PH
55.6625	do	27	PP	156.1875	do	27, 42	
55.670	do		PP	156.195 156.2025	do		PH PH
55.6775	do	27	PP		do	27	PP
55.685	do	27	PP	156.210	do	27	PP
55.6925	do	27	PP	156.2175	do	27	
55.700	do			156.225	do	07.40	PH
55.7075	do	27	PP	156.2325	do	27, 10	PH
55.715	do		PX PX	156.240	do	79	PH PS
55.7225	do	27		157.450	Base	13, 30, 45	
5.730	do		PP	158.7225	Base or Mobile	44	PP
55.7375	do	27	PP	158.730	do	81	PP
55.745	do	81	PX	158.7375	do	27, 80	PP
55.7525	do	27, 80, 83	PX	158.745	do	81	PX
55.760	do	81	PX	158.7525	do	27	PX
5.7675	do	27	PX	158.760	do		PX
5.775	do		PX	158.7675	do	27	PX
5.7825	do	27	PX	158.775	do		PX
5.790	do		PP	158.7825	do	27	PX
5.7975	do	27	PP	158.790	do		PP
5.805	do		PX	158.7975	do	27	PP
5.8125	do	27	PX	158.805	do		PX
5.820	do		PX	158.8125	do	27	PX
5.8275	do	27	PX	158.820	do		PX
5.835	do		PX	158.8275	do		PX
5.8425	do	27	PX	158.835	do		PX
5.850	Mobile		PP	158.8425	do	27	PX
5.8575	do	27	PP	158.850	do		PP
5.865	Base or mobile		PX	158.8575	do	27	PP
55.8725	do	27	PX	158.865	Mobile		PX
5.880	do		PX	158.8725	do	27	PX
5.8875	do	27	PX	158.880	do		PX
5.895	do		PX	158.8875	do		PX
5.9025	do	27	PX	158.895	do		PX
55.910	Mobile		PP	158.9025	do	27	PX
5.9175	do	27	PP	158.910	do		PP
5.925	Base or mobile		PX	158.9175	do	27	PP
5.9325	do	27	PX	158.925	do		PX
5.940	do		PX	158.9325	do	27	PX
5.9475	do	27	PX	158.940	do		PX
5.955	do		PX	158.9475	do		PX
5.9625	do	27	PX	158.955	do		PX
5.970	Mobile		PP	158.9625	do	27	PX
5.9775	do	27	PP	158.970	do		PP
5.985	do		PX	158.9775	do	27	PP
5.9925	do	27	PX	158.985	do		PH
6.000	do		PX	158.9925	do	27	PH
6.0075	do	27	PX	159.000	do		PH
6.015	do		PX	159.0075	do	27	PH
6.0225	do	27	PX	159.015	do		PH
6.030	do		PP	159.0225	do	27	PH
6.0375	do	27	PP	159.030	do		PP
6.045	do	42	PH	159.0375	do	27	PP
6.0525	do	27, 42	PH	159.045	do		PH
6.060	do	42	PH	159.0525	do	27	PH
6.0675	do	27, 42	PH	159.060	do		PH
6.075	do		PH	159.0675	do	27	PH
6.0825	do	27	PH	159.075	do		PH
6.090	do		PP	159.0825	do	27	PH
				100.0020			PP
6.0975	do	27	PP	159.090	Base or mobile		

PUBLIC SAFETY POOL FREQUENCY TABLE— Continued

PUBLIC SAFETY POOL FREQUENCY TABLE— Continued

Frequency or band Class of starbino(s) Coordinator band Class of starbino(s) Class of starbin			-					
199.1125			Limitations		Frequency or band		Limitations	
199, 120					173.2625	do		PX
159.135	159.120	do		PH	173.2875	do	32, 33, 34,	PX
159.150	159.135	do		PH	173.3125	do	32, 33, 34,	PX
159,165	159.150	do		PP	173.3375	do	32, 33, 34,	PX
159.1870	159.165	do		PH	173.3625	do	32, 33, 34,	PX
159.195 do PH 173.39625 do 33, 34, 35, 9X PX 159.210 do PP 20 to 222 Base or mobile 55, 55, 55, 55, 55, 55, 55, 55, 55, 55,	159.180	do		PH	173.390	do	34, 35, 36,	PX
159,210	159.195	do		PH	173.39625	do		PX
159,225	159.210	do		PP	220 to 222	Base or mobile		
199, 225		do			220.8025	Base	55	
159,240								
159,2475								
159,2655		do						
159.2625	159 255	do						
159.270 do 46 PO 220.8375 do 55 159.2755 do 27, 46 PO 220.8425 do do 55 159.2855 do 46 PO 220.8425 do	159 2625	do	27 46					
159.2775								
159.285 do								
159.2925 do 27, 46 PO 220.9075								
159.300 do 46 PO 220.9075 do 55 PM 159.3075 do 27, 46 PO 220.9125 do 55 PM 159.315 do 46 PO 220.9125 do 55 PM 159.325 do d6 PO 221.8025 do 55 PM 159.3375 do d6 PO 221.8075 do 55 PM 159.345 do d6 PO 221.8075 do 55 PM 159.365 do d6 PO 221.8125 do				PO				DM
199.3075	159.300		46	PO				
199.3255	159.3075	do	27, 46					
199.3225	159.315		46					
199.3375			27, 46					
199.345	159.330							
159.3525								
159.360								
159.3675 do 46 PO 221.8225 do 55 do 159.375 do 46 PO 221.8325 do 55 do 55 do 55 do 55 do								
159.375 do 46 PO 221.82/5 do 55 159.3825 do 27, 46 PO 221.8375 do 55 159.3975 do 46 PO 221.8425 do 55 159.4975 do do 46 PO 221.8425 do 55 159.4125 do do 46 PO 221.9025 do 55 159.420 do 46 PO 221.9025 do 55 PM 159.435 do 27, 46 PO 221.9125 do 55 PM 159.435 do 27, 46 PO 221.9125 do 55 PM 159.435 do 27, 46 PO 221.9125 do 55 PM 159.465 do do 27, 46 PO 221.9125 do 55 PM 162.250 Base or mobile 47						do	55	
1593,8825 do 27, 46 PO 221,8325 do 55 159,390 do 46 PO 221,8425 do 55 159,3975 do 27,46 PO 221,8425 do 55 159,4125 do 27,46 PO 221,9025 do 55 PM 159,420 do 46 PO 221,9075 do 55 PM 159,4275 do 27,46 PO 221,9125 do 55 PM 159,4275 do 46 PO 221,9125 do 55 PM 159,4275 do 46 PO 221,9125 do 55 PM 159,455 do do 27 PO 406 to 416 Operational 48 159,475 do 80 PO 450 to 470 Fixed, base, or mobile 76, 56 163,250 Base or mobile 47 PF					221.8275			
159,390								
159.3975 do 27, 46 PO 221.8425 do 55		do	46					
159,405 do d6 d0 27, 46 PO 221,9025 d0 d5 mM 159,4125 do d6 d0 d6 d0 d0 d5 mM mM d0 d0 d6 d0 d0 d0 d0 d0 d0 d0 d0 55 PM	159.3975	do	27, 46					
159,420			46					DM
159.4275								
159.435								
159.4425								
159.450								
159.4575 do 27 PO 450 to 470 fixed. Fixed, base, or mobile. 26, 56 PO 159.4725 do 80 PO 450 to 470 Fixed, base, or mobile. 26, 56 PO 163.250 Base or mobile 13, 30 PS 453.0125 Mobile 57, 78 PX 169 to 172 Mobile or operational fixed. 48 453.0375 do 27, 59, 62, PX 84 170.425 do 9, 49 PO 453.04375 do 27, 59, 62, PX PM 170.475 do 9, 49 PO 453.0505 do 44, 49, 62, PM PM 171.475 do 9, 49 PO 453.0505 do PX 171.475 do 9, 49 PO 453.05625 do 27, 84 PX 171.575 do 9, 49 PO 453.0625 do 27, 84 PX 171.575 do 9, 49 PO 453.0625								' '''
159.465					400 to 410		0.	
159.4725					450 to 470		26, 56	
163.250 Base 13, 30 PS 453.0125 Mobile 57, 78 PX 166.250 Base or mobile 47 PF 453.03125 Base or mobile 44, 49, 62, PM PM 169 to 172 Mobile or operational fixed. 48. 453.0375 do 27, 59, 62, RM PX 170.150 Base or mobile 47 PF 84. 27, 59, 62, RM PX 170.475 do 9, 49 PO. 453.04375 do 44, 49, 62, PM PM 170.475 do 9, 49 PO. 453.0505 do 44, 49, 62, PM PM 171.425 do 9, 49 PO. 453.05625 do PX PX 171.475 do 9, 49 PO. 453.0625 do 27, 84 PX 171.275 do 9, 49 PO. 453.06875 do 27, 84 PX 172.275 do 9, 49 PO. 453.06875 do 44, 84								
166.250 Base or mobile Mobile or operational fixed. 47 PF 453.03125 Base or mobile 84, 49, 62, 84. 84. PM 170.150 Base or mobile not fixed. 48 453.0375 do 27, 59, 62, PX PX 170.475 do 9, 49 PO. 453.04375 do 44, 49, 62, PM PM 170.475 do 9, 49 PO. 453.050do do PX 171.425 do 9, 49 PO. 453.05625 do 27, 84 PX 171.475 do 9, 49 PO. 453.0625 do 27, 84 PX 171.475 do 9, 49 PO. 453.0625 do 27, 84 PX 171.475 do 9, 49 PO. 453.0625 do 27, 84 PX 171.475 do 9, 49 PO. 453.0627 do 27, 84 PX 172.275 do 9, 49 PO. 453.06875 do 44, 84					453.0125	Mobile	57, 78	PX
169 to 172 Mobile or operational fixed. 48. 453.0375 do 27, 59, 62, PX 170.150 Base or mobiledo 9, 49 PO. 453.04375 do 44, 49, 62, PM 170.475 do 9, 49 PO. 453.050 do 44, 49, 62, PM 170.575 do 9, 49 PO. 453.050 do 94, 48 PX 171.425 do 9, 49 PO. 453.0625 do 44, 84 PX 171.475 do 9, 49 PO. 453.0625 do 27, 84 PX 171.575 do 9, 49 PO. 453.06875 do 44, 84 PX 172.275 do 9, 49 PO. 453.075 Central control, 58, 59, 60, PM 172.375 do 9, 49 PO. 453.08125 Base or mobile ase, or mobile					453.03125	Base or mobile		PM
170.150 Base or mobile 47 PF 453.04375 84. 44, 49, 62, PM PM 170.425 do 9, 49 PO. 453.04375 do 444, 49, 62, PM PM 170.575 do 9, 49 PO. 453.050 do 94, 84 PX 171.425 do 9, 49 PO. 453.0625 do 44, 84 PX 171.475 do 9, 49 PO. 453.0625 do 27, 84 PX 171.575 do 9, 49 PO. 453.06875 do 27, 84 PX 172.225 do 9, 49 PO. 453.06375 do 44, 84 PX 172.275 do 9, 49 PO. 453.075 Central control, 58, 59, 60, PM 173.2075 do 54 PP 453.08125 Base or mobile 84, 59, 62, PM 173.210 do 34, 35, 36, PX 36. 453.09375 do 27, 59, 62, PX <tr< td=""><td></td><td>Mobile or oper-</td><td>48.</td><td></td><td>453.0375</td><td>do</td><td></td><td>PX</td></tr<>		Mobile or oper-	48.		453.0375	do		PX
170.425 do 9, 49 PO. 453.04375 do 44, 49, 62, 84. PM 170.475 do 9, 49 PO. 453.050 do 84. PX 170.575 do 9, 49 PO. 453.05625 do 44, 84 PX 171.475 do 9, 49 PO. 453.0625 do 27, 84 PX 171.575 do 9, 49 PO. 453.06875 do 27, 84 PX 172.2255 do 9, 49 PO. 453.075 Central control, fixed base, or mobile. 58, 59, 60, PM PM 173.075 do 9, 49 PO. 453.08125 Base or mobile 44, 59, 62, PM PM 173.20375 Fixed or mobile 33, 34, 35, 36, 54, 54, 54, 54, 54, 54 453.0875 do 27, 59, 62, PX PX 173.2375 do 34, 35, 36, 54, 54, 54, 54, 54, 54 453.09375 do 44, 49, 62, PM PM	170.150		47	PF				
170.475 do 9, 49 PO. 453.050 do PX 170.575 do 9, 49 PO. 453.05625 do 44, 84 PX 171.475 do 9, 49 PO. 453.0625 do 27, 84 PX 171.575 do 9, 49 PO. 453.06875 do 44, 84 PX 172.225 do 9, 49 PO. 453.06875 do 44, 84 PX 172.275 do 9, 49 PO. 453.075 Central control, 58, 59, 60, PM 173.075 do 9, 49 PO. 453.08125 Base or mobile 44, 59, 62, PM 173.205 Fixed or mobile 33, 34, 35, 36, 54, 54, 54, 54, 54, 54, 54 PX 453.0875 do 27, 59, 62, PX 173.2375 do 34, 35, 36, 54, 54, 54, 54, 54, 54, 54 PX 453.09375 do 44, 59, 62, PM 173.2375 do 32, 33, 34, PX PX 453.09375 do 44, 59, 62, PM					453.04375	do		PM
170.575 do 9, 49 PO. 453.0562 do PX PX 171.425 do 9, 49 PO. 453.05625 do 44, 84 PX 171.475 do 9, 49 PO. 453.0625 do 27, 84 PX 171.575 do 9, 49 PO. 453.06875 do 44, 84 PX 172.225 do 9, 49 PO. 453.075 Central control, fixed base, or mobile. 58, 59, 60, PM PM 172.275 do 9, 49 PO. 453.08125 Base or mobile 44, 59, 62, PM PM 173.20375 Fixed or mobile 33, 34, 35, PX 36. 453.0875 do 27, 59, 62, PX PX 173.2375 do 34, 35, 36, 54, 54, 54 PX 453.09375 do 44, 59, 62, PM PM 173.2375 do 32, 33, 34, PX 453.09375 do 44, 59, 62, PM PM			9, 49				84.	
171.425 do 9, 49 PO. 453.05625 do 44, 84 PX 171.475 do 9, 49 PO. 453.0625 do 27, 84 PX 171.575 do 9, 49 PO. 453.0625 do 44, 84 PX 172.225 do 9, 49 PO. 453.075 Central control, 58, 59, 60, PM 172.275 do 9, 49 PO. fixed base, or mobile. 61, 62 173.075 do 53 PP 453.08125 Base or mobile 44, 59, 62, PM 173.20375 do 33, 34, 35, 36, PX 453.0875 do 27, 59, 62, PX 173.210 do 34, 35, 36, PX 453.09375 do 27, 59, 62, PX 173.2375 do 32, 33, 34, PX 453.09375 do 44, 59, 62, PM			9, 49		453.050	do		PX
171.475 do 9, 49 PO. 453.0625 do 27, 84 PX 171.575 do 9, 49 PO. 453.06875 do 44, 84 PX 172.225 do 9, 49 PO. 453.075 Central control, fixed base, or mobile. 58, 59, 60, PM 172.275 do 9, 49 PO. PO. fixed base, or mobile. 61, 62 PM 173.075 do 53 PP 453.08125 Base or mobile 44, 59, 62, PM PM 173.2075 Fixed or mobile 33, 34, 35, 86, 54, 54, 54, 4 PX 453.0875 do 27, 59, 62, PX PX 173.2375 do 34, 35, 36, 54, 54, 54, 32, 33, 34, PX 453.09375 do 44, 59, 62, PM PM				PO.	453.05625	do	44, 84	PX
171.575 do 9, 49 PO. 453.06875 do 44, 84 PX 172.225 do 9, 49 PO. 453.075 do 58, 59, 60, 60, 61, 62. PM 172.375 do 9, 49 PO. PO. mobile. 61, 62. PM 173.075 do 53 PP 453.08125 Base or mobile 44, 59, 62, 84. PM 173.210 do 34, 35, 36, 54. PX do do 27, 59, 62, PX 173.2375 do 32, 33, 34, PX 453.09375 do do 44, 59, 62, PM 173.2375 do 32, 33, 34, PX PX 453.09375 do do 44, 59, 62, PM	171.475		9, 49	PO.			27, 84	
172.225 do 9, 49 PO. 453.075 Central control, fixed base, or mobile. 58, 59, 60, PM 172.375 do 9, 49 PO. fixed base, or mobile. 61, 62. 173.075 do 53 PP 453.08125 Base or mobile 44, 59, 62, PM 173.20375 do 34, 35, 36, 54. 54. PX do 27, 59, 62, 84. 84. 173.2375 do 32, 33, 34, PX 453.09375 do do 44, 59, 62, PM	171.575		9, 49	PO.			44, 84	
172.275 do 9, 49 PO. fixed base, or mobile. 61, 62. 172.375 do 9, 49 PO. mobile. 173.075 do 53 PP 453.08125 Base or mobile. 44, 59, 62, PM 173.210 do 36, 34, 35, 36, 54, 54, 54. PX 84. 173.2375 do 32, 33, 34, PX 453.09375 do 44, 59, 62, PM 173.2375 do 32, 33, 34, PX	172.225		9, 49		453.075			PM
172.375 do	172.275		9, 49				61, 62.	
173.075 do 53	172.375		9, 49					
173.210dododododo	173.075		53		453.08125	Base or mobile		PM
173.210dodo	173.20375	Fixed or mobile		PX	450.0075	4-		DV.
173.2375 dodo 32, 33, 34, PX 84.	173.210	do	34, 35, 36,	PX			84.	
	173.2375	do	32, 33, 34,	PX				
				l	453.100	ldo	l	PX

PUBLIC SAFETY POOL FREQUENCY TABLE— Continued

PUBLIC SAFETY POOL FREQUENCY TABLE— Continued

Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
453.10625	do	44, 84	PX	453.500	do		PX
453.1125	do	27, 84	PX	453.50625	do	44	PX
453.11875	do	44, 84	PX	453.5125	do	27	PX
453.125	Central control,	58, 59, 60,	PM	453.51875	do	44	PX
	fixed base, or	61, 62.	l · ···	453.525	do		PX
		01, 02.		453.53125	do	44	PX
450 40405	mobile.						
453.13125	Base or mobile	44, 59, 62,	PM	453.5375	do	27	PX
		84.		453.54375	do	44	PX
453.1375	do	27, 59, 62,	PX	453.550	do		PX
		84.		453.55625	do	44	PX
453.14375	do	44, 59, 62,	PM	453.5625	do	27	PX
		84.		453.56875	do	44	PX
453.150	do		PX	453.575	do		PX
453.15625		44	PX	453.58125	do	44	PX
	do						
453.1625	do	27	PX	453.5875	do	27	PX
453.16875	do	44	PX	453.59375	do	44	PX
453.175	Central control,	58, 59, 60,	PM	453.600	do		PX
	fixed base, or	61, 62.		453.60625	do	44	PX
	mobile.			453.6125	do	27	PX
453.18125	Base or mobile	44, 59, 62	PM	453.61875	do	44	PX
453.1875	do	27, 59, 62	PX	453.625	do		PX
453.19375	do	44, 59, 62	PM	453.63125	do	44	PX
453.200	do	81	PX	453.6375	do	27	PX
453.20625	do	44, 82	PX	453.64375	do	44	PX
453.2125	do	27, 80, 83	PX	453.650	do		PX
453.21875	do	44, 82	PX	453.65625	do	44	PX
453.225	do	81	PX	453.6625	do	27	PX
453.23125	do	44	PX	453.66875	do	44	PX
453.2375	do	27	PX	453.675	do		PX
				453.68125	do	44	PX
453.24375	do	44	PX	453.00123		27	PX
453.250	do		PX	453.6875	do	27	
453.25625	do	44	PX	453.69375	do	44	PX
453.2625	do	27	PX	453.700	do	81	PX
453.26875	do	44	PX	453.70625	do	44, 82	PX
453.275	do		PX	453.7125	do	27, 80	PX
453.28125	do	44	PX	453.71875	do	44, 82	PX
453.2875	do	27	PX	453.725	do	81	PX
			PX	453.73125	do	44	PX
453.29375	do	44		453.7375	do	27	PX
453.300	do		PX				
453.30625	do	44	PX	453.74375	do	44	PX
453.3125	do	27	PX	453.750	do		PX
453.31875	do	44	PX	453.75625	do	44	PX
453.325	do		PX	453.7625	do	27	PX
453.33125	do	44	PX	453.76875	do	44	PX
453.3375	do	27	PX	453.775	do		PX
453.34375	do	44	PX	453.78125	do	44	PX
450.04070			PX				PX
453.350	do			453.7875	do	27	
453.35625	do	44	PX	453.79375	do	44	PX
453.3625	do	27	PX	453.800	do		PX
453.36875	do	44	PX	453.80625	do	44	PX
453.375	do		PX	453.8125	do	27	PX
453.38125	do	44	PX	453.81875	do	44	PX
453.3875	do	27	PX	453.825	do		PX
453 30375			PX	453.83125	do		PX
453.39375	do	44				44	
453.400	do		PX	453.8375	do	27	PX
453.40625	do	44	PX	453.84375	do	44	PX
453.4125	do	27	PX	453.850	do	81	PX
453.41875	do	44	PX	453.85625	do	44, 82	PX
453.425	do		PX	453.8625	do	27, 80	PX
453.43125	do	44	PX	453.86875	do	44, 82	PX
	do	27	PX				PX
453.4375				453.875	do	81	
453.44375	do	44	PX	453.88125	do	44, 84	PX
453.450	do	81	PX	453.8875	do	27, 84	PX
453.45625	do	44, 82	PX	453.89375	do	44, 84	PX
453.4625	do	27, 80	PX	453.900	do		PX
453.46875	do	44, 82	PX	453.90625	do	44, 84	PX
453.475	do	81	PX	453.9125	do	27, 84	PX
			PX	453.91875	do	44, 84	PX
						144 84	l PX
453.48125	do	44					
	dodododo	27	PX PX	453.925 453.93125	do	44, 84	PX PX

PUBLIC SAFETY POOL FREQUENCY TABLE— Continued

PUBLIC SAFETY POOL FREQUENCY TABLE— Continued

Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
453.9375	do	27, 84	PX	458.26875	do	44	PX
453.94375	do	44, 84	PX	458.275	do		PX
453.950	do		PX	458.28125	do	44	PX
453.95625	do	44, 84	PX	458.2875	do	27	PX
453.9625	do	27, 84	PX	458.29375	do	44	PX
453.96875	do	44, 84	PX	458.300	do		PX
453.975	do	144, 04	PX	458.30625	do	44	PX
453.98125	do	44, 84	PX	458.3125	do	27	PX
453.9875	do	27, 84	PX	458.31875	do	44	PX
453.99375	do	44, 84	PX	458.325	do		PX
458.0125	Mobile	57	PS	458.33125	do	44	PX
458.025	Central control,	58, 59, 61,	PM	458.3375	do	27	PX
	fixed base, or	62, 63.		458.34375	do	44	PX
	mobile.	02, 00.		458.350	do		PX
4E0 0242E		14 50 61	DM				
458.03125	Mobile	44, 59, 61,	PM	458.35625	do	44	PX
		62, 84.		458.3625	do	27	PX
458.0375	do	27, 59, 61,	PX	458.36875	do	44	PX
		62, 84.		458.375	do		PX
458.04375	do	44, 59, 61,	PM	458.38125	do	44	PX
		62, 84.		458.3875	do	27	PX
458.050	do	02, 04.	PX	458.39375	do	44	PX
			PX	458.400	do		PX
458.05625	do	44, 84					PX
458.0625	do	27, 84	PX	458.40625	do	44	
458.06875	do	44, 84	PX	458.4125	do	27	PX
458.075	Central control,	58, 59, 61,	PM	458.41875	do	44	PX
	fixed base, or	62, 63.		458.425	do		PX
	mobile.			458.43125	do	44	PX
458.08125	Mobile	44, 59, 61,	PM	458.4375	do	27	PX
-100.001Z0	14100110	62, 84.	l · ····	458.44375	do	44	PX
450.0075	مام		DV	458.450	do	81	PX
458.0875	do	27, 59, 61,	PX				PX
		62, 84.		458.45625	do	44, 82	
458.09375	do	44, 59, 61,	PM	458.4625	do	27, 80	PX
		62, 84.		458.46875	do	44, 82	PX
458.100	do		PX	458.475	do	81	PX
458.10625	do	44, 84	PX	458.48125	do	44	PX
458.1125	do	27, 84	PX	458.4875	do	27	PX
458.11875	do	44, 84	PX	458.49375	do	44	PX
				458.500	do		PX
458.125	Central control,	58, 59, 61,	PM				PX
	fixed base, or	62, 63.		458.50625	do	44	
	mobile.			458.5125	do	27	PX
458.13125	Mobile	44, 59, 61,	PM	458.51875	do	44	PX
		62, 84.		458.525	do		PX
458.1375	do	27, 59, 61,	PX	458.53125	do	44	PX
		62, 84.	` ``	458.5375	do	27	PX
450 44075	-d		DM	458.54375	do	44	PX
458.14375	do	44, 59, 61,	PM				
		62, 84.		458.550	do		PX
458.150	do		PX	458.55625	do	44	PX
458.15625	do	44	PX	458.5625	do	27	PX
458.1625	do	27	PX	458.56875	do	44	PX
458.16875	do	44	PX	458.575	do		PX
458.175	Central control,	58, 59, 61,	PM	458.58125	do	44	PX
	fixed base, or	62, 63.		458.5875	do	27	PX
		02, 00.	1	458.59375	do	44	PX
450 40405	mobile.	44 50 04	DM		uo	44	
458.18125	Mobile	44, 59, 61,	PM	458.600	do		PX
		62.		458.60625	do	44	PX
458.1875	do	27, 59, 61,	PX	458.6125	do	27	PX
		62.		458.61875	do	44	PX
458.19375	do	44, 59, 61,	PM	458.625	do		PX
		62.	1	458.63125	do	44	PX
			PX	458.6375	do	27	PX
458 200	do						PX
	do	81	DV				
458.20625	do	44, 82	PX	458.64375	do	44	
458.20625 458.2125	dodo	44, 82 27, 80, 83	PX	458.650	do		PX
458.20625 458.2125	do	44, 82	PX PX			44	PX PX
458.20625 458.2125 458.21875	dodo	44, 82 27, 80, 83 44, 82	PX	458.650	do	44	PX
458.20625 458.2125 458.21875 458.225	dododododododo	44, 82 27, 80, 83 44, 82 81	PX PX PX	458.650 458.65625 458.6625	dodododo	44 27	PX PX PX
458.2125 458.21875 458.225 458.23125	do	44, 82 27, 80, 83 44, 82 81	PX PX PX PX	458.650 458.65625 458.6625 458.66875	do	44 27 44	PX PX PX PX
458.20625 458.2125 458.21875 458.225 458.23125 458.2375	do	44, 82 27, 80, 83 44, 82 81 44 27	PX PX PX PX PX	458.650	do .	27 44	PX PX PX PX PX
458.20625	do	44, 82 27, 80, 83 44, 82 81 44 27 44	PX PX PX PX PX PX PX	458.650	do	44 44 44	PX PX PX PX PX PX
458.20625	do	44, 82 27, 80, 83 44, 82 81 44 27	PX PX PX PX PX PX PX PX	458.650	do	44	PX PX PX PX PX PX PX PX
458.20625	do	44, 82 27, 80, 83 44, 82 81 44 27 44	PX PX PX PX PX PX PX	458.650	do	44 44 44	PX PX PX PX PX PX

PUBLIC SAFETY POOL FREQUENCY TABLE— Continued

PUBLIC SAFETY POOL FREQUENCY TABLE— Continued

Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
458.70625	do	44	PX	460.15625	do	44	PP
458.7125	do	27	PX	460.1625	do	27	PP
458.71875	do	44	PX	460.16875	do	44	PP
458.725	do		PX	460.175	do		PP
458.73125	do	44	PX	460.18125	do	44	PP
458.7375	do	27	PX	460.1875	do	27	PP
458.74375	do	44	PX	460.19375	do	44	PP
458.750	do		PX	460.200	do		PP
458.75625	do	44	PX	460.20625	do	44	PP
458.7625	do	27	PX	460.2125	do	27	PP
458.76875	do	44	PX	460.21875	do	44	PP
458.775	do		PX	460.225	do		PP
458.78125	do	44	PX	460.23125	do	44	PP
458.7875	do	27	PX	460.2375	do	27	PP
458.79375	do	44	PX	460.24375	do	44	PP
458.800	do		PX	460.250	do		PP
458.80625	do	44	PX	460.25625	do	44	PP
458.8125		27	PX	460.2625	do	27	PP
400.0120	dodo	44	PX	460.26875	do	44	PP
458.81875			PX	460.275	do		PP
458.825	do			460.28125	do	44	PP
458.83125	do	44	PX	460.2875	do	27	PP
458.8375	do	27	PX	460.29375	do	44	PP
458.84375	do	44	PX	460.300	do		PP
458.850	do	81	PX	460.30625	do	44	PP
458.85625	do	44, 82	PX	460.3125	do	27	PP
458.8625	do	27, 80	PX	460.31875	do	44	PP
458.86875	do	44, 82	PX				PP
458.875	do	81	PX	460.325	do		PP
458.88125	do	44, 84	PX	460.33125	do	44	PP
458.8875	do	27, 84	PX	460.3375	do	27	PP
458.89375	do	44, 84	PX	460.34375	do	44	PP
458.900	do		PX	460.350	do		
458.90625	do	44. 84	PX	460.35625	do	44	PP
458.9125	do	27, 84	PX	460.3625	do	27	PP
458.91875	do	44, 84	PX	460.36875	do	44	PP
458.925	do		PX	460.375	do		PP
458.93125	do	44, 84	PX	460.38125	do	44	PP
458.9375	do	27, 84	PX	460.3875	do	27	PP
458.94375	do	44, 84	PX	460.39375	do	44	PP
458.950	do		PX	460.400	do		PP
458.95625		44, 84	PX	460.40625	do	44	PP
458.9625		27, 84	PX	460.4125	do	27	PP
		44 04	PX	460.41875	do	44	PP
458.96875	do	44, 84		460.425	do		PP
458.975	do		PX	460.43125	do	44	PP
458.98125	do	44, 84	PX	460.4375	do	27	PP
458.9875	do	27, 84	PX	460.44375	do	44	PP
458.99375	do	44, 84	PX	460.450	do		PP
460.0125	do	27, 64	PP	460.45625	do	44	PP
460.01875	Base or mobile	44	PP	460.4625	do	27	PP
460.025	do		PP	460.46875	do	44	PP
460.03125	do	44	PP	460.475	do		PP
460.0375	do	27	PP	460.48125	do	44, 84	PP
460.04375	do	44	PP	460.4875	do	27, 84	PP
460.050	do		PP	460.49375	do	44, 84	PP
460.05625	do	44	PP	460.500	do		PP
460.0625	do	27	PP	460.50625	do	44, 84	PP
460.06875	do	44	PP	460.5125		27, 84	PP
460.075	do		PP	460.51875	dodo	44, 84	PP
	do	44	PP				
460.08125			PP	460.525	do		PP, PF,
460.0875	do	27				l	PM
460.09375	do	44	PP	460.53125	do	44, 84	PP, PF,
460.100	do		PP				PM
460.10625	do	44	PP	460.5375	do	27, 84	PP, PF,
460.1125	do	27	PP				PM
460.11875	do	44	PP	460.54375	do	44, 84	PP, PF,
460.125	do		PP				PM
460.13125	do	44	PP	460.550	do		PP, PF,
460.1375	do	27	PP				PM
460.14375	do	44	PP	460.55625	do	44, 84	PP, PF,
460.150			PP			I .	PM

PUBLIC SAFETY POOL FREQUENCY TABLE— Continued

PUBLIC SAFETY POOL FREQUENCY TABLE— Continued

Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
460.5625	do	27, 84	PP, PF, PM	463.1625	do	27, 59, 66, 76.	PM
460.56875	do	44, 84	PP, PF, PM	463.16875	do	44, 59, 66, 76.	PM
460.575	do		PF	463.175	do	59, 66, 76	PM
460.58125	do	44	PF	463.18125	do	44, 59, 66,	PM
460.5875	do	27	PF			76.	
460.59375	do	44	PF	463.1875	do	27, 59, 66,	PM
460.600	do		PF			76.	
460.60625	do	44	PF	463.19375	do	44, 59, 66,	PM
460.6125	do	27	PF			76.	
460.61875	do	44	PF	465.0125	Mobile	57	PP
460.625	do		PF	465.025	do		PP
460.63125	do	44	PF	465.03125	do	44	PP
460.6375	do	27	PF	465.0375	do	27	PP
460.64375	do	44	PF	465.04375	do	44	PP
462.9375	do	57	PF	465.050	do		PP
462.950	do	38, 65	PM	465.05625	do	44	PP
462.95625	do	10, 44, 65	PM	465.0625	do	27	PP
462.9625	do	27, 10, 65	PM	465.06875	do	44	PP
462.96875	do	10, 44, 65	PM	465.075	do		PP
462.975	do	10, 65	PM	465.08125	do	44	PP
462.98125	do	10, 44, 65	PM	465.0875	do	27	PP
462.9875	do	27, 10, 65	PM	465.09375	do	44	PP
462.99375	do	10, 44, 65	PM	465.100	do		PP
463.000	do	59, 66, 67	PM	465.10625	do	44	PP
463.00625	do	44, 59, 66,	PM	465.1125	do	27	PP
		67.		465.11875	do	44	PP
463.0125	do	27, 59, 66,	PM	465.125	do		PP
		67.		465.13125	do	44	PP
463.01875	do	44, 59, 66,	PM	465.1375	do	27	PP
		67.		465.14375	do	44	PP
463.025	do	59, 66, 67	PM	465.150	do		PP
463.03125	do	44, 59, 66,	PM	465.15625	do	44	PP
		67.		465.1625	do	27	PP
463.0375	do	27, 59, 66,	РМ	465.16875	do	44	PP
100.0010		67.	l	465.175	do		PP
463.04375	do	44, 59, 66,	РМ	465.18125	do	44	PP
10010 1010 1111111		67.	l · ···	465.1875	do	27	PP
463.050	do	59, 66, 67	PM	465.19375	do	44	PP
463.05625	do	44, 59, 66,	PM	465.200	do		PP
		67.		465.20625	do	44	PP
463.0625	do	27, 59, 66,	PM	465.2125	do	27	PP
		67.		465.21875	do	44	PP
463.06875	do	44, 59, 66,	РМ	465.225	do		PP
		67.	l · ···	465.23125	do	44	PP
463.075	do	59, 66, 76	PM	465.2375	do	27	PP
463.08125	do	44, 59, 66,	PM	465.24375	do	44	PP
		76.		465.250	do		PP
463.0875	do	27, 59, 66,	PM	465.25625	do	44	PP
		76.		465.2625	do	27	PP
463.09375	do	44, 59, 66,	РМ	465.26875	do	44	PP
		76.	"	465.275	do		PP
463.100	do	59, 66, 76	PM	465.28125	do	44	PP
463.10625	do	44, 59, 66,	PM	465.2875	do	27	PP
		76.	l ·	465.29375	do	44	PP
463.1125	do	27, 59, 66,	РМ	465.300	do		PP
		76.	l · ···	465.30625	do	44	PP
463.11875	do	44, 59, 66,	РМ	465.3125	do	27	PP
		76.		465.31875	do	44	PP
463.125	do	59, 66, 76	РМ	465.325	do	44	PP
463.13125	do	44, 59, 66,	PM	465.33125	do	44	PP
TUU. IU IZU	uu	76.	' '''	465.3375	do		PP
463.1375	do		PM		do	27	PP
403.13/3	uu	27, 59, 66,	L. IAI	465.34375	do	44	
462 1427E	do	76.	PM	465.350	do		PP PP
463.14375	do	44, 59, 66,	L. IAI	465.35625	do	44	
100 150	مام	76.	DM	465.3625	do	27	PP
463.150	do	59, 66, 76	PM	465.36875	do	44	PP PP
400 4E00E							
463.15625	do	44, 59, 66, 76.	PM	465.375 465.38125	dodo	44	PP

Federal Communications Commission

PUBLIC SAFETY POOL FREQUENCY TABLE—Continued

Continued					
Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator		
465.3875	do	27	PP		
465.39375	do	44	PP		
465.400	do		PP		
465.40625	do	44	PP		
465.4125	do		PP		
465.41875	do	44	PP		
465.425	do		PP		
465.43125	do		PP		
465.4375	do	27	PP		
465.44375	do	44	PP		
465.450	do		PP		
465.45625	do	44	PP PP		
465.4625 465.46875	dodo	27	PP		
465.475	do	44	PP		
465.48125	do	44, 84	PP		
465.4875	do	27, 84	PP		
465.49375	do	27, 84 44, 84	PP		
465.500	do		PP		
465.50625	do	44, 84	PP		
465.5125	do	27, 84	PP		
465.51875	do	27, 84 44, 84	PP		
465.525	do		PP, PF,		
465.53125	do	44, 84	PM PP, PF,		
465.5375	do	27, 84	PM PP, PF,		
465.54375	do	44, 84	PM PP, PF,		
465.550	Base or mobile		PM PP, PF,		
465.55625	do	44, 84	PM PP, PF,		
465.5625	do	27, 84	PM PP, PF, PM		
465.56875	do	44, 84	PP, PF, PM		
465.575	Mobile		PF		
465.58125	do	44	PF		
465.5875	do	27	PF		
465.59375	do	44	PF		
465.600	do		PF		
465.60625	do	44	PF		
465.6125	do	27	PF		
465.61875	do	44	PF		
465.625	do		PF PF		
465.63125 465.6375	dodo	27	PF		
465.64375	do	44	PF		
467.9375	do	57	PS		
467.950	do	38, 65	PM		
467.95625	do	38, 44, 65	PM		
467.9625	do	27, 38, 65	PM		
467.96875	do	27, 38, 65 38, 44, 65	PM		
467.975	do	38, 65	PM		
467.98125	do	38, 44, 65	PM		
467.9875	do	27, 38, 65	PM		
467.99375	do	38, 44, 65	PM		
468.000	do		PM		
468.00625	do	44, 59, 66, 67.	PM		
468.0125	do	27, 59, 66, 67.	PM		
468.01875	do	44, 59, 66, 67.	PM		
468.025 468.03125	dodo	59, 66, 67 44, 59, 66, 67.	PM PM		
468.0375	do	27, 59, 66,	PM		

PUBLIC SAFETY POOL FREQUENCY TABLE—Continued

		-	
Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
468.04375	do	44, 59, 66, 67.	PM
468.050 468.05625	do	59, 66, 67 44, 59, 66, 67.	PM PM
468.0625	do	27, 59, 66, 67.	РМ
468.06875	do	44, 59, 66, 67.	РМ
468.075 468.08125	dodo	59, 66, 76 44, 59, 66, 76.	PM PM
468.0875	do	27, 59, 66, 76.	PM
468.09375	do	44, 59, 66, 76.	PM
468.100 468.10625	do	59, 66, 76 44, 59, 66, 76.	PM PM
468.1125	do	27, 59, 66, 76.	PM
468.11875	do	44, 59, 66, 76.	PM
468.125 468.13125	dodo	59, 66, 76 44, 59, 66, 76.	PM PM
468.1375	do	27, 59, 66, 76.	РМ
468.14375	do	44, 59, 66, 76.	РМ
468.150 468.15625	dodo	59, 66, 76 44, 59, 66, 76.	PM PM
468.1625	do	27, 59, 66, 76.	PM
468.16875	do	44, 59, 66, 76.	РМ
468.175 468.18125	dodo	59, 66, 76 44, 59, 66, 76.	PM PM
468.1875	do	27, 59, 66, 76.	РМ
468.19375	do	44, 59, 66, 76.	PM
470 to 512 763 to 775 793 to 805 806 to 817 851 to 862 928 and above	Base or mobile Base, mobile Mobiledodo Base or mobile Operational fixed.	68. 77 77 69. 69. 70.	PX PX
929 to 930 1,427 to 1,432	Base only Base, mobile or operational fixed.	71. O='xl'≤72.	
2,450 to 2,500 4940 to 4990	Base or mobile Fixed, base or mobile.	73. 85	
5850–5925	Base or mobile	86	Not appli- cable.
10,550 to 10,680.	do	74.	Cable.

(d) Explanation of assignment limitations appearing in the frequency table of paragraph (c)(3) of this section:

(1) This frequency is available for use by Travelers' Information Stations in accordance with § 90.242.

(2) The frequency is available for assignment only in accordance with a geographical assignment plan.

- (3) Base stations operating on this frequency and rendering service to state police mobile units may be authorized to use a maximum output power in excess of the maximum indicated in §90.205 but not in excess of 7500 watts: Provided, That such operation is secondary to other stations.
- (4) The use of this frequency is on a secondary basis to any Canadian station.
- (5) In addition to base and mobile stations, this frequency may be assigned to fixed stations on a secondary basis to base or mobile stations. Upon a showing of need, the use of a second frequency in the band 2505–3500 kHz may be made available to governmental entities through appropriate arrangements with Federal Government agencies for restricted area use on a shared basis with maximum power output, emission, and hours of operation determined on the basis of the technical conditions involved in using the selected frequency in the particular area.

(6) Only the central governments of the fifty individual States, the District of Columbia, and the insular areas of the Commonwealth of the Northern Mariana Islands, the Commonwealth of Puerto Rico, and the unincorporated territories of American Samoa, Guam and the United States Virgin Islands are eligible to be licensed to use this spectrum, and then only for disaster communications purposes. Licensees may not use this spectrum to provide operational communications circuits. See also, §90.264.

(7) This frequency is shared with the Industrial/Business Pool.

(8) This frequency is available for assignment only in accordance with a geographical assignment plan. This frequency may be used for conservation activities on a secondary basis to any station using the frequency for forest fire prevention, detection, and suppression.

(9) This frequency is reserved primarily for assignment to state licens-

ees. Assignments to other licensees will be made only where the frequency is required for coordinated operation with the State system to which the frequency is assigned. Any request for such assignment must be supported by a statement from the State system concerned, indicating that the assignment is necessary for coordination of activities.

(10) A licensee regularly conducting two-way communication operations on this frequency may, on a secondary basis, also transmit one-way alert-paging signals to ambulance and rescue squad personnel.

(11) The maximum output power of any transmitter authorized to operate on this frequency shall not exceed 10 watts.

(12) This frequency is available in this service only to persons eligible under the provisions of paragraph (a)(2)(v) of this section for operation of transmitters having a maximum power output of three watts using A1A, A1D, A2B, A2D, F1B, F1D, F2B, F2D, G1B, G1D, G2B, or G2D emission. This frequency is also available in the Industrial/Business Pool on a co-equal basis with the Public Safety licensees.

(13) This frequency will be assigned only for one-way paging communications to mobile receivers. Transmissions for the purpose of activating or controlling remote objects on this frequency are not authorized.

(14) The maximum output power of any transmitter authorized to operate on this frequency, after June 1, 1956, shall not exceed two watts. Licensees holding a valid authorization as of June 1, 1956, for base or mobile station operation on this frequency, with a power in excess of two watts, may continue to be authorized for such operation without regard to this power limitation.

(15) This frequency is reserved for assignment to stations for intersystem operations only: Provided, however, That licensees holding a valid authorization to use this frequency for local base or mobile operations as of June 1, 1956, may continue to be authorized for such use.

(16) This frequency is reserved primarily for assignment to state police licensees. Assignments to other police

licensees will be made only where the frequency is required for coordinated operation with the state police system to which the frequency is assigned. Any request for such assignment must be supported by a statement from the state police system concerned indicating that the assignment is necessary for coordination of police activities.

(17) In the State of Alaska only, the frequency 42.40 MHz is available for assignment on a primary basis to stations in the Common Carrier Rural Radio Service utilizing meteor burst communications. The frequency may be used by private radio stations for meteor burst communications on a secondary, noninterference basis. Usage shall be in accordance with part 22 of this chapter or part 90. Stations utilizing meteor burst communications shall not cause harmful interference to stations of other radio services operating in accordance with the allocation table.

(18) No new licenses will be granted for one-way paging under §90.487 for use on this frequency after August 1, 1980. This frequency is available to persons eligible for station licenses under the provisions of paragraph (a)(2)(v) of this section on a co-equal basis with one-way paging users under §90.487 prior to August 1, 1985, and on a primary basis after August 1, 1985. Only A1A, A1D, A2B, A2D, F1B, F1D, F2B, F2D, G1B, G1D, G2B, G2D emissions and power not exceeding 10 watts will be authorized. Antennas having gain greater than 0 dBd will not be authorized. Transmissions shall not exceed two seconds duration.

(19) This frequency is reserved for assignment to stations in this service for intersystem operations only and these operations must be primarily base-mobile communications.

(20) In the State of Alaska only, the frequency 45.90 MHz is available for assignment on a primary basis to private land mobile radio stations utilizing meteor burst communications. The frequency may be used by common carrier stations for meteor burst communications on a secondary, noninterference basis. Usage shall be in accordance with part 22 of this chapter and part 90. Stations utilizing meteor burst com-

munications shall not cause harmful interference to stations of other radio services operating in accordance with the allocation table.

(21) This frequency will be assigned only in accordance with a geographical assignment plan and is reserved primarily for assignment to Highway maintenance systems operated by states. The use of this frequency by other Highway maintenance licensees will be authorized only where such use is necessary to coordinate activities with the particular state to which the frequency is assigned. Any request for such use must be supported by a statement from the state concerned.

(22) Notwithstanding the provisions of paragraph (d)(21) of this section, this frequency may be used by any licensees in the Public Safety Pool without a separate license for the purpose of operating self-powered vehicle detectors for traffic control and safety purposes, on a secondary basis, in accordance with § 90.269.

(23) Thus frequency is reserved for assignment only to national organizations eligible for disaster relief operations under paragraph (a)(2)(vii) of this section.

(24) Assignment and use of frequencies in the band 72–76 MHz are governed by $\S 90.257$ for operational-fixed stations and by $\S 90.241$ for emergency call box operations. Specific frequencies are listed at $\S 90.257(a)(1)$.

(25) This frequency is available to Public Safety Pool licensees for fire call box operations on a shared basis in Industrial/Business Pool. All communications on this frequency must be conducted with persons or organizations charged with specific fire protection responsibility. All operations on this frequency are subject to the provisions of §90.257(b).

(26) Assignment of frequencies in this band are subject to the provisions of §90.173. Licensees as of August 18, 1995 who operate systems in the 150–170 MHz band that are 2.5 kHz removed from regularly assignable frequencies may continue to operate on a secondary, non-interference basis after August 1, 2003.

(27) This frequency will be assigned with an authorized bandwidth not to exceed $11.25~\mathrm{kHz}.$ In the $450\text{-}470~\mathrm{MHz}$

band, secondary telemetry operations pursuant to \$90.238(e) will be authorized on this frequency.

(28) This frequency is not available for assignment in this service in Puerto Rico or the Virgin Islands.

(29) This frequency is removed by 22.5 kHz from frequencies assigned to other radio services. Utilization of this frequency may result in, as well as be subject to, interference under certain operating conditions. In considering the use of this frequency, adjacent channel operations should be taken into consideration. If interference occurs, the licensee may be required to take the necessary steps to resolve the problem. See § 90.173(b).

(30) This frequency will be authorized a channel bandwidth of 25 kHz.

(31) The maximum output power of any transmitter authorized to operate on this frequency shall not exceed 100 watts. Stations authorized prior to July 15, 1992 for fixed operations will be permitted to continue such operations, but at a maximum transmitter power output of 10 watts.

(32) The maximum effective radiated power (ERP) may not exceed 20 watts for fixed stations and 2 watts for mobile stations. The height of the antenna system may not exceed 15.24 meters (50 ft.) above ground. All such operation is on a secondary basis to adjacent channel land mobile operations.

(33) For FM transmitters, the sum of the highest modulating frequency in Hertz and the amount of the frequency deviation or swing in Hertz may not exceed 2800 Hz and the maximum deviation may not exceed 2.5 kHz. For AM transmitters, the highest modulation frequency may not exceed 2000 Hz. The carrier frequency must be maintained within .0005 percent of the center of the frequency band, and the authorized bandwidth may not exceed 6 kHz.

(34) This frequency is available on a shared basis with the Industrial/Business Pool for remote control and telemetry operations.

(35) Operational fixed stations must employ directional antennas having a front-to-back ratio of at least 20 dB. Omnidirectional antennas having unity gain may be employed for stations communicating with at least three re-

ceiving locations separated by 160 degrees of azimuth.

(36) The maximum power output of the transmitter may not exceed 50 watts for fixed stations and 1 watt for mobile stations. A1A, A1D, A2B, A2D, F1B, F1D, F2D, G1B, G1D, G2B, or G2D emission may be authorized.

(37) Use of this frequency is limited to stations located at least 120.7 km (75 miles) from the center of any urbanized area of 200,000 or more population (U.S. Census of Population 1970). Operation is on a secondary basis to licensees of the Industrial/Business Pool.

(38) [Reserved]

(39) In addition to other authorized uses, the use of F1B, F1D, F2B or F2D emission is permitted on this frequency for the operation of biomedical telemetry systems except in the following geographic locations:

(i) New York, N.Y.-Northeastern New Jersey; Los Angeles-Long Beach, Calif.; Chicago, Ill.-Northwestern Indiana; Philadelphia, Pa.-N.J.; Detroit, Mich.; San Francisco-Oakland, Calif.; Boston, Mass.: Washington, D.C.-Md.-Va.; Cleveland, Ohio; St. Louis, Mo.-Ill.; Pittsburgh, Pa.; Minneapolis-St. Paul, Minn.; Houston, Tex.; Baltimore, Md.; Dallas, Tex.; Milwaukee, Wis.; Seattle-Everett, Wash.; Miami, Fla.; San Diego, Calif.; Atlanta, Ga.; Cincinnati, Ohio-Ky.; Kansas City, Mo.-Kans.; Buffalo, N.Y.; Denver, Colo.; San Jose, Calif.; New Orleans, La.; Phoenix, Ariz.; Portland, Oreg.-Wash.; Indianapolis, Ind.; Providence-Pawtucket-Warwick, R.I.-Mass.; Columbus, Ohio; San Antonio, Tex.; Louisville, Ky.-Ind.; Dayton, Ohio; Forth Worth, Tex.; Norfolk-Portsmouth, Va.; Memphis, Tenn.-Miss.; Sacramento, Calif.; Fort Lauderdale-Hollywood, Fla.; Rochester, N.Y.; Tampa-St. Petersburg, Fla;

(ii) The continuous carrier mode of operation may be used for telemetry transmissions on this frequency for periods up to two-minutes duration; following which there must be a break in the carrier for at least a one-minute period; and

(iii) Geographical coordinates for the above-listed urbanized areas may be found at Table 1 of § 90.635.

(40) This frequency may be designated by common consent as an

intersystem mutual assistance frequency under an area-wide medical communications plan.

- (41) This frequency is available nationwide for use in police emergency communications networks operated under statewide law enforcement emergency communications plans.
- (42) This frequency may not be assigned within 161 km (100 miles) of New Orleans, La. (coordinates 29°56′53″ N and 90°04′10″ W).
 - (43) [Reserved]
- (44) This frequency will be assigned with an authorized bandwidth not to exceed 6 kHz.
- (45) Operations on this frequency are limited to 30 watts transmitter output power.
- (46) This frequency is shared with the Industrial/Business Pool in Puerto Rico and the Virgin Islands.
- (47) This frequency may be assigned to stations in the Public Safety Pool in accordance with the provisions of \$90.265.
- (48) Frequencies in this band will be assigned only for transmitting hydrological or meteorological data or for low power wireless microphones in accordance with the provisions of \$90.265.
- (49) This frequency may be assigned only for forest firefighting and conservation activities in accordance with the provisions of § 90.265.
 - (50)-(51) [Reserved]
- (52) In addition to agencies responsible for forest fire prevention, detection, and suppression, this frequency may be assigned to conservation agencies which do not have forest fire responsibilities on a secondary basis to any U.S. Government stations, *Provided*, That such assignment is necessary to permit mobile relay operation by such agencies.
- (53) This frequency is subject to the provisions of paragraph (e)(6) of this section.
- (54) For FM transmitters, the sum of the highest modulating frequency in hertz and the amount of the frequency deviation or swing in hertz may not exceed 1700 Hz and the maximum deviation may not exceed 1.2 kHz. For AM transmitters, the highest modulating frequency may not exceed 1200 Hz. The carrier frequency must be maintained

- within .0005 percent of the center of the frequency band, and the authorized bandwidth may not exceed 3 kHz.
- (55) Subpart T of this part contains rules for assignment of frequencies in the 220-222 MHz band.
- (56) The frequencies available for use at fixed stations in this band and the requirements for assignment are set forth in §90.261. Operation on these frequencies is secondary to stations in the Industrial/Business Pool where they are assigned for land mobile operations.
- (57) This frequency is available for systems first licensed prior to August 18, 1995. No new systems will be authorized after August 18, 1995, but prior authorized systems may be modified, expanded, and renewed.
- (58) This frequency is available for systems first licensed prior to March 31, 1980, for radio call box communications related to safety on highways in accordance with the provisions of \$90.241(c). No new systems will be authorized of this nature, but systems authorized prior to March 31, 1980 may be modified, expanded, and renewed.
- (59) The continuous carrier mode of operation may be used for telemetry transmission on this frequency.
- (60) Paging licensees as of March 20, 1991, may continue to operate on a primary basis until January 14, 1998.
- (61) Highway radio call box operations first licensed prior to March 31, 1980 on this frequency may continue to operate in accordance with paragraph (d) (58) of this section.
- (62) This frequency is also authorized for use by biomedical telemetry stations. F1B, F1D, F2B, F2D, F3E, G1B, G1D, G2B, G2D, and G3E emissions may be authorized for biomedical transmissions.
- (63) Available for medical services mobile operations in the Public Safety Pool in accordance with paragraph (d) (61) of this section.
- (64) Use of this frequency is on a secondary basis, limited to 2 watts output power and subject to the provisions of 90.267(h)(1), (h)(2), (h)(3), and (h)(4).
- (65) This frequency is primarily authorized for use in the dispatch of medical care vehicles and personnel for the

rendition or delivery of medical services. This frequency may also be assigned for intra-system and inter-system mutual assistance purposes. For uniformity in usage these frequency pairs may be referred to by channel name as follows:

Frequencies base and mobile (megahertz)	Mobile only (MHz)	Channel name
462.950	467.950	MED-9
462.95625	467.95625	MED-91
462.9625	467.9625	MED-92
462.96875	467.96875	MED-93
462.975	467.975	MED-10
462.98125	467.98125	MED-101
462.9875	467.9875	MED-102
462.99375	467.99375	MED-103

(66) For applications for new radio systems, the thirty-two frequency pairs listed in paragraph (d)(66)(i) of this section will be assigned in a block for shared operation under \$90.20(a)(1)(iii) or \$90.20(a)(2)(xiii) subject to the following:

(i) For uniformity in usage, these frequency pairs may be referred to by channel name as follows:

Frequencies base and mobile (megahertz)	Mobile only (MHz)	Channel name
463.000	468.000	MED-1
463.00625	468.00625	MED-11
463.0125	468.0125	MED-12
463.01875	468.01875	MED-13
463.025	468.025	MED-2
463.03125	468.03125	MED-21
463.0375	468.0375	MED-22
463.04375	468.04375	MED-23
463.050	468.050	MED-3
463.05625	468.05625	MED-31
463.0625	468.0625	MED-32
463.06875	468.06875	MED-33
463.075	463.075	MED-4
463.08125	468.08125	MED-41
463.0875	468.0875	MED-42
463.09375	468.09375	MED-43
463.100	468.100	MED-5
463.10625	468.10625	MED-51
463.1125	468.1125	MED-52
463.11875	468.11875	MED-53
463.125	468.125	MED-6
463.13125	468.13125	MED-61
463.1375	468.1375	MED-62
463.14375	468.14375	MED-63
463.150	468.150	MED-7
463.15625	468.15625	MED-71
463.1625	468.1625	MED-72
463.16875	468.16875	MED-73
463.175	468.175	MED-8
463.18125	468.18125	MED-81
463.1875	468.1875	MED-82
463.19375	468.19375	MED-83

(ii) Except as provided in paragraphs (d)(66)(iv) and (v) of this section, mobile or portable stations licensed prior to July 6, 2000, must employ equipment

that is both wired and equipped to transmit/receive, respectively, on each of the following MED frequency pairs with transmitters operated on the 468 MHz frequencies: MED-1, MED-2, MED-3, MED-4, MED-5, MED-6, MED-7, and MED-8.

(iii) Except as provided in paragraphs (d)(66)(v) and (vi) of this section, mobile or portable stations licensed on or after July 6, 2000, must employ equipment that is both wired and equipped to transmit/receive, respectively, on each of the following MED frequency pairs with transmitters operated on the 468 MHz frequencies: MED-1, MED-12, MED-2, MED-22, MED-3, MED-32, MED-4, MED-42, MED-5, MED-52, MED-66 MED-62, MED-7, MED-72, MED-88, and MED-82.

(iv) Except as provided in paragraphs (d)(66)(v) and (vi) of this section, mobile or portable stations licensed on or after January 1, 2006, must employ equipment that is both wired and equipped to transmit/receive, respectively, on each of these MED frequency pairs with transmitters operated on the 468 MHz frequencies.

(v) Portable (hand-held) units operated with a maximum output power of 2.5 watts are exempted from the multichannel equipment requirements specified in paragraphs (d)(66)(ii), (d)(66)(iii), and (d)(66)(iv) of this section.

(vi) Stations located in areas above line A, as defined in $\S 90.7$ will be required to meet multi-channel equipment requirements only for those frequencies up to the number specified in paragraphs (d)(66)(ii), (d)(66)(iii), and (d)(66)(iv) of this section that have been assigned and coordinates with Canada in accordance with the applicable U.S.-Canada agreement.

(67) This frequency is authorized for use only for operations in biomedical telemetry stations. F1B, F1D, F2B, F2D, F3E, G1B, G1D, G2B, G2D and G3E emissions may be authorized. Entities eligible in the Public Safety Pool may use this frequency on a secondary basis for any other permissible communications consistent with §90.20(a)(1)(iii) or §90.20(a)(2)(xiii).

(68) Subpart L of this part contains rules for assignment of frequencies in the 470–512 MHz band.

- (69) Subpart S of this part contains rules for assignment of frequencies in the 806-817 MHz and 851-862 MHz bands.
- (70) Assignment of frequencies above 928 MHz for operational-fixed stations is governed by part 101 of this chapter.
- (71) Frequencies in this band are available only for one-way paging operations in accordance with § 90.494.
- (72) This frequency band is available to stations in this service subject to the provisions of § 90.259.
- (73) Available only on a shared basis with stations in other services, and subject to no protection from interference due to the operation of industrial, scientific, or medical (ISM) devices. In the band 2483.5-2500 MHz, no applications for new stations or modification to existing stations to increase the number of transmitters will be accepted. Existing licensees as of July 25, 1985, and licensees whose initial applications were filed on or before July 25, 1985, are grandfathered and their operations are on a co-primary basis with the mobile-satellite and radiodetermination-satellite services, and in the segment 2495-2500 MHz, their operations are also on a co-primary basis with part 27 fixed and mobile except aeronautical mobile service operations.
- (74) This band is available for Digital Termination Systems and for associated internodal links in the Point-to-Point Microwave Radio Service. No new licenses will be issued under this subpart but current licenses will be renewed.
- (75) Appropriate frequencies in the band 2000–3000 kHz which are designated in part 80 of this chapter as available to Public Ship Stations for telephone communications with Public Coast Stations may be assigned on a secondary basis to fixed Stations in the Public Safety Pool for communication with Public Coast Stations only, provided such stations are located in the United States and the following conditions are met:
- (i) That such fixed station is established pursuant to the eligibility provisions of (§ 90.47) and that the isolated area involved is an island or other location not more than 480 km (300 statute miles) removed from the desired;
- (ii) That evidence is submitted showing that an arrangement has been

- made with the coast station licensee for the handling of emergency communications permitted by \$80.453 of this chapter and \$90.20(a)(2)(x)(C); and
- (iii) That operation of the Public Safety fixed station shall at no time conflict with any provision of part 80 of this chapter and further, that such operation in general shall conform to the practices employed by Public Ship Stations for radiotelephone communication with the same Public Coast Station.
- (76) This frequency is authorized only for communications between medical facilities vehicles and personnel related to medical supervision and instruction for the treatment and transport of patients in the rendition or delivery of medical services. F1B, F1D, F2B, F2D, G1B, G1D, G2B, F3E and G3E emissions are authorized. Public Safety entities may use this frequency on a secondary basis for any other permissible communications consistent with §90.20(a)(1)(iii) or §90.20(a)(2)(xiii).
- (77) Subpart R of this part contains rules for assignment of channels in the 763-775 MHz and 793-805 MHz bands.
- (78) Paging operations are not permitted on this frequency.
- (79) This frequency will be secondary to marine port operations within 161 km (100 miles) of Los Angeles, Calif. (coordinates 34°03′15″ N and 118°14′28″ W).
- (80) After December 7, 2000 this frequency is available primarily for public safety interoperability only communications. Stations licensed prior to December 7, 2000 may continue to use this frequency on a co-primary basis until January 1, 2005. After January 1, 2005, all operations will be secondary to co-channel interoperability communications.
- (81) After December 7, 2000 new stations will only be licensed with an authorized bandwidth not to exceed 1125 kHz. Licensees authorized prior to December 7, 2000 may continue to use bandwidths wider that 1125 kHz on a co-primary basis until January 1, 2005. After January 1, 2005, all stations operating with an authorized bandwidth greater than 11.25 kHz will be secondary to adjacent channel interoperability operations.

- (82) This frequency is reserved for assignment only in support of, and on a secondary basis to, nationwide interoperability use.
- (83) This interoperability frequency is dedicated for the express purpose of nationwide interoperability calling.
- (84) Operation on this frequency is subject to the low power provisions of §90.267. This frequency is assigned to the Public Safety Group in the low power pool.
- (85) Subpart Y of this part contains rules for assignment of frequencies in the 4940-4990 MHz band.
- (86) Subpart M of this part contains rules for assignment of frequencies in the 5850–5925 MHz band.
- (87) The use the frequencies 150.775 MHz and 150.790 MHz are limited to a transmitter output power of 100 watts Effective Radiated Power (ERP) as of May 27, 2005.
- (88) Use of this frequency is limited to stations licensed as of May 27, 2005.
- (89) As of March 25, 2007, the FCC will cease to issue licenses for new stations in the fixed and mobile services in the following bands: 5900-5950 kHz, 7300-7350 kHz and 9400-9500 kHz. As of March 29, 2009, the FCC will cease to issue licenses for new stations in the fixed and mobile services in the band 7350-7400 kHz and, in the U.S. Pacific insular areas in Region 3, the band 7400-7450 kHz. Stations licensed as of March 25, 2007 in the bands 5900-5950 kHz. 7300-7350 kHz and 9400-9500 kHz and as of March 29, 2009 for the band 7350-7400 kHz in Region 2 and the band 7350-7450 kHz in Region 3 shall:
- (1) Be limited to communications only within the United States and its insular areas:
- (2) Not cause harmful interference to the broadcasting service;
- (3) Be limited to the minimum power needed to achieve communications; and
- (4) Take account of the seasonal use of frequencies by the broadcasting service published in accordance with Article 12 of the ITU *Radio Regulations*.
- (e) Additional frequencies available. In addition to the frequencies shown in the frequency table of this section, the following frequencies are available in this service. (See also § 90.253.)

- (1) Substitution of frequencies available below 25 MHz may be made in accordance with the provisions of §90.263.
- (2) Frequencies in the band 73.0-74.6 MHz may be assigned to stations authorized their use on or before December 1, 1961, but no new stations will be authorized in this band, nor will expansion of existing systems be permitted. See also §90.257.
- (3) The frequency bands 31.99-32.00 MHz, 33.00-33.01 MHz, 33.99-34.00 MHz, 37.93-38.00 MHz, 39.99-40.00 MHz, and 42.00-42.01 MHz, are available for assignment for developmental operation subject to the provisions of subpart Q of this part.
- (4) Frequencies in the 421–430 MHz band are available in the Detroit, Mich., Cleveland, Ohio and Buffalo, N.Y. areas in accordance with the rules in §§ 90.273 through 90.281.
- (5) A Police licensee may use transmitters on the frequencies indicated below in connection with official police activities without specific authorization from the Commission, provided that such use shall be on a secondary basis and shall not cause harmful interference to services of other licensees operating on regularly assigned frequencies, and further provided that all such use complies with the requirements of Federal, State and local laws. The provisions of §90.429 shall not apply to transmitters authorized under this paragraph. To be eligible for operations in this manner, the transmitter must comply with all of the following requirements.
- (i) In accordance with §§ 90.203 and 2.803 of this chapter, the transmitter must be of a type which has been certificated by the Commission.
- (ii) The carrier frequency shall be within the bands listed below and must be maintained within 0.005 percent of the frequency of operation. Use on assigned channel center frequencies is not required.

30.85-30.87 MHz	31.21-31.23 MHz
30.89-30.91 MHz	31.25-31.27 MHz
30.93-30.95 MHz	31.29-31.31 MHz
30.97-30.99 MHz	31.33-31.35 MHz
31.01-31.03 MHz	31.37-31.39 MHz
31.05-31.07 MHz	31.41-31.43 MHz
31.09-31.11 MHz	31.45-31.47 MHz
31.13-31.15 MHz	31.49-31.51 MHz
31.17-31.19 MHz	31.53-31.55 MHz

31.57-31.59 MHz 31.61-31.63 MHz 31.65-31.67 MHz 31.69-31.71 MHz 31.73-31.75 MHz 31.73-31.79 MHz 31.81-31.83 MHz 31.85-31.87 MHz 31.89-31.91 MHz 31.93-31.95 MHz 31.97-32.00 MHz 33.05-33.07 MHz 33.05-33.07 MHz 33.05-33.07 MHz 37.00-37.43 MHz 37.00-37.43 MHz 37.00-37.43 MHz 39.00-40.00 MHz 42.00-42.91 MHz	45.93-45.95 MHz 45.97-45.99 MHz 46.01-46.03 MHz 46.05-46.60 MHz 47.00-47.41 MHz 150.995-151.490 MHz 153.740-154.445 MHz 154.635-155.195 MHz 155.415-156.250 MHz 158.715-159.465 MHz 453.0125-453.9875 MHz 458.0125-460.5125 MHz 460.0125-460.5125 MHz 460.5625-460.6375 MHz 465.0125-465.5125 MHz 465.0125-465.5125 MHz 465.0125-465.5125 MHz
42.00–42.91 MHz 44.61–45.91 MHz	465.5625–465.6375 MHz 467.9375–467.9875 MHz

- (iii) The emitted signal shall be non-voice modulation (type PO emission).
- (iv) The maximum occupied bandwidth, containing 99 percent of the radiated power, shall not exceed 2.0 kHz.
- (v) The transmitter output power shall not exceed a mean power of 30 mW nor shall any peak exceed 1 watt peak power, as measured into a 50 ohm resistive load. Should the transmitter be supplied with a permanently attached antenna or should the transmitter and antenna combination be contained in a sealed unit, the following standard may be used in lieu of the above: the field strength of the fundamental signal of the transmitter and antenna combination shall not exceed 0.4 V/m mean or 2.3 V/m peak when measured at a distance of 3 meters.
- (vi) The transmitter shall contain positive means to limit the transmission time to no more than 10 days. In the event of a malfunction of this positive means, the transmitter signal shall cease. The use of battery life to accomplish the transmission time limitation is permissible.
- (6) The frequency 173.075 MHz is available for stolen vehicle recovery systems on a shared basis with Federal stations in the fixed and mobile services.
- (i) Stolen vehicle recovery systems are limited to tracking and recovering vehicles, cargo, and hazardous materials that have been reported stolen or missing; missing or wanted persons; and individuals at risk, or individuals of interest to law enforcement, only when established boundaries are violated. Stolen vehicle recovery systems

are not authorized for general purpose tracking or monitoring. Mobile units may also transmit automatic collision notifications, vehicle fire notifications, and carjacking alerts.

- (ii) Any type of emission may be used within a maximum authorized bandwidth of 12.5 kHz, except that stations that operate as part of a stolen vehicle recovery system that was authorized and in operation prior to May 27, 2005 may operate with a maximum authorized bandwidth of 20 kHz until May 27, 2019. For a complete listing of emission symbols allowable under this part, see §2.201 of this chapter.
- (iii) Mobile transmitters operating on this frequency with emissions authorized in a maximum bandwidth of 12.5 kHz are limited to 5.0 watts power output. Mobile transmitters operating on this frequency with emissions authorized in a maximum bandwidth of 20 kHz are limited to 2.5 watts power output.
- (iv) Base station transmitters operating on this frequency with emissions authorized in a maximum bandwidth of 12.5 kHz are limited to 300 watts ERP before February 18, 2009, and 500 watts ERP thereafter. Base station transmitters operating on this frequency with emissions authorized in a maximum bandwidth of 20 kHz are limited to 300 watts ERP.
- (v) Transmissions from mobiles shall be limited to 400 milliseconds for every 10 seconds, except when a vehicle is being tracked actively transmissions are limited to 400 milliseconds for every second. Alternatively, transmissions from mobiles shall be limited to 7200 milliseconds for every 300 seconds with a maximum of six such messages in any 30 minute period.
- (vi) Transmissions from base stations shall be limited to a total rate of five seconds every minute.
- (vii) Any entity eligible to hold authorizations in the Public Safety Pool in accordance with §\$90.20(a) and 90.111 of this chapter is authorized by this rule to operate mobile transmitters on this frequency. No license will be issued for mobile transmitters.
- (viii) Applications for base stations operating on this frequency shall require coordination with the Federal Government. Applicants shall perform

an analysis for each base station that is located within 169 km (105 miles) of a TV Channel 7 transmitter of potential interference to TV Channel 7 viewers. Applicants shall serve a copy of the analysis to the licensee of the affected TV Channel 7 transmitter upon filing the application with the Commission. Such base stations will be authorized if the applicant has limited fewer than 100 residences or if the applicant:

(A) Shows that the proposed site is the only suitable location (which, at the application stage, requires a showing that the proposed site is especially well-suited to provide the proposed service):

(B) Develops a plan to control any interference caused to TV reception from operations; and

(C) Agrees to make such adjustments in the TV receivers affected as may be necessary to eliminate interference caused by its operations.

(ix) The licensee must eliminate any interference caused by its operation to TV Channel 7 reception within 30 days after notification in writing by the Commission. If this interference is not removed within this 30-day period, operation of the base station must be discontinued. The licensee is expected to help resolve all complaints of interference.

(7) Frequencies governed by § 90.35(c) (17).

(f) Limitation on number of frequencies assignable. Normally only two frequencies or pairs of frequencies in the paired frequency mode of operation will be assigned for mobile service operations by a single applicant in a given area. The assignment of an additional frequency or pair of frequencies will be made only upon a satisfactory showing of need, except that:

(1) Additional frequencies above 25 MHz may be assigned in connection with the operation of mobile repeaters in accordance with \$90.247 notwithstanding this limitation;

(2) The frequency 39.06 MHz may be assigned notwithstanding this limitation:

(3) Frequencies in the 25-50 MHz, 150-170 MHz, 450-512 MHz and 902-928 MHz bands may be assigned for the operation of Location and Monitoring Service (LMS) systems in accordance with the provisions of subpart M of this part, notwithstanding this limitation;

(4) A licensee of a radio station in this service may operate radio units for the purpose of determining distance, direction, speed, or position by means of a radiolocation device on any frequency available for radiolocation purposes without additional authorization from the Commission, provided type accepted equipment or equipment authorized pursuant to §90.203(b)(4) and (b)(5) of this part is used, and all other rule provisions are satisfied. A licensee in this service may also operate, subject to all of the foregoing conditions and on a secondary basis, radio units at fixed locations and in emergency vehicles that transmit on the frequency 24.10 GHz, both unmodulated continuous wave radio signals and modulated FM digital signals for the purpose of alerting motorists to hazardous driving conditions or the presence of an emergency vehicle. Unattended and continuous operation of such transmitters will be permitted.

(5) A Police licensee may use, without special authorization from the Commission, any mobile service frequency between 40 and 952 MHz, listed in paragraph (c)(3) of this section, for communications in connection with physical surveillance, stakeouts, raids, and other such activities. Such use shall be on a secondary basis to operations of licensees regularly authorized on the assigned frequencies. The maximum output power that may be used for such communications is 2 watts. Transmitters, operating under this provision of the rules, shall be exempted from the station identification requirements of § 90.425. Use of frequencies not designated by a "PP" in the coordinator column of the frequency table in paragraph (c)(3) of this section, is conditional on the approval of the coordinator corresponding to each frequency. Spread spectrum transmitters may be operated on Public Safety Pool frequencies between 37 and 952 MHz, providing that they are certificated by the Commission under the provisions of §2.803 of this chapter and §90.203, and meet the following conditions:

- (i) Frequency hopping transmitters can be operated, with a maximum output power of 2 watts, on any Public Safety Pool frequency between 37 and 952 MHz listed in paragraph (c)(3) of this section. At least 20 hopping frequencies shall be used and the average time of occupancy on any frequency shall not be greater than $\frac{1}{100}$ second in every 2 seconds;
- (ii) Use of spread spectrum transmitters under paragraph (f)(4) of this section is subject to approval by the applicable frequency coordinator of the radio services of the district in which the license and equipment are to be used: and
- (iii) The use of direct sequence spread spectrum equipment is also permitted. Equipment must meet the technical standards of §15.247 of this chapter.
- (6) In addition to the frequencies assigned for mobile service operation, one base station frequency above 152 MHz may be assigned as a common frequency to all licensees in a particular area to permit intersystem communication between base stations or mobile stations or both. This frequency use will not be authorized in any area where all available frequencies are required for independent systems.
- (7) A licensee may use, without a specific authorization from the Commission, transmitters on the frequencies indicated below in connection with wildlife tracking and/or telemetry and in connection with official forestryconservation activities, provided that such use shall be on a secondary basis and shall not cause harmful interference to services of other licensees operating on regularly assigned frequencies. The provisions of §§ 90.203, 90.425, and 90.429 shall not apply to transmitters complying with this paragraph. To be eligible for operations in this manner, the transmitter must comply with all of the following reauirements.
- (i) The carrier frequency shall be within the bands listed below. The carrier frequency must be maintained within 0.005 percent of the frequency of operation.

Use on assigned channel center frequencies is not required.

	(MHZ)
31.17 to 31.19	31.85 to 31.87
31.21 to 31.23	31.89 to 31.91
31.25 to 31.27	31.93 to 31.95
31.29 to 31.31	31.97 to 31.99
31.33 to 31.35	44.63 to 44.65
31.37 to 31.39	44.67 to 44.69
31.41 to 31.43	44.71 to 44.73
31.45 to 31.47	44.75 to 44.77
31.49 to 31.51	44.79 to 44.81
31.53 to 31.55	44.83 to 44.85
31.57 to 31.59	44.87 to 44.89
31.61 to 31.63	44.91 to 44.93
31.65 to 31.67	44.95 to 44.97
31.69 to 31.71	44.99 to 45.01
31.73 to 31.75	45.03 to 45.05
31.77 to 31.79	151.145 to 151.475
31.81 to 31.83	159.225 to 159.465

(MIII7)

- (ii) The emitted signal shall be non-voice modulation (A1D, A2D, F1D, or F2D emission).
- (iii) The maximum occupied bandwidth, containing 99 percent of the radiated power, shall not exceed $0.25~\mathrm{kHz}.$
- (iv) The transmitter output power shall not exceed a mean power of 5 mW nor shall any peak exceed 100 mW peak power, as measured into a permanently attached antenna; or if the transmitter and antenna combination are contained in a sealed unit, the field strength of the fundamental signal of the transmitter and antenna combination shall not exceed 0.29 V/m mean or 1.28 V/m peak when measured at a distance of 3 meters.
- (v) The requirements of §90.175 regarding frequency coordination apply.
- (8) An additional frequency may be assigned for paging operations from those frequencies available under paragraph (d)(13) of this section.
- (9) The frequency 155.340 MHz may be assigned as an additional frequency when it is designated as a mutual assistance frequency as provided in paragraph (d)(40) of this section.
- (10) Additional frequencies may be assigned for fixed station operations.
- (11) The assignment of an additional frequency or frequencies may be authorized notwithstanding this limitation for common, intra-county, intra-fire-district, or intrastate fire coordination operations. The frequency or frequencies requested must be in accordance with a frequency utilization plan, for the area involved, on file with the Commission.

- (g) Former public correspondence working channel in the maritime VHF (156–162 MHz) band allocated for public safety use in 33 inland Economic Areas. (1) We define service areas in the marine VHF (156-162 MHz) band by forty-two geographic areas called VHF Public Coast (VPCSAs). Service Areas §80.371(c)(1)(ii) of this chapter (Public correspondence frequencies). VPCSAs are based on, and composed of one or more of, the U.S. Department of Commerce's 172 Economic Areas (EAs). See 60 Fed Reg. 13114 (Mar. 10, 1995). You may inspect and copy maps of the EAs and VPCSAs at the FCC Reference Center, Room CY A-257, 445 12th St., SW., Washington, DC 20554. These maps and data are also available on the FCC website at http://www.fcc.gov/oet/info/ maps/areas/. We number public correspondence channels in the maritime VHF (156-162 MHz) band as channels 24 to 28 and channels 84 to 88. Each channel number represents a channel pair. See §80.371(c) of this chapter.
- (2) In VHF Public Coast Service Areas (VPCSAs) 10-42, the duplex channel pair 157.250 MHz/161.850 MHz (VHF Maritime Channel 25) is allocated for public safety use by entities eligible for licensing under paragraph (a) of this section, and is designated primarily for the purpose of interoperability communications. See 47 CFR 80.371(c)(1)(ii) for the definitions of VPCSAs.
- (i) The channel pair 157.250 MHz/161.850 MHz was formerly allocated and assigned (under §80.371(c) (1997) of this chapter) as a public correspondence working channel in the maritime VHF 156-162 MHz band, and was also shared (under former §90.283 (1997) of this chapter) with private land mobile stations, including grandfathered public safety licensees. Thus, there are grandfathered licensees nationwide (maritime and private land mobile radio stations, including by rule waiver) operating on this channel both inside and outside of VPCSAs 10-42.
- (ii) The channel pairs 157.225 MHz/161.825 MHz and 157.275 MHz/161.875 MHz were formerly allocated and assigned under this section as public safety interoperability channels but were reallocated for assignment as VHF public coast station channels under §80.371(c)

- of this chapter. Public safety operations licensed on these channels as of March 2, 2009 or licensed pursuant to an application filed prior to September 19, 2008, may remain authorized to operate on the channels on a primary basis until March 4, 2024.
- (3) All applicants and licensees under this paragraph must comply with the relevant technical sections under this part unless otherwise stated in this paragraph (g) of this section using the following standards and procedures:
- (i) Provide evidence of frequency coordination in accordance with §90.175. Public safety coordinators except the Special Emergency Coordinator are certified to coordinate applications for the channel pair 157.250 MHz/161.850 MHz (i.e., letter symbol PX under paragraph (c)(2) of this section).
- (ii) Station power, as measured at the output terminals of the transmitter, must not exceed 50 Watts for base stations and 20 Watts for mobile stations, except in accordance with the provisions of paragraph (g)(3)(vi) of this section. Antenna height (HAAT) must not exceed 122 meters (400 feet) for base stations and 4.5 meters (15 feet) for mobile stations, except in accordance with paragraph (g)(3)(vi) of this section. Antenna height (HAAT) must not exceed 122 meters (400 feet) for base stations and 4.5 meters (15 feet) for mobile stations, except in accordance with paragraph (g)(3)(vi) of this section. Such base and mobile channels shall not be operated on board aircraft in flight.
- (iii) Frequency protection must be provided to other stations in accordance with the following guidelines for each channel and for each area and adjacent area:
- (A) Protect coast stations licensed prior to July 6, 1998, by the required separations shown in Table C below.
- (B) Protect stations described in paragraph (g)(2)(i) of this section, by frequency coordination in accordance $\S 90.175$ of this part.
- (C) Protect public safety stations granted under paragraph (g) of this section by frequency coordination in accordance with §90.175 of this part.
- (D) Where the Public safety designated channel is not a Public safety designated

channel in an adjacent VPCSA: Applicants shall engineer base stations such that the maximum signal strength at the boundary of the adjacent VPCSA does not exceed $5dB\mu V/m$.

(iv) The following table, along with the antenna height (HAAT) and power (ERP), must be used to determine the minimum separation required between proposed base stations and co-channel public coast stations licensed prior to July 6, 1998 under part 80 of this chapter. Applicants whose exact ERP or HAAT are not reflected in the table must use the next highest figure shown.

TABLE C—REQUIRED SEPARATION IN KILOMETERS (MILES) OF BASE STATION FROM PUBLIC COAST STATIONS

Base Station Characteristics					
HAAT	ERP (watts)				
Meters (feet)	400	300	200	100	50
15 (50)		135 (84) 151 (94) 167 (104) 177 (110)	129 (80) 145 (90) 161 (100) 183 (114)	129 (80) 137 (85) 153 (95) 169 (105)	116 (72) 130 (81) 145 (90) 159 (99)

(v) In the event of interference, the Commission may require, without a hearing, licensees of base stations authorized under this section that are located within 241 kilometers (150 miles) of a co-channel public coast, I/LT, or grandfathered public safety station licensed prior to July 6, 1998, or an international border, to reduce power, decrease antenna height, and/or install directional antennas.

Mobile stations must be operated only within radio range of their associated base station.

(vi) Applicants seeking to be licensed for stations exceeding the power/antenna height limits of the table in paragraph (g)(3)(iv) of this section must request a waiver of that paragraph and must submit with their application an interference analysis, based upon an appropriate, generallyaccepted terrain-based propagation model, that shows that co-channel protected entities, described in paragraph (g)(3)(iii) of this section, would receive the same or greater interference protection than the relevant criteria outlined in paragraph (g)(3)(iii) of this section.

(h) Spectrum leasing arrangements. Notwithstanding any other provisions of this section to the contrary, licensees in the Public Safety Radio Services (see part 90, subpart B) may enter into spectrum leasing arrangements (see part 1, subpart X of this chapter) with

entities providing communications in support of public safety operations.

[62 FR 18845, Apr. 17, 1997]

EDITORIAL NOTE: For FEDERAL REGISTER citations affecting §90.20, see the List of CFR Sections Affected, which appears in the Finding Aids section of the printed volume and on GPO Access.

§ 90.22 Paging operations.

Unless specified elsewhere in this part, paging operations may be authorized in the Public Safety Pool on any frequency except those assigned under the provisions of §90.20(d)(78). Paging operations on frequencies subject to §90.20(d)(78) authorized before August 17, 1974, may be continued only if they do not cause harmful interference to regular operations on the same frequencies. Such paging operations may be renewed indefinitely on a secondary basis to regular operations, except within 125 km (75 mi) of the following urbanized areas:

Urbanized area	North latitude	West longitude
New York, NY-Northeastern NJ	40-45-06.4	73-59-37.5
Los Angeles-Long Beach, CA	34-03-15.0	118-14-
		31.3
Chicago, IL	41-52-28.1	87-38-22.2
Philadelphia, PA-NJ	39-56-58.4	75-09-19.6
Detroit, MI	42-19-48.1	83-02-56.7
San Francisco-Oakland, CA	37-46-38.7	122-24-
		43.9
Boston, MA	42-21-24.4	71-03-23.2
Washington, DC-MD-VA	38-53-51.4	77-00-31.9
Cleveland, OH	41-29-51.2	81-41-49.5
St Louis, MO-IL	38-37-45.2	90-12-22.4
Pittsburgh, PA	40-26-19.2	79-59-59.2