

§ 15.401

(e) The frame period (a set of consecutive time slots in which the position of each time slot can be identified by reference to a synchronizing source) of an intentional radiator operating in these sub-bands shall be 20 milliseconds or 10 milliseconds/X where X is a positive whole number. Each device that implements time division for the purposes of maintaining a duplex connection on a given frequency carrier shall maintain a frame repetition rate with a frequency stability of at least 50 parts per million (ppm). Each device which further divides access in time in order to support multiple communication links on a given frequency carrier shall maintain a frame repetition rate with a frequency stability of at least 10 ppm. The jitter (time-related, abrupt, spurious variations in the duration of the frame interval) introduced at the two ends of such a communication link shall not exceed 25 microseconds for any two consecutive transmissions. Transmissions shall be continuous in every time and spectrum window during the frame period defined for the device.

(f) The frequency stability of the carrier frequency of the intentional radiator shall be maintained within ± 10 ppm over 1 hour or the interval between channel access monitoring, whichever is shorter. The frequency stability shall be maintained over a temperature variation of -20° to $+50^{\circ}$ C at normal supply voltage, and over a variation in the primary supply voltage of 85 percent to 115 percent of the rated supply voltage at a temperature of 20° C. For equipment that is capable only of operating from a battery, the frequency stability tests shall be performed using a new battery without any further requirement to vary supply voltage.

[58 FR 59180, Nov. 8, 1993; 59 FR 15269, Mar. 31, 1994. Redesignated at 59 FR 32852, June 24, 1994, as amended at 59 FR 32853, June 24, 1994; 59 FR 40835, Aug. 10, 1994; 59 FR 55373, Nov. 7, 1994; 60 FR 3303, Jan. 13, 1995; 69 FR 62621, Oct. 27, 2004]

47 CFR Ch. I (10–1–11 Edition)

Subpart E—Unlicensed National Information Infrastructure Devices

§ 15.401 Scope.

This subpart sets out the regulations for unlicensed National Information Infrastructure (U-NII) devices operating in the 5.15–5.35 GHz, 5.47–5.725 GHz and 5.725–5.825 GHz bands.

[69 FR 2686, Jan. 20, 2004]

§ 15.403 Definitions.

(a) *Access Point (AP)*. A U-NII transceiver that operates either as a bridge in a peer-to-peer connection or as a connector between the wired and wireless segments of the network.

(b) *Available Channel*. A radio channel on which a *Channel Availability Check* has not identified the presence of a radar.

(c) *Average Symbol Envelope Power*. The average symbol envelope power is the average, taken over all symbols in the signaling alphabet, of the envelope power for each symbol.

(d) *Channel Availability Check*. A check during which the U-NII device listens on a particular radio channel to identify whether there is a radar operating on that radio channel.

(e) *Channel Move Time*. The time needed by a U-NII device to cease all transmissions on the current channel upon detection of a radar signal above the DFS detection threshold.

(f) *Digital modulation*. The process by which the characteristics of a carrier wave are varied among a set of predetermined discrete values in accordance with a digital modulating function as specified in document ANSI C63.17–1998.

(g) *Dynamic Frequency Selection (DFS)* is a mechanism that dynamically detects signals from other systems and avoids co-channel operation with these systems, notably radar systems.

(h) *DFS Detection Threshold*. The required detection level defined by detecting a received signal strength (RSS) that is greater than a threshold specified, within the U-NII device channel bandwidth.

(i) *Emission bandwidth*. For purposes of this subpart the emission bandwidth shall be determined by measuring the width of the signal between two points,

one below the carrier center frequency and one above the carrier center frequency, that are 26 dB down relative to the maximum level of the modulated carrier. Determination of the emissions bandwidth is based on the use of measurement instrumentation employing a peak detector function with an instrument resolution bandwidth approximately equal to 1.0 percent of the emission bandwidth of the device under measurement.

(j) *In-Service Monitoring*. A mechanism to check a channel in use by the U-NII device for the presence of a radar.

(k) *Non-Occupancy Period*. The required period in which, once a channel has been recognized as containing a radar signal by a U-NII device, the channel will not be selected as an available channel.

(l) *Operating Channel*. Once a U-NII device starts to operate on an Available Channel then that channel becomes the Operating Channel.

(m) *Peak Power Spectral Density*. The peak power spectral density is the maximum power spectral density, within the specified measurement bandwidth, within the U-NII device operating band.

(n) *Maximum Conducted Output Power*. The total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (*e.g.*, alternative modulation methods), the *maximum conducted output power* is the highest total transmit power occurring in any mode.

(o) *Power Spectral Density*. The power spectral density is the total energy output per unit bandwidth from a pulse or sequence of pulses for which the transmit power is at its peak or maximum level, divided by the total duration of the pulses. This total time does not include the time between pulses during which the transmit power is off or below its maximum level.

(p) *Pulse*. A pulse is a continuous transmission of a sequence of modulation symbols, during which the average symbol envelope power is constant.

(q) *RLAN*. Radio Local Area Network.

(r) *Transmit Power Control (TPC)*. A feature that enables a U-NII device to dynamically switch between several transmission power levels in the data transmission process.

(s) *U-NII devices*. Intentional radiators operating in the frequency bands 5.15–5.35 GHz and 5.470–5.825 GHz that use wideband digital modulation techniques and provide a wide array of high data rate mobile and fixed communications for individuals, businesses, and institutions.

[69 FR 2687, Jan. 20, 2004, as amended at 69 FR 54036, Sept. 7, 2004]

§ 15.405 Cross reference.

(a) The provisions of subparts A, B, and C of this part apply to unlicensed U-NII devices, except where specific provisions are contained in subpart E. Manufacturers should note that this includes the provisions of §§ 15.203 and 15.205.

(b) The requirements of subpart E apply only to the radio transmitter contained in the U-NII device. Other aspects of the operation of a U-NII device may be subject to requirements contained elsewhere in this chapter. In particular, a U-NII device that includes digital circuitry not directly associated with the radio transmitter also is subject to the requirements for unintentional radiators in subpart B.

[63 FR 40835, July 31, 1998]

§ 15.407 General technical requirements.

(a) *Power limits*:

(1) For the band 5.15–5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 50 mW or 4 dBm + 10 log B, where B is the 26-dB emission bandwidth in MHz. In addition, the peak power spectral density shall not exceed 4 dBm in any 1-MHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the peak power spectral density shall be reduced by the