

accuracy specified in §15.711(b)(1), *i.e.* 50 meters. This capability is used with a TV bands database approved by the FCC to determine the availability of TV channels at a TVBD's location.

(e) *Mode I personal/portable device.* A personal/portable TVBD that does not use an internal geo-location capability and access to a TV bands database to obtain a list of available channels. A Mode I device must obtain a list of available channels on which it may operate from either a fixed TVBD or Mode II personal/portable TVBD. A Mode I device may not initiate a network of fixed and/or personal/portable TVBDs nor may it provide a list of available channels to another Mode I device for operation by such device.

(f) *Mode II personal/portable device.* A personal/portable TVBD that uses an internal geo-location capability and access to a TV bands database, either through a direct connection to the Internet or through an indirect connection to the Internet by way of fixed TVBD or another Mode II TVBD, to obtain a list of available channels. A Mode II device may select a channel itself and initiate and operate as part of a network of TVBDs, transmitting to and receiving from one or more fixed TVBDs or personal/portable TVBDs. A Mode II personal/portable device may provide its list of available channels to a Mode I personal/portable device for operation on by the Mode I device.

(g) *Network initiation.* The process by which a fixed or Mode II TVBD sends control signals to one or more fixed TVBDs or personal/portable TVBDs and allows them to begin communications.

(h) *Operating channel.* An available channel used by a TVBD for transmission and/or reception.

(i) *Personal/portable device.* A TVBD that transmits and/or receives radiocommunication signals at unspecified locations that may change. Personal/portable devices may only transmit on available channels in the frequency bands 512–608 MHz (TV channels 21–36) and 614–698 MHz (TV channels 38–51).

(j) *Receive site.* The location where the signal of a full service television station is received for rebroadcast by a television translator or low power TV station, including a Class A TV sta-

tion, or for distribution by a Multiple Video Program Distributor (MVPD) as defined in 47 U.S.C. 602(13).

(k) *Sensing only device.* A personal/portable TVBD that uses spectrum sensing to determine a list of available channels. Sensing only devices may transmit on any available channels in the frequency bands 512–608 MHz (TV channels 21–36) and 614–698 MHz (TV channels 38–51).

(l) *Spectrum sensing.* A process whereby a TVBD monitors a television channel to detect whether the channel is occupied by a radio signal or signals from authorized services.

(m) *Television band device (TVBD).* Intentional radiators that operate on an unlicensed basis on available channels in the broadcast television frequency bands at 54–60 MHz (TV channel 2), 76–88 MHz (TV channels 5 and 6), 174–216 MHz (TV channels 7–13), 470–608 MHz (TV channels 14–36) and 614–698 MHz (TV channels 38–51).

(n) *TV bands database.* A database system that maintains records of all authorized services in the TV frequency bands, is capable of determining the available channels as a specific geographic location and provides lists of available channels to TVBDs that have been certified under the Commission's equipment authorization procedures. TV bands databases that provide lists of available channels to TVBDs must receive approval by the Commission.

[75 FR 75835, Dec. 6, 2010]

#### § 15.705 Cross reference.

(a) The provisions of subparts A, B, and C of this part apply to TVBDs, except where specific provisions are contained in subpart H.

(b) The requirements of subpart H apply only to the radio transmitter contained in the TVBD. Other aspects of the operation of a TVBD may be subject to requirements contained elsewhere in this chapter. In particular, a TVBD that includes a receiver that tunes within the frequency range specified in §15.101(b) contains digital circuitry not directly associated with the radio transmitter is also subject to the requirements for unintentional radiators in subpart B.