

§ 24.130

(6) Three 100 kHz channels paired with 50 kHz channels:

Channel 23: 940.55–940.65 and 901.45–901.50 MHz;
Channel 24: 940.30–940.40 and 901.55–901.60 MHz; and
Channel 25: 940.45–940.55 and 901.85–901.90 MHz.

(b) Five frequencies are available for assignment on a regional basis as follows:

(1) One 50 kHz channel paired with 50 kHz channel:

Channel 12: 940.25–940.30 and 901.25–901.30 MHz.
Channel 13: RESERVED.

(2) Four 50 kHz channels paired with 12.5 kHz channels:

Channel 14: 930.55–930.60 and 901.7875–901.8000 MHz;
Channel 15: 930.60–930.65 and 901.8000–901.8125 MHz;
Channel 16: 930.65–930.70 and 901.8125–901.8250 MHz; and
Channel 17: 930.70–930.75 and 901.8250–901.8375 MHz.

(c) Seven frequencies are available for assignment on an MTA basis as follows:

(1) Three 50 kHz unpaired channels:

Channel 26: 901.35–901.40 MHz;
Channel 27: 901.40–901.45 MHz; and
Channel 28: 940.40–940.45 MHz.

(2) One 50 kHz channel paired with 50 kHz channel:

Channel 29: 930.80–930.85 and 901.95–902.00 MHz.

(3) One 100 kHz channel paired with 50 kHz channel:

Channel 30: 930.30–930.40 and 901.65–901.70 MHz.

(4) One 150 kHz channel paired with 50 kHz channel:

Channel 31: 930.85–931.00 and 901.7–901.75 MHz.

(5) One 100 kHz channel paired with 12.5 kHz channel:

Channel 32: 940.90–941 and 901.8375–901.85 MHz.

NOTE TO § 24.129: Operations in markets or portions of markets which border other countries, such as Canada and Mexico, will be subject to on-going coordination arrangements with neighboring countries.

[66 FR 29920, June 4, 2001]

47 CFR Ch. I (10–1–11 Edition)

§ 24.130 [Reserved]

§ 24.131 Authorized bandwidth.

The authorized bandwidth of narrowband PCS channels will be 10 kHz for 12.5 kHz channels and 45 kHz for 50 kHz channels. For aggregated adjacent channels, a maximum authorized bandwidth of 5 kHz less than the total aggregated channel width is permitted.

§ 24.132 Power and antenna height limits.

(a) Stations transmitting in the 901–902 MHz band are limited to 7 watts e.r.p.

(b) Mobile stations transmitting in the 930–931 MHz and 940–941 MHz bands are limited to 7 watts e.r.p.

(c) Base stations transmitting in the 930–931 MHz and 940–941 MHz bands are limited to 3500 watts e.r.p. per authorized channel and are unlimited in antenna height except as provided in paragraph (d) of this section.

(d)(1) MTA and regional base stations located between 200 kilometers (124 miles) and 80 kilometers (50 miles) from their licensed service area border are limited to the power levels in the following table:

Antenna HAAT in meters (feet) (see § 24.53 for HAAT HAAT calculation method)	Effective radiated power (e.r.p.) (watts)
183 (600) and below	3500
183 (600) to 208 (682)	3500 to 2584
208 (682) to 236 (775)	2584 to 1883
236 (775) to 268 (880)	1883 to 1372
268 (880) to 305 (1000)	1372 to 1000
305 (1000) to 346 (1137)	1000 to 729
346 (1137) to 394 (1292)	729 to 531
394 (1292) to 447 (1468)	531 to 387
447 (1468) to 508 (1668)	387 to 282
508 (1668) to 578 (1895)	282 to 206
578 (1895) to 656 (2154)	206 to 150
656 (2154) to 746 (2447)	150 to 109
746 (2447) to 848 (2781)	109 to 80
848 (2781) to 963 (3160)	80 to 58
963 (3160) to 1094 (3590)	58 to 42
1094 (3590) to 1244 (4080)	42 to 31
1244 (4080) to 1413 (4636)	31 to 22
Above 1413 (4636)	16

(2) For heights between the values listed in the table, linear interpolation shall be used to determine maximum e.r.p.

(e) MTA and regional base stations located less than 80 kilometers (50 miles) from the licensed service area