

Criteria for Microwave Systems,” May 1994 (TSB10–F).

(f) For microwave paths longer than 25 kilometers, the interference protection criterion shall be such that the interfering signal will not produce more than 1.0 dB degradation of the practical threshold of the microwave receiver for analog system, or such that the interfering signal will not cause an increase in the bit error rate (BER) from $10E-6$ to $10E-5$ for digital systems.

(g) The development of the C/I ratios and interference criteria specified in paragraphs (e) and (f) of this section and the methods employed to compute the interfering power at the microwave receivers shall follow generally acceptable good engineering practices. The procedures described for computing interfering signal levels in (Appendix I to this subpart E Appendix E of the Memorandum Opinion and Order, GEN Docket No. 90–314, FCC 94–144) shall be applied. Alternatively, procedures for determining interfering signal levels and other criteria as may be developed by the Electronics Industries Association (EIA), the Institute of Electrical and Electronics Engineers, Inc. (IEEE), the American National Standards Institute (ANSI) or any other recognized authority will be acceptable to the Commission.

[59 FR 32854, June 24, 1994, as amended at 61 FR 29691, June 21, 1996; 69 FR 75171, Dec. 15, 2004]

§ 24.238 Emission limitations for Broadband PCS equipment.

The rules in this section govern the spectral characteristics of emissions in the Broadband Personal Communications Service.

(a) *Out of band emissions.* The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

(b) *Measurement procedure.* Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent

of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (*i.e.* 1 MHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

(c) *Alternative out of band emission limit.* Licensees in this service may establish an alternative out of band emission limit to be used at specified band edge(s) in specified geographical areas, in lieu of that set forth in this section, pursuant to a private contractual arrangement of all affected licensees and applicants. In this event, each party to such contract shall maintain a copy of the contract in their station files and disclose it to prospective assignees or transferees and, upon request, to the FCC.

(d) *Interference caused by out of band emissions.* If any emission from a transmitter operating in this service results in interference to users of another radio service, the FCC may require a greater attenuation of that emission than specified in this section.

[67 FR 77192, Dec. 17, 2002]

POLICIES GOVERNING MICROWAVE RELOCATION FROM THE 1850–1990 MHZ BAND

§ 24.239 Cost-sharing requirements for broadband PCS.

Frequencies in the 1850–1990 MHz band listed in § 101.147(c) of this chapter have been allocated for use by PCS. In accordance with procedures specified in §§ 101.69 through 101.81 of this chapter, PCS entities (both licensed and unlicensed) are required to relocate the existing Fixed Microwave Services (FMS) licensees in these bands if interference to the existing FMS operations would occur. All PCS entities who benefit from spectrum clearance by other PCS entities or a voluntarily relocating