

§ 24.301

Building Height and Building Penetration Factors. The building height correction, BH, is a function of the average building height within the nominal coverage area of the base station. It is used in conjunction with the building penetration loss, BP, to adjust the expected interference contribution from that portion of the portables transmitting from within buildings. The adjustment is given by:

BP=20 dB in urban areas

BP=10 dB in suburban areas

BH=2.5×(nf-1) dB

where nf is the average height (number of floors) of the buildings in the area.

(Note that this formula implies a net gain when the average building height is greater than 8 floors). All buildings more than twice the average height should be considered individually. The contribution to BH from that portion of portables in the building above the average building height should be increased by a factor of 20Log(h) dB, where h is the height of the portables above the average building height in meters.

Channel Discrimination Factor. A factor based on the interference selectivity of the microwave receiver.

Propagation Model. The PCS to microwave path loss, L, is calculated using the Longley-Rice propagation model, Version 1.2.2., in the point-to-point mode. The Longley-Rice [1] model was derived from NBS Technical Note 101 [2], and updated in 1982 by Hufford [3]. Version 1.2.2 incorporated modifications described in a letter by Hufford [4] in 1985. Terrain elevations used as input to the model should be from the U.S. Geological Survey 3-second digitized terrain database.

Special Situations. If a cell size is large compared to the distance between the cell and a microwave receiving site so that it subtends an angle greater than 5 degrees, the cell should be subdivided and calculations should be based on the expected distribution of mobiles and portables within each subdivision.

If terrain elevations within a cell differ by more than a factor of two-to-one, the cell should be subdivided and microwave interference calculations should be based on the average terrain elevation for each subdivision.

If a co-channel PCS base station lies within the main beam of a microwave antenna (±5 degrees), there is no intervening terrain obstructions, and the power at the microwave receiver from that base station, assuming free space propagation, would be 3 dB or less below the interference threshold, interference will be assumed to exist unless the PCS licensee can demonstrate otherwise by specific path loss calculations based on terrain and building losses.

If any part of a cell or cell subdivision lies within the main beam of a co-channel microwave antenna, there is no intervening ter-

47 CFR Ch. I (10-1-11 Edition)

rain obstructions, and the accumulative power of 5 percent or less of the mobiles, assuming free space propagation would be 3 dB or less below the interference threshold, interference will be assumed to exist unless the PCS licensee can demonstrate otherwise by specific path loss calculations based on terrain and building losses.

If a building within a cell or cell subdivision lies within the main beam of a co-channel microwave antenna, there is no intervening terrain obstructions, and the cumulative power of 5 percent or fewer of the portables, assuming free space propagation, would be 3 dB or less below the interference threshold, interference will be assumed to exist unless the PCS licensee can demonstrate otherwise by specific path loss calculations based on terrain and building losses.

REFERENCES:

1. Longley, A.G. and Rice, P.L., "Prediction of Tropospheric Radio Transmission Loss Over Irregular Terrain, A Computer Method-1968", ESSA Technical Report ERL 79-ITS 67, Institute for Telecommunications Sciences, July 1968.
2. Rice, P.L. Longley, A.G., Norton, K.A., Barsis, A.P., "Transmission Loss Predictions for Tropospheric Communications Circuits," NBS Technical Note 101 (Revised), Volumes I and II, U.S. Department of Commerce, 1967.
3. Hufford, G.A., Longley, A.G. and Kissick, W.A., "A Guide to the use of the ITS Irregular Terrain Model in the Area Prediction Mode", NTIA Report 82-100, U.S. Department of Commerce, April 1982. Also, Circular letter, dated January 30, 1985, from G.A. Hufford, identifying modifications to the computer program.
4. Hufford, G.A., Memorandum to Users of the ITS Irregular Terrain Model, Institute for Telecommunications Sciences, U.S. Department of Commerce, January 30, 1985.

Subpart F—Competitive Bidding Procedures for Narrowband PCS

SOURCE: 59 FR 26747, May 24, 1994, unless otherwise noted.

§ 24.301 Narrowband PCS subject to competitive bidding.

Mutually exclusive initial applications for narrowband PCS service licenses are subject to competitive bidding. The general competitive bidding procedures set forth in part 1, subpart Q of this chapter will apply unless otherwise provided in this subpart.

[67 FR 45367, July 9, 2002]