

§ 25.219

47 CFR Ch. I (10–1–11 Edition)

where θ is defined in paragraph (c)(2) of this section. For the purposes of this section, the envelope may be exceeded by no more than 10% of the sidelobes provided no individual sidelobe exceeds the envelope given above by more than 6 dB. The region of the main reflector spillover energy is to be interpreted

as a single lobe and shall not exceed the envelope by more than 6 dB.

(h) *Extended Ku-band digital earth station operations.* (1) In the plane of the geostationary satellite orbit as it appears at the particular earth station location:

15–10log ₁₀ (N)–25log ₁₀ θ	dBW/4 kHz	For	1.5° ≤ θ ≤ 7°
– 6–10log ₁₀ (N)	dBW/4 kHz	For	7° < θ ≤ 9.2°
18–10log ₁₀ (N)–25log ₁₀ θ	dBW/4 kHz	For	9.2° < θ ≤ 48°
– 24–10log ₁₀ (N)	dBW/4 kHz	For	48° < θ ≤ 180°

where θ and the plane of the geostationary satellite orbit are defined in paragraph (c)(1) of this section, and N is defined below. For the purposes of this section, the peak EIRP of an individual sidelobe may not exceed the envelope defined above for θ between 1.5° and 7.0°. For θ greater than 7.0°, the envelope may be exceeded by no more than 10% of the sidelobes, provided no individual sidelobe exceeds the envelope given above by more than 3 dB. For digital SCPC using frequency division multiple access (FDMA) or time divi-

sion multiple access (TDMA) technique, N is equal to one. For digital SCPC using code division multiple access (CDMA) technique, N is the maximum number of co-frequency simultaneously transmitting earth stations in the same satellite receiving beam.

(2) In all other directions, or in the plane of the horizon including any out-of-plane potential terrestrial interference paths:

18–10log ₁₀ (N)–25log ₁₀ θ	dBW/4 kHz	For	3° ≤ θ ≤ 48°
– 24–10log ₁₀ (N)	dBW/4 kHz	For	48° < θ ≤ 85°

where θ is defined in paragraph (c)(2) of this section and N is defined in paragraph (h)(1) of this section. For the purposes of this section, the envelope may be exceeded by no more than 10% of the sidelobes provided no individual sidelobe exceeds the envelope given above by more than 6 dB. The region of the main reflector spillover energy is to be interpreted as a single lobe and shall not exceed the envelope by more than 6 dB.

[73 FR 70902, Nov. 24, 2008, as amended at 74 FR 57099, Nov. 4, 2009]

EFFECTIVE DATE NOTE: At 74 FR 9962, Mar. 9, 2009, § 25.218, which contains information collection and recordkeeping requirements, became effective with approval by the Office of Management and Budget for a period of three years.

§ 25.219 [Reserved]

§ 25.220 Non-conforming transmit/receive earth station operations.

(a)(1) This section applies to earth station applications other than ESV, VMES and 17/24 GHz BSS feeder link applications in which the proposed earth station operations do not fall

within the applicable off-axis EIRP envelope specified in § 25.218.

(2) The requirements for petitions to deny applications filed pursuant to this section are set forth in § 25.154.

(b) If an antenna proposed for use by the applicant does not comply with the antenna performance standards contained in § 25.209(a) and (b), the applicant must provide, as an exhibit to its FCC Form 312 application, the antenna gain patterns specified in § 25.132(b).

(c) [Reserved]

(d)(1) The applicant must submit the certifications listed in paragraphs (d)(1)(i) through (d)(1)(iv) of this section. The applicant will be authorized to transmit only to the satellite systems included in the coordination agreements referred to in the certification required by paragraph (d)(1)(ii) of this section. The applicant will be granted protection from receiving interference only with respect to the satellite systems included in the coordination agreements referred to in the certification required by paragraph (d)(1)(ii) of this section, and only to the