

§ 25.225 Geographic Service Requirements for 17/24 GHz Broadcasting Satellite Service.

(a) Each operator of a 17/24 GHz BSS space station that is used to provide video programming directly to consumers in the 48 contiguous United States (CONUS) must provide comparable service to Alaska and Hawaii, unless such service is not technically feasible or not economically reasonable from the authorized orbital location.

(b) Each operator of a 17/24 GHz BSS space station subject to paragraph (a) of this section must design and configure its space station to be capable of providing service to Alaska and Hawaii, that is comparable to the service that such satellites will provide to CONUS subscribers, from any orbital location capable of providing service to either Alaska or Hawaii to which it may be located or relocated in the future.

(c) If an operator of a 17/24 GHz BSS space station that is used to provide video programming directly to consumers in the United States relocates or replaces a 17/24 GHz BSS space station at a location from which service to Alaska and Hawaii had been provided by another 17/24 GHz BSS space station, the operator must use a space station capable of providing at least the same level of service to Alaska and Hawaii as previously provided from that location.

[72 FR 50033, Aug. 29, 2007]

§ 25.226 Blanket licensing provisions for domestic, U.S. Vehicle-Mounted Earth Stations (VMESs) receiving in the 10.95–11.2 GHz (space-to-Earth), 11.45–11.7 GHz (space-to-Earth), and 11.7–12.2 GHz (space-to-Earth) frequency bands and transmitting in the 14.0–14.5 GHz (Earth-to-space) frequency band, operating with Geostationary Satellites in the Fixed-Satellite Service.

(a) The following ongoing requirements govern all VMES licensees and operations in the 10.95–11.2 GHz (space-to-Earth), 11.45–11.7 GHz (space-to-Earth), 11.7–12.2 GHz (space-to-Earth) and 14.0–14.5 GHz (Earth-to-space) frequency bands receiving from and transmitting to geostationary orbit satellites in the fixed-satellite service. VMES licensees shall comply with the

requirements in either paragraph (a)(1), (a)(2) or (a)(3) of this section and all of the requirements set forth in paragraphs (a)(4) through (a)(9) and paragraphs (c), (d), and (e) of this section. Paragraph (b) of this section identifies items that shall be included in the application for VMES operations to demonstrate that these ongoing requirements will be met.

(1) The following requirements shall apply to a VMES that uses transmitters with off-axis EIRP spectral-densities lower than or equal to the levels in paragraph (a)(1)(i) of this section. A VMES, or VMES system, operating under this section shall provide a detailed demonstration as described in paragraph (b)(1) of this section. The VMES transmitter also shall comply with the antenna pointing and cessation of emission requirements in paragraphs (a)(1)(ii) and (a)(1)(iii) of this section.

(i) A VMES system shall not exceed the off-axis EIRP spectral-density limits and conditions defined in paragraphs (a)(1)(i)(A) through (D) of this section.

(A) The off-axis EIRP spectral-density emitted from the VMES, in the plane of the geostationary satellite orbit (GSO) as it appears at the particular earth station location, shall not exceed the following values:

- 15–10log(N)–25logθ dBW/4kHz for $1.5^\circ \leq \theta \leq 7^\circ$
- 6 – 10log(N) dBW/4kHz for $7^\circ < \theta \leq 9.2^\circ$
- 18 – 10log(N)–25logθ dBW/4kHz for $9.2^\circ < \theta \leq 48^\circ$
- 24 – 10log(N) dBW/4kHz for $48^\circ < \theta \leq 85^\circ$
- 14 – 10log(N) dBW/4kHz for $85^\circ < \theta \leq 180^\circ$

where theta (θ) is the angle in degrees from the line connecting the focal point of the antenna to the orbital location of the target satellite, the plane of the GSO is determined by the focal point of the antenna and the line tangent to the arc of the GSO at the orbital location of the target satellite. For VMES networks using frequency division multiple access (FDMA) or time division multiple access (TDMA) techniques, N is equal to one. For VMES networks using multiple co-frequency transmitters that have the same EIRP, N is the maximum expected number of co-frequency simultaneously transmitting VMES earth stations in the