

base stations in accordance with §§24.53(b) and (c) of this chapter exceeds the height benchmark ( $hb_m$ ).

(c) *Protection for receiving antennas not exceeding the height benchmark.* Absent agreement between the two licensees to the contrary, if a transmitting antenna of one BRS/EBS licensee's base station exceeds its applicable height benchmark and such licensee is notified by another BRS/EBS licensee that it is generating an undesired signal level in excess of  $-107$  dBm/5.5 megahertz at the receiver of a co-channel base station that is within its applicable height benchmark, then the licensee of the base station that exceeds its applicable height benchmark shall either limit the undesired signal at the receiver of the protected base station to  $-107$  dBm/5.5 megahertz or less or reduce the height of its transmission antenna to no more than the height benchmark. If the interfering base station has been modified to increase the EIRP transmitted in the direction of the protected base station, it shall be deemed to have commenced operations on the date of such modification. Such corrective action shall be completed no later than:

(i) 24 hours after receiving such notification, if the base station that exceeds its height benchmark commenced operations after the station that is within its applicable height benchmark; or

(ii) 90 days after receiving such notification, if the base station that exceeds its height commenced operations prior to the station that is within its applicable height benchmark. For purposes of this section, if the interfering base station has been modified to increase the EIRP transmitted in the direction of the victim base station, it shall be deemed to have commenced operations on the date of such modification.

(d) *No protection from a transmitting antenna not exceeding the height benchmark.* The licensee of a base station transmitting antenna less than or equal to its applicable height benchmark shall not be required pursuant to paragraph (c) of this section to limit that antennas undesired signal level to  $-107$  dBm/5.5 megahertz or less at the receiver of any co-channel base station.

(e) *No protection for a receiving-antenna exceeding the height benchmark.* The licensee of a base station receive antenna that exceeds its applicable height benchmark shall not be entitled pursuant to paragraph (c) of this section to insist that any co-channel base station limit its undesired signal level to  $-107$  dBm/5.5 megahertz or less at the receiver.

(f) *Information exchange.* A BRS/EBS licensee shall provide the geographic coordinates, the height above ground level of the center of radiation for each transmit and receive antenna, and the date transmissions commenced for each of the base stations in its GSA within 30 days of receipt of a request from a co-channel BRS/EBS licensee with an operational base station located in a proximate GSA. Information shared pursuant to this section shall not be disclosed to other parties except as required to ensure compliance with this section.

[69 FR 72034, Dec. 10, 2004, as amended at 70 FR 1190, Jan. 6, 2005; 71 FR 35191, June 19, 2006; 73 FR 26041, May 8, 2008]

#### **§ 27.1222 Operations in the 2568–2572 and 2614–2618 bands.**

All operations in the 2568–2572 and 2614–2618 MHz bands shall be secondary to adjacent-channel operations. Stations operating in the 2568–2572 and 2614–2618 MHz must not cause interference to licensees in operation in the LBS, MBS, and UBS and must accept any interference from any station operating in the LBS, MBS, and UBS in compliance with the rules established in this subpart. Stations operating in the 2568–2572 and 2614–2618 bands may cause interference to stations in operation in the LBS, MBS, and UBS if the affected licensees consent to such interference.

#### **POLICIES GOVERNING THE TRANSITION OF THE 2500–2690 MHz BAND FOR BRS AND EBS**

#### **§ 27.1230 Conversion of the 2500–2690 MHz band.**

BRS and EBS licensees in the 2500–2690 MHz band on the pre-transition A-I Channels will be transitioned from the frequencies assigned to them under § 27.5(i)(1) to the frequencies assigned to