base stations in accordance with $\S\S24.53(b)$ and (c) of this chapter exceeds the height benchmark (hb_m).

- (c) Protection for receiving antennas not exceeding the height benchmark. Absent agreement between the two licensees to the contrary, if a transmitting antenna of one BRS/EBS licensee's base station exceeds its applicable height benchmark and such licensee is notified by another BRS/EBS licensee that it is generating an undesired signal level in excess of -107 dBm/5.5 megahertz at the receiver of a co-channel base station that is within its applicable height benchmark, then the licensee of the base station that exceeds its applicable height benchmark shall either limit the undesired signal at the receiver of the protected base station to -107dBm/5.5 megahertz or less or reduce the height of its transmission antenna to no more than the height benchmark. If the interfering base station has been modified to increase the EIRP transmitted in the direction of the protected base station, it shall be deemed to have commenced operations on the date of such modification. Such corrective action shall be completed no later than:
- (i) 24 hours after receiving such notification, if the base station that exceeds its height benchmark commenced operations after the station that is within its applicable height benchmark; or
- (ii) 90 days after receiving such notification, if the base station that exceeds its height commenced operations prior to the station that is within its applicable height benchmark. For purposes of this section, if the interfering base station has been modified to increase the EIRP transmitted in the direction of the victim base station, it shall be deemed to have commenced operations on the date of such modification.
- (d) No protection from a transmitting antenna not exceeding the height benchmark. The licensee of a base station transmitting antenna less than or equal to its applicable height benchmark shall not be required pursuant to paragraph (c) of this section to limit that antennas undesired signal level to -107dBm/5.5 megahertz or less at the receiver of any co-channel base station.

- (e) No protection for a receiving-antenna exceeding the height benchmark. The licensee of a base station receive antenna that exceeds its applicable height benchmark shall not be entitled pursuant to paragraph (c) of this section to insist that any co-channel base station limit its undesired signal level to -107dBm/5.5 megahertz or less at the receiver.
- (f) Information exchange. A BRS/EBS licensee shall provide the geographic coordinates, the height above ground level of the center of radiation for each transmit and receive antenna, and the date transmissions commenced for each of the base stations in its GSA within 30 days of receipt of a request from a co-channel BRS/EBS licensee with an operational base station located in a proximate GSA. Information shared pursuant to this section shall not be disclosed to other parties except as required to ensure compliance with this section.

[69 FR 72034, Dec. 10, 2004, as amended at 70 FR 1190, Jan. 6, 2005; 71 FR 35191, June 19, 2006; 73 FR 26041, May 8, 2008]

§ 27.1222 Operations in the 2568–2572 and 2614–2618 bands.

All operations in the 2568-2572 and 2614-2618 MHz bands shall be secondary to adjacent-channel operations. Stations operating in the 2568-2572 and 2614-2618 MHz must not cause interference to licensees in operation in the LBS, MBS, and UBS and must accept any interference from any station operating in the LBS, MBS, and UBS in compliance with the rules established in this subpart. Stations operating in the 2568-2572 and 2614-2618 bands may cause interference to stations in operation in the LBS, MBS, and UBS if the affected licensees consent to such interference.

POLICIES GOVERNING THE TRANSITION OF THE 2500–2690 MHz BAND FOR BRS AND EBS

§ 27.1230 Conversion of the 2500–2690 MHz band.

BRS and EBS licensees in the 2500–2690 MHz band on the pre-transition A-I Channels will be transitioned from the frequencies assigned to them under §27.5(i)(1) to the frequencies assigned to

§ 27.1231

them under §27.5(i)(2). The transition, which will be undertaken by one or more proponent(s), will occur in the following five phases: initiating the transition process (see §27.1231), planning the transition (see §27.1232), reimbursing transition costs (see §27.1233 and 27.1237–1239), terminating existing operations in transitioned markets that do not comport with §27.5(i)(2) (see §27.1234), and filing the post-transition notification (see §27.1235). Licensees may also self-transition (see §27.1236).

[71 FR 35191, June 19, 2006]

§27.1231 Initiating the transition.

- (a) Transition areas. Unless paragraph (b) of this section applies, the transition will occur by Basic Trading Area (BTA). BTAs are based on the Rand McNally 1992 Commercial Atlas & Marketing Guide, 123rd Edition, at pages 38-39, that identifies 487 BTAs based on the 50 States: it also includes the following additional BTA-like areas: American Samoa; Guam; Northern Mariana Islands; Mayaguez/Aguadilla-Ponce, Puerto Rico; San Juan, Puerto Rico: and the United States Virgin Islands, for a total of 493 BTAs. The Mayaguez/Aguadilla-Ponce BTA-like area consists of the following municipios: Adjuntas, Aguada, Aguadilla, Anasco, Arroyo, Cabo Rojo, Coamo, Guanica, Guayama, Guayanilla, Hormigueros, Isabela, Jayuya, Juana Diaz, Lajas, Las Marias, Maricao, Maunabo, Mayaguez, Moca, Patillas, Penuelas, Ponce, Quebradillas, Rincon, Sabana Grande, Salinas, San German, Santa Isabel, Villalba, and Yauco. The San Juan BTA-like area consists of all other municipios in Puerto Rico. The BTA associated with the Gulf of Mexico will not be transitioned.
- (b) Overlapping GSAs. When a Geographic Service Area (GSA) overlaps two or more BTAs:
- (1) The proponents of the adjacent BTAs may agree on how to transition a GSA that overlaps their respective BTAs
- (2) If an agreement has not been reached between or among the proponents of the adjacent BTAs:
- (i) Each proponent must transition all of the facilities associated with the GSA that are inside the GSA and inside

the proponent's BTA if all of the adjacent BTAs are transitioning; or

- (ii) The proponent of the BTA that is transitioning must transition all of the facilities associated with the GSA that are within the GSA but outside the BTA, if the adjacent BTA is not transitioning.
- (c)(1) *Proponent(s)*. The proponent or co-proponent must:
- (i) Be a BRS or EBS licensee or BRS or EBS lessee;
- (ii) Send a Pre-Transition Data Request (see paragraph (d) of this section) and a Transition Notice (see paragraph (e) of this section) to every BRS and EBS licensee in the BTA, using the contact information in the Commission's Universal Licensing System; and
- (iii) Be first to file an Initiation Plan (see paragraph (f) of this section) with the Secretary of the Commission.
- (2) Before filing an Initiation Plan, BRS or EBS licensees or BRS or EBS lessees may agree to be co-proponents. After the Initiation Plan is filed the proponent may accept a co-proponent at its sole discretion.
- (d) Pre-Transition Data Request. The Pre-Transition Data Request must include the potential proponent's full name, postal mailing address, contact person, e-mail address, and phone and fax numbers.
- (1) BRS and EBS licensees that receive a Pre-Transition Data Request must provide the following information to the potential proponent within 45 days of receiving the Pre-Transition Data Request:
- (i) The BRS or EBS licensee's full name, postal mailing address, contact person, e-mail address, and phone and fax number.
- (ii) The location (by street address and by geographic coordinates) of every constructed EBS receive site that, as of the date of receipt of the Pre-Transition Data Request, is entitled to a replacement downconverter (see § 27.1233(a)). The response must:
- (A) Specify whether the downconverting antenna is mounted on a structure attached to the building or on a free-standing structure;
- (B) Specify the approximate height above ground level of the downconverting antenna; and