§90.267

47 CFR Ch. I (10–1–11 Edition)

(c) No protection is afforded to users of these frequencies from harmful interference caused by foreign operations.

(d) In the event that a complaint of harmful interference resulting from operation of these circuits is received from a foreign source, the offending circuit(s) must cease operation on the particular frequency concerned immediately upon notification by the Commission.

(e) In order to accommodate the situations described in paragraphs (c) and (d) of this section, the equipment shall be capable of transmitting and receiving on any frequency within the bands between 2 and 25 MHz and capable of immediate change among the frequencies, provided, however, that this requirement does not apply to equipment manufactured prior to August 15, 1983.

(f) Only 2K80J3E, 100HA1A, 100HA1B and those emission types listed in §90.237(g) are permitted.

(g) Applicants must fulfill eligibility requirements set out in §90.35(c)(1) and submit communications plans pursuant to §90.129(o).

(h) Exercises or circuits tests which require use of these frequencies for more than seven hours per week cumulative are prohibited unless prior written approval is obtained from the Commission.

[48 FR 32996, July 20, 1983, as amended at 49 FR 48712, Dec. 14, 1984; 52 FR 29856, Aug. 12, 1987; 62 FR 18929, Apr. 17, 1997]

§90.267 Assignment and use of frequencies in the 450–470 MHz band for low power use.

(a) The following frequencies between 450-470 MHz are designated for lowpower use subject to the provisions of this section. For purposes of this section these frequencies are referred to as "low power frequencies." Pairs are shown but single frequencies are available for simplex operations.

(b) Group A1 Frequencies. The Industrial/Business Pool frequencies in Group A1 are available on a coordinated basis, pursuant to §§90.35(b)(2) and 90.175(b), as follows:

(1) Group A1 frequencies are available for voice and non-voice operations on a co-primary basis. Base, mobile and operational fixed stations will be authorized on Group A1 frequencies. Fixed stations may be licensed as mobile.

(2) Within 80 kilometers (50 miles) of the specified coordinates of the top 100 urban areas listed in $\S90.741$ of this chapter ("80 km circles") only low power operation will be authorized. The coordinates of an operational fixed or base station and the geographic center (latitude and longitude) of a mobile area of operation determine whether a station is within an "80 km circle."

(i) The maximum ERP for low power operation on Group A1 frequencies is as follows:

Operation	Low side of frequency pair (watts)	High side of frequency pair (watts)
Operational Fixed or Base	20	6
Mobile	6	6
Portable	2	2

(ii) The maximum antenna height for low power fixed stations on Group A1 frequencies will be 23 meters (75 feet) above ground.

(3) Outside the "80 km circles" defined in paragraph (b)(2), full-power operational fixed, base, or mobile stations will be authorized as follows:

(i) Power and antenna height limits are governed by §90.205 of this chapter;

(ii) For any operational fixed, base or mobile station exceeding the low power or antenna height limits listed in paragraph (b)(2), the 21 dBu F(50,10) contour may not overlap any portion of an "80 km circle;" and,

(iii) Wide area operations will not be permitted. The area of normal day-today operations will be described in the application in terms of maximum distance from a geographic center (latitude and longitude).

(4) The Industrial/Business Pool Group A1 Low Power Frequencies are as follows:

451/456.18125	451/456.58125	452/457.10625	452/457.70625
451/456.1875	451/456.5875	452/457.1125	452/457.7125
451/456.19375	451/456.59375	452/457.11875	452/457.71875

Federal Communications Commission

451/456.28125	451/456.60625
451/456.2875	451/456.6125
451/456.29375	451/456.61875
451/456.30625	451/456.65625
451/456.3125	451/456.6625
451/456.31875	451/456.66875
451/456.35625	451/456.68125
451/456.3625	451/456.6875
451/456.36875	451/456.69375
451/456.38125	451/456.70625
451/456.3875	451/456.7125
451/456.39375	451/456.71875
451/456.40625	451/456.73125
451/456.4125	451/456.7375
451/456.41875	451/456.74375
451/456.45625	451/456.75625
451/456.4625	451/456.7625
451/456.46875	451/456.76875
451/456.48125	452/457.03125
451/456.4875	452/457.0375
451/456.49375	452/457.04375
451/456.50625	452/457.05625
451/456.5125	452/457.0625
451/456.51875	452/457.06875
451/456.55625	452/457.08125
451/456.5625	452/457.0875
451/456.56875	452/457.09375

452/457.13125 452/457.78125 452/457.7875 452/457.1375 452/457.14375 452/457.79375 452/457.80625 452/457.15625 452/457.1625452/457.8125452/457.16875 452/457.81875 452/457.83125 452/457.18125 452/457.1875452/457.8375 452/457.19375 452/457.84375 452/457.28125 452/457.88125 452/457.2875 452/457.8875 452/457.29375 452/457.89375 452/457.48125 452/457.98125 452/457.4875 452/457.9875 452/457.49375452/457.99375 462/467.18125 452.53125 (unpaired) 452.5375 (unpaired) 462/467.1875 452.54375 (unpaired) 462/467.19375 452/457.63125 462/467.45625 452/457.6375 462/467.4625452/457.64375 462/467.46875 452/457.65625 462/467.48125 452/457.6625 462/467.4875 452/457.66875 462/467.49375 452/457.68125 462/467.50625 452/457.6875 462/467.5125452/457.69375 462/467.51875

(c) *Group A2 Frequencies*. The Industrial/Business Pool frequencies in Group A2 are available nationwide on a coordinated basis, pursuant §§ 90.35(b)(2) and 90.175(b) as follows:

(1) Group A2 frequencies are available for voice and non-voice operations on a co-primary basis. Base, mobile or operational fixed stations will be authorized on Group A2 frequencies. Fixed stations may be licensed as mobile.

(2) Low power operation will be authorized nationwide on Group A2 frequencies.

(i) The maximum ERP for low power operation on these frequencies is as follows:

Operation	Low side of frequency pair	High side of frequency pair (watts)
Operational Fixed or Base	20	6
Mobile	6	6
Portable	2	2

(ii) The maximum antenna height for low power fixed stations will be 23 meters (75 feet) above ground.

(3) The Industrial/Business Pool Group A2 Low Power Frequencies are as follows:

$\begin{array}{c} 451/456.23125\\ 451/456.2375\\ 451/456.24375\\ 451/456.33125\\ 451/456.3375\\ 451/456.34375\\ 451/456.43125\\ 451/456.4375\\ 451/456.4375\\ 451/456.44375\end{array}$	$\begin{array}{c} 451/456.53125\\ 451/456.5375\\ 451/456.54375\\ 451/456.63125\\ 451/456.6375\\ 451/456.64375\\ 452/457.30625\\ 452/457.3125\\ 452/457.31875\\ \end{array}$	$\begin{array}{r} 452/457.40625\\ 452/457.4125\\ 452/457.41875\\ 452/457.50625\\ 452/457.5125\\ 452/457.51875\\ 452/457.75625\\ 452/457.7625\\ 452/457.7625\\ 452/457.76875\end{array}$	452/457.85625 452/457.8625 452/457.86875
---	---	---	--

(d) Group B Frequencies. The Industrial/Business Pool frequencies in Group B are available nationwide on a

§ 90.267

462/467.26875

coordinated basis, pursuant to §§ 90.35(b)(2) and 90.175(b) as follows:

(1) Group B frequencies are available for non-voice operations on a primary basis. Voice operations will be permitted on a secondary basis. Base, mobile or operational fixed stations will be authorized on Group B frequencies. Fixed stations may be licensed as mobile.

462/467.20625 462/467.28125 462/467.2125 462/467.2875 462/467.21875 462/467.29375 462/467.23125 462/467.30625462/467.2375 462/467.3125 462/467.24375 462/467.31875 462/467.25625 462/467.33125 462/467.2625 462/467.3375

462/467.34375

(e) Group C Frequencies. The Industrial/Business Pool frequencies in Group C are available nationwide for non-coordinated itinerant use as follows.

(1) Group C frequencies are available for voice and non-voice operations on a co-primary basis. Only mobile operations will be authorized on Group C frequencies. Stations may operate at fixed locations for a temporary period of time. No stations operating at a per-

47	CFR	Ch.	L	(10-	1-1	1	Edition)
----	-----	-----	---	------	-----	---	----------

(2) Operation on these frequencies is limited to 6 watts ERP for base, mobile or operational fixed stations and 2 watts ERP for portable units. A maximum antenna height of 7 meters (20 ft) above ground is authorized for fixed stations.

(3) The Industrial/Business Pool Group B Frequencies are as follows:

$\begin{array}{c} 462/467.35625\\ 462/467.3625\\ 462/467.36875\\ 462/467.38125\\ 462/467.3875\\ 462/467.39375\\ 462/467.40625\\ 462/467.4125\\ \end{array}$	462/467.43125 462/467.4375 462/467.44375
462/467.4125 462/467.41875	

manent fixed location will be authorized on Group C frequencies.

(2) Operation on these frequencies is limited to 6 watts effective radiated power for fixed or mobile units and 2 watts ERP for portable units. Stations operating at fixed locations for a temporary period of time will be limited to an antenna height of 7 meters (20 feet) above ground.

(3) The Industrial/Business Pool Group C Low Power Frequencies are as follows:

$\begin{array}{rrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrr$	461/466.28125 461/466.2875 461/466.29375 461/466.30625 461/466.3125 461/466.31875 461/466.33125 461/466.3375 461/466.35625 461/466.35625 461/466.36875 461/466.36875 462.7625 (unpaired) 462.7875 (unpaired)	462.8125 462.8375 (unpaired) 462/467.8625 462/467.8875 462/467.9125 464/469.48125 464/469.4875 464/469.5125 464/469.51875 464/469.53125 464/469.5375 464/469.5625 464/469.56875
--	---	---

(f) Group D Frequencies. The Industrial/Business Pool frequencies in Group D are available for central station alarm operations on a coordinated basis, pursuant to \$\$90.35(b)(2) and 90.175(b). (1) Base, mobile or operational fixed stations will be authorized on Group D frequencies. Fixed stations may be licensed as mobile.

Federal Communications Commission

(2) Group D frequencies subject to §90.35(c)(63) are limited to central station alarm use within the urban areas described in §90.35(c)(63). Outside the urban areas described in §90.35(c)(63). Group D frequencies subject to §90.35(c)(63) are available for general Industrial/Business use on a coordinated basis, pursuant to §§90.35(b)(2) and 90.175(b).

(3) Group D frequencies subject to §90.35(c)(66) are limited to central station alarm use nationwide.

460/465.90625	460/465.95625
460/465.9125	460/465.9625
460/466.91875	460/465.96875
460/465.93125	460/465.98125
460/465.9375	460/465.9875
460/465.94375	460/465.99375

(g) Low Power Public Safety Frequencies. The frequencies in the Public Safety Pool Low Power Group are available nationwide on a coordinated basis, pursuant to §§90.20(c)(2) and 90.175(b).

(1) Base, mobile or operational fixed stations will be authorized on Public Safety Low Power frequencies. Fixed stations may be licensed as mobile.

$\begin{array}{r} 453/458.03125\\ 453/458.0375\\ 453/458.04375\\ 453/458.05625\\ 453/458.0625\\ 453/458.06875\\ 453/458.08125\\ 453/458.0875\\ 453/458.09375\\ 453/458.10625\\ 453/458.1125\\ 453/458.11875\\ \end{array}$	$\begin{array}{c} 453/458.13125\\ 453/458.1375\\ 453/458.14375\\ 453/458.88125\\ 453/458.8875\\ 453/458.89375\\ 453/458.90625\\ 453/458.9125\\ 453/458.9125\\ 453/458.9125\\ 453/458.93125\\ 453/458.9375\\ 453/458.9375\\ 453/458.9375\\ 453/458.9375\\ \end{array}$	$\begin{array}{r} 453/458.95625\\ 453/458.9625\\ 453/458.96875\\ 453/458.98125\\ 453/458.99375\\ 453/458.99375\\ 460/465.48125\\ 460/465.48125\\ 460/465.49375\\ 460/465.50625\\ 460/465.5125\\ 460/465.51875\\ \end{array}$	$\begin{array}{r} 460/465.53125\\ 460/465.5375\\ 460/465.54375\\ 460/465.55625\\ 460/465.5625\\ 460/465.56875\\ \end{array}$
--	---	--	--

(h) Unless otherwise noted, the following conditions apply to all low power frequencies:

(1) Except for itinerant operations on Group C, wide area operations will not be authorized. The area of normal dayto-day operations will be described in the application in terms of maximum distance from a geographic center (latitude and longitude).

(2) A hospital or health care institution holding a license to operate a

(4) Operation on Group D frequencies is limited to 2 watts output power for mobile, base or operational fixed stations. Fixed stations used for central station alarm operations may utilize antennas mounted not more than 7 meters (20 feet) above a man-made supporting structure, including antenna structure.

(5) The Industrial/Business Pool Group D Low Power Frequencies are as follows:

461/466.00625 461/466.0125 461/466.01875

> (2) Operation on these frequencies is limited to 6 watts effective radiated power for base, mobile or operational fixed stations and 2 watts ERP for portable units. A maximum antenna height of 7 meters (20 feet) above ground is authorized for fixed stations. (3) The Public Safety Pool Low

Power Frequencies are as follows:

	453/458.96875	460/465.54375
	453/458.98125	460/465.55625
	453/458.9875	460/465.5625
	453/458.99375	460/465.56875
	460/465.48125	
	460/465.4875	
	460/465.49375	
	460/465.50625	
	460/465.5125	
	460/465.51875	
l-	radio station	under this part may
W	ate a medic	al radio telemetry de
	with an out <u>r</u>	out power not to exce

operlevice ed 20 milliwatts without specific authorization from the Commission. All licensees operating under this authority must comply with the requirements and limitations set forth in this section.

(3) No limit shall be placed on the length or height above ground level of any commercially manufactured radiating transmission line when the transmission line is terminated in a non-radiating load and is routed at least 7 meters (20 feet) interior to the edge of any structure or is routed below ground level.

(4) Sea-based stations may utilize antennas mounted not more than 7 meters (20 feet) above a man-made supporting structure, including antenna structures.

(5) Continuous carrier operations are prohibited on these frequencies.

(6) Unless specified elsewhere in this part, licensees as of August 5, 1999, licensed for operations with an emission designator wider than 11.25 kHz on low power frequencies that are subject to an authorized bandwidth of 11.25 kHz, may obtain primary status with respect to co-channel licensees by supplying their coordinates to the Commission. These licensees will continue to operate on a secondary basis with respect to adjacent channel licensees. Additionally, these licensees may continue to operate with an authorized bandwidth wider than 11.25 kHz on such low power frequencies, subject to the provisions of §90.209(b) of this chapter.

(7) Unless specified elsewhere in this part, licensees as of August 5, 1999, licensed for operations with an emission designator wider than 11.25 kHz on frequencies that are subject to an authorized bandwidth of 11.25 kHz, which are not low power frequencies, may obtain primary status with respect to cochannel licensees by modifying their license to low power frequencies, supplying their coordinates to the Commission, and otherwise complying with the conditions of paragraphs (b) through (g) of this section. These licensees will continue to operate on a secondary basis with respect to adjacent channel licensees. Additionally, these licensees may continue to operate with an authorized bandwidth wider than 11.25 kHz on such low power frequencies, subject to the provisions of §90.209(b) of this chapter.

(8) Applicants proposing to operate with an authorized bandwidth wider than 11.25 kHz, on low power frequencies that are subject to an authorized bandwidth of 11.25 kHz, may be licensed on a secondary, non-inter47 CFR Ch. I (10–1–11 Edition)

ference basis. Such applicants are subject to the conditions of paragraphs (b) through (g) of this section and the provisions of §90.209(b) of this chapter.

[68 FR 19461, Apr. 21, 2003; 68 FR 55319, Sept.
25, 2003, as amended at 69 FR 4254, Jan. 29, 2004; 75 FR 19284, Apr. 14, 2010]

§90.269 Use of frequencies for selfpowered vehicle detectors.

(a) Frequencies subject to §90.20(d)(22) may be used for the operation of self-powered vehicle detectors by licensees of base/mobile stations in the Public Safety Pool in accordance with the following conditions:

(1) All stations are limited to 100 milliwatts carrier power and 20K00F7W, 20K00F7X, 20K00F8W, 20K00F8X, 20K00F9W or 20K00F9X emissions. The frequency deviation shall not exceed 5 kHz. No more than two 30 ms. pulses may be emitted for each vehicle sensed.

(2) The transmitters must be crystal controlled with a frequency tolerance of plus or minus .005% from -20° to plus 50 °C. They must be certificated.

(3) The total length of the transmission line plus antenna may not exceed one-half wavelength and must be integral with the unit.

(4) All operation shall be on a secondary, non-interference basis.

(b) [Reserved]

[48 FR 54982, Dec. 8, 1983, as amended at 54
 FR 38681, Sept. 20, 1989; 62 FR 18929, Apr. 17, 1997; 63 FR 36610, July 7, 1998]

§90.273 Availability and use of frequencies in the 421–430 MHz band.

The frequency bands 422.1875-425.4875 MHz and 427.1875-429.9875 MHz are available for use in the Detroit, Michigan and Cleveland, Ohio areas. The hands 423.8125-425.4875 MHz and 428.8125-429.9875 MHz are available for use in the Buffalo, New York area. Sections 90.273 through 90.281 address the specific rules applicable to these bands. Use of these bands is also subject to the general technical standards and application procedures contained in other subparts of part 90. The technical standards applicable in this band are the same as those contained in subpart I of part 90 for the 450-470 MHz band.