radiotelephony on frequencies below 500 MHz, the deviation arising from modulation may not exceed plus or minus 15 kHz from the unmodulated carrier.

(d) Each unmultiplexed radiotelephone transmitter having more than 3 watts plate power input to the final radio frequency stage and initially installed at the station in this service after September 4, 1956, must be provided with a device that will automatically prevent modulation in excess of that specified in paragraphs (b) and (c) of this section which may be caused by greater than normal audio level.

## § 101.813 Remote control operation of mobile television pickup stations.

- (a) Mobile television pickup stations (including nonbroadcast) may be operated by remote control from the fixed locations for periods not to exceed 6 months.
- (b) The Commission may, upon adequate showing by the licensee as to why the television pickup operations should not be conducted under a fixed station authorization, renew the authority granted under the provisions of paragraph (a) of this section.
- (c) Reference should be made to §101.125 concerning mobile station antenna height restrictions and to paragraphs (c) and (f) of §101.131 concerning control points.

## § 101.815 Stations at temporary fixed locations.

- (a) Authorizations may be issued upon proper application for the use of frequencies listed in §101.803 by stations in the Local Television Transmission Service for rendition of temporary service to subscribers under the following conditions:
- (1) When a fixed station is to remain at a single location for less than 6 months, the location is considered to be temporary.
- (2) When a fixed station authorized to operate at temporary locations is installed and it subsequently becomes necessary for the station to operate from such location for more than six months, an application for a station authorization to specify the permanent location must be filed at least thirty

days prior to the expiration of the six month period.

- (3) The station must be used only for rendition of communication service at a remote point where the provision of wire facilities is not practicable.
- (4) The antenna structure height employed at any location may not exceed the criteria set forth in §17.7 of this chapter unless, in each instance, authorization for use of a specific maximum antenna structure height for each location has been obtained from the Commission prior to erection of the antenna. See §101.125.
- (5) Applications for such stations must comply with the provisions of §101.21(f).
- (b) Applications for authorizations to operate stations at temporary locations under the provisions of this section may be made upon FCC Form 601. Blanket applications may be submitted for the required number of transmitters.
- (c) Prior coordination of mobile assignments will be in accordance with the procedures in §101.103(d) except that the prior coordination process for mobile (temporary fixed) assignments may be completed orally and the period allowed for response to a coordination notification may be less than 30 days if the parties agree.

 $[61\ FR\ 26677,\ May\ 28,\ 1996,\ as\ amended\ at\ 63\ FR\ 68984,\ Dec.\ 14,\ 1998;\ 65\ FR\ 38332,\ June\ 20,\ 2000;\ 68\ FR\ 4961,\ Jan.\ 31,\ 2003]$ 

## § 101.817 Notification of station operation at temporary locations.

- (a) The licensee of stations authorized pursuant to §101.813 must notify the Commission prior to each period of operation. This notification must include:
- (1) The call sign, manufacturer's name, type or model number, output power and specific location of the transmitter(s);
- (2) The maintenance location for the transmitter;
- (3) The location of the transmitting or receiving station with which it will communicate and the identity of the correspondent operating such facilities:
- (4) The exact frequency or frequencies to be used;