

Federal Communications Commission

§ 15.709

TVBDs must receive approval by the Commission.

[75 FR 75835, Dec. 6, 2010]

§ 15.705 Cross reference.

(a) The provisions of subparts A, B, and C of this part apply to TVBDs, except where specific provisions are contained in subpart H.

(b) The requirements of subpart H apply only to the radio transmitter contained in the TVBD. Other aspects of the operation of a TVBD may be subject to requirements contained elsewhere in this chapter. In particular, a TVBD that includes a receiver that tunes within the frequency range specified in §15.101(b) contains digital circuitry not directly associated with the radio transmitter is also subject to the requirements for unintentional radiators in subpart B.

§ 15.706 Information to the user.

(a) In addition to the labeling requirements contained in §15.19, the instructions furnished to the user of a TVBD shall include the following statement, placed in a prominent location in the text of the manual:

This equipment has been tested and found to comply with the rules for TV bands devices, pursuant to part 15 of the FCC rules. These rules are designed to provide reasonable protection against harmful interference. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- (1) Reorient or relocate the receiving antenna.
- (2) Increase the separation between the equipment and receiver.
- (3) Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- (4) Consult the manufacturer, dealer or an experienced radio/TV technician for help.

(b) In cases where the manual is provided only in a form other than paper, such as on a computer disk or over the Internet, the information required by this section may be included in the

manual in that alternative form, provided the user can reasonably be expected to have the capability to access information in that form.

[74 FR 7326, Feb. 17, 2009, as amended at 75 FR 75836, Dec. 6, 2010]

§ 15.707 Permissible channels of operation.

(a) All TVBDs are permitted to operate available channels in the frequency bands 512–608 MHz (TV channels 21–36) and 614–698 MHz (TV channels 38–51), subject to the interference protection requirements in §§15.711 and 15.712, except that operation of TVBDs is prohibited on the first channel above and the first channel below TV channel 37 (608–614 MHz) that are available, *i.e.*, not occupied by an authorized service. If a channel is not available both above and below channel 37, operation is prohibited on the first two channels nearest to channel 37. These channels will be identified and protected in the TV bands database(s).

(b) Operation on available channels in the bands 54–60 MHz (TV channel 2), 76–88 MHz (TV channels 5 and 6), 174–216 MHz (TV channels 7–13) and 470–512 MHz (TV channels 14–20), subject to the interference protection requirements in §§15.711 and 15.712, is permitted only for fixed TVBDs that communicate only with other fixed TVBDs.

(c) Fixed and Mode II TVBDs shall operate only on available channels as identified in paragraphs (a) and (b) of this section and as determined by a TV bands database in accordance with the interference avoidance mechanisms of §§15.711 and 15.712.

(d) Mode I TVBDs shall operate only on available channels as identified in paragraphs (a) and (b) of this section and provided from a fixed or Mode II TVBD in accordance with §15.711(b)(3)(iv).

[75 FR 75836, Dec. 6, 2010]

§ 15.709 General technical requirements.

(a) *Power limits for TVBDs.* (1) For fixed TVBDs, the maximum power delivered to the transmitting antenna shall not exceed one watt per 6 megahertz of bandwidth on which the device operates. The power delivered to the