

**§ 17.54**

Aviation surface orange, enamel.	TT-E-489 <sup>1</sup> (Color No. 12197, FS-595).
Aviation red obstruction light—color.	MIL-C-25050 <sup>2</sup> .
Flashing beacons .....	CAA-446 <sup>3</sup> Code Beacons, 300 mm.
Do .....	MIL-6273 <sup>2</sup> .
Double and single obstruction light.	L-810 <sup>3</sup> (FAA AC No. 150/5345-2 <sup>4</sup> ).
Do .....	MIL-L-7830 <sup>2</sup> .
High intensity white obstruction light.	FAA/DOD L-856 (FAA AC No. 150/5345-43B <sup>4</sup> ).
116-Watt lamp .....	No. 116 A21/TS (6,000 h).
125-Watt lamp .....	No. 125 A21/TS (6,000 h).
620-Watt lamp .....	No. 620 PS-40 (3,000 h).
700-Watt lamp .....	No. 700 PS-40 (6,000 h).

<sup>1</sup>Copies of this specification can be obtained from the Specification Activity, Building 197, Room 301, Naval Weapons Plant, 1st and N Streets, SE., Washington, D.C. 20407.

<sup>2</sup>Copies of Military specifications can be obtained by contacting the Commanding Officer, Naval Publications and Forms Center, 5801 Tabor Ave., Attention: NPPC-105, Philadelphia, Pa. 19120.

<sup>3</sup>Copies of Federal Aviation Administration specifications may be obtained from the Chief, Configuration Control Branch, AAF-110, Department of Transportation, Federal Aviation Administration, 800 Independence Avenue SW., Washington, D.C. 20591.

<sup>4</sup>Copies of Federal Aviation Administration advisory circulars may be obtained from the Department of Transportation, Publications Section, TAD-443.1, 400 7th St. SW., Washington, D.C. 20590.

[33 FR 11540, Aug. 14, 1968, as amended at 40 FR 30267, July 18, 1975]

**§ 17.54 Rated lamp voltage.**

To insure the necessary lumen output by obstruction lights, the rated voltage of incandescent lamps used shall correspond to be within 3 percent higher than the voltage across the lamp socket during the normal hours of operation.

[42 FR 54826, Oct. 11, 1977]

**§ 17.56 Maintenance of lighting equipment.**

(a) Replacing or repairing of lights, automatic indicators or automatic control or alarm systems shall be accomplished as soon as practicable.

(b) The flash tubes in a high intensity obstruction lighting system shall be replaced whenever the peak effective daytime intensity falls below 200,000 candelas.

[40 FR 30267, July 18, 1975]

**§ 17.57 Report of radio transmitting antenna construction, alteration, and/or removal.**

The owner of an antenna structure for which an Antenna Structure Registration Number has been obtained must notify the Commission within 24 hours of completion of construction

**47 CFR Ch. I (10–1–12 Edition)**

(FCC Form 854-R) and/or dismantlement (FCC Form 854). The owner must also immediately notify the Commission using FCC Form 854 upon any change in structure height or change in ownership information.

[61 FR 4364, Feb. 6, 1996]

**§ 17.58 Facilities to be located on land under the jurisdiction of the U.S. Forest Service or the Bureau of Land Management.**

Any application proposing new or modified transmitting facilities to be located on land under the jurisdiction of the U.S. Forest Service or the Bureau of Land Management shall include a statement that the facilities will be so located, and the applicant shall comply with the requirements of § 1.70 of this chapter.

[32 FR 11274, Aug. 3, 1967]

**PART 18—INDUSTRIAL, SCIENTIFIC, AND MEDICAL EQUIPMENT**

**Subpart A—General Information**

- Sec.
- 18.101 Basis and purpose.
- 18.107 Definitions.
- 18.109 General technical requirements.
- 18.111 General operating conditions.
- 18.113 Inspection by Commission representatives.
- 18.115 Elimination and investigation of harmful interference.
- 18.117 Report of interference investigation.
- 18.121 Exemptions.

**Subpart B—Applications and Authorizations**

- 18.201 Scope.
- 18.203 Equipment authorization.
- 18.207 Technical report.
- 18.209 Identification of authorized equipment.
- 18.211 Multiple listing of equipment.
- 18.212 Compliance information.
- 18.213 Information to the user.

**Subpart C—Technical Standards**

- 18.301 Operating frequencies.
- 18.303 Prohibited frequency bands.
- 18.305 Field strength limits.
- 18.307 Conduction limits.
- 18.309 Frequency range of measurements.
- 18.311 Methods of measurements.

AUTHORITY: 47 U.S.C. 4, 301, 302, 303, 304, 307.