Subpart C—Operating Requirements and Procedures

STATION REQUIREMENTS—GENERAL

§ 80.61 Commission inspection of stations.

All stations and required station records must be made available for inspection by authorized representatives of the Commission.

\$80.63 Maintenance of transmitter power.

- (a) The power of each radio transmitter must not be more than that necessary to carry on the service for which the station is licensed.
- (b) Except for transmitters using single sideband and independent sideband emissions, each radio transmitter rated by the manufacturer for carrier power in excess of 100 watts must contain the instruments necessary to determine the transmitter power during its operation

STATION REQUIREMENTS—LAND STATIONS

§ 80.67 General facilities requirements for coast stations.

- (a) All coast stations licensed to transmit in the band 156-162 MHz must be able to transmit and receive on 156.800 MHz and at least one working frequency in the band.
- (b) All coast stations that operate telephony on frequencies in the 1605–3500 kHz band must be able to transmit and receive using J3E emission on the frequency 2182 kHz and at least one working frequency in the band.
- $[51~{\rm FR}~31213,~{\rm Sept.}~2,~1986,~{\rm as}~{\rm amended}~{\rm at}~68~{\rm FR}~46960,~{\rm Aug.}~7,~2003]$

§ 80.68 Facilities requirements for public coast stations using telegraphy.

Public coast station using telegraphy must be provided with the following facilities.

- (a) Stations having a frequency assignment below 150 kHz must:
- (1) Transmit A1A emission on at least one working frequency within the band $100{\text -}150~{\rm kHz};$
- (2) Receive A1A emission on all radio channels authorized for transmission by mobile stations operating in the

maritime mobile service for telegraphy within the band 100–150 kHz.

- (b) Stations having a frequency assignment within the 405–525 kHz band must transmit and receive on 500 kHz and at least one working frequency in the band.
- (c) Stations having frequency assignments above 4000 kHz must be equipped to receive on each of their assigned frequencies and all ship station radiotelegraphy frequencies in the same subband as the assigned frequency of the coast station. See subpart H of this part for the list of frequencies.

§80.69 Facilities requirement for public coast stations using telephony.

Public coast stations using telephony must be provided with the following facilities

- (a) When the station is authorized to use frequencies in the 1605–3500 kHz band, equipment meeting the requirements of §80.67(b) must be installed at each transmitting location.
- (b) The transmitter power on the frequency 2182 kHz must not exceed 50 watts carrier power for normal operation. During distress, urgency and safety traffic, operation at maximum power is permitted.

§80.70 Special conditions relative to coast station VHF facilities.

- (a) Coast stations which transmit on the same radio channel above 150 MHz must minimize interference by reducing radiated power, by decreasing antenna height or by installing directional antennas. Coast stations at locations separated by less than 241 kilometers (150 miles) which transmit on the same radio channel above 150 MHz must also consider a time-sharing arrangement. The Commission may order station changes if agreement cannot be reached between the involved licensees.
- (b) Coast stations which transmit on a radio channel above 150 MHz and are located within interference range of any station within Canada or Mexico must minimize interference to the involved foreign station(s), and must notify the Commission of any station changes.
- (c) A VHF (156-162 MHz) public coast licensee initially authorized on any of the channels listed in the table in