

§ 95.801

*MedRadio programmer/control transmitter.* A MedRadio transmitter that operates or is designed to operate outside of a human body for the purpose of communicating with a receiver, or for triggering a transmitter, connected to a medical implant device or to a medical body-worn device used in the MedRadio Service; and which also typically includes a frequency monitoring system that initiates a MedRadio communications session.

*MedRadio Service.* Medical Device Radiocommunication Service.

*MedRadio transmitter.* A transmitter authorized to operate in the MedRadio service.

*MURS.* Multi-Use Radio Service.

*Peak envelope power.* TP averaged during one RF cycle at the highest crest of the modulation envelope.

*R/C.* Radio Control Radio Service.

*R/C transmitter.* A transmitter that operates or is intended to operate at a station authorized in the R/C.

*RF.* Radio frequency.

*TP.* RF transmitter power expressed in W, either mean or peak envelope, as measured at the transmitter output antenna terminals.

*Transmitter.* Apparatus that converts electrical energy received from a source into RF energy capable of being radiated.

*W.* Watts.

[65 FR 60878, Oct. 13, 2000, as amended at 74 FR 22708, May 14, 2009; 77 FR 4269, Jan. 27, 2012]

EFFECTIVE DATE NOTE: At 77 FR 55733, Sept. 11, 2012, appendix 1 was amended by adding a definition for “Medical Body Area Network”, effective Oct. 11, 2012. For the convenience of the user, the added text is set forth as follows:

APPENDIX 1 TO SUBPART E OF PART 95—  
GLOSSARY OF TERMS

\* \* \* \* \*

*Medical Body Area Network (MBAN).* An MBAN is a low power network consisting of a MedRadio programmer/control transmitter and multiple medical body-worn devices all of which transmit or receive non-voice data or related device control commands for the purpose of measuring and recording physiological parameters and other patient information or performing diagnostic or therapeutic functions via radiated bi- or uni-directional electromagnetic signals.

\* \* \* \* \*

Subpart F—218–219 MHz Service

GENERAL PROVISIONS

SOURCE: 57 FR 8275, Mar. 9, 1992, unless otherwise noted.

§ 95.801 Scope.

This subpart sets out the regulations governing the licensing and operation of a 218–219 MHz system. This subpart supplements part 1, subpart F of this chapter, which establishes the requirements and conditions under which commercial and private radio stations may be licensed and used in the Wireless Telecommunications Services. The provisions of this subpart contain additional pertinent information for current and prospective licensees specific to the services governed by this part 95.

[64 FR 59659, Nov. 3, 1999]

§ 95.803 218–219MHz Service description.

(a) The 218–219 MHz Service is authorized for system licensees to provide communication service to subscribers in a specific service area.

(b) The components of each 218–219 MHz Service system are its administrative apparatus, its response transmitter units (RTUs), and one or more cell transmitter stations (CTSs). RTUs may be used in any location within the service area. CTSs provide service from a fixed point, and certain CTSs must be individually licensed as part of a 218–219 MHz Service system. See § 95.811.

(c) Each 218–219 MHz Service system service area is one of the cellular system service areas as defined by the Commission, unless modified pursuant to § 95.823.

[66 FR 9218, Apr. 9, 2001]

§ 95.805 Permissible communications.

A 218–219 MHz Service system may provide any fixed or mobile communications service to subscribers within its service area on its assigned spectrum, consistent with the Commission’s rules and the regulatory status of the system to provide services on a common carrier or private basis.

[64 FR 59660, Nov. 3, 1999]