Federal Communications Commission

- (b) The following frequency bands and segments are authorized to Earth stations:
- (1) The 17 m, 15 m, 12 m, and 10 m bands, 6 mm, 4 mm, 2 mm and 1 mm bands; and
- $\begin{array}{c} (2) \ \ {\rm The} \ \ 7.0\text{--}7.1 \ \ {\rm MHz}, \ 14.00\text{--}14.25 \ \ {\rm MHz}, \\ 144\text{--}146 \ \ {\rm MHz}, \ 435\text{--}438 \ \ {\rm MHz}, \ 1260\text{--}1270 \ \ {\rm MHz} \\ {\rm and} \ \ 2400\text{--}2450 \ \ \ {\rm MHz}, \ \ 3.40\text{--}3.41 \ \ {\rm GHz}, \ 5.65\text{--} \\ 5.67 \ \ {\rm GHz}, \ 10.45\text{--}10.50 \ \ {\rm GHz} \ \ {\rm and} \ \ 24.00\text{--}24.05 \\ {\rm GHz} \ \ {\rm segments}. \end{array}$

[54 FR 25857, June 20, 1989, as amended at 54 FR 39535, Sept. 27, 1989]

§ 97.211 Space telecommand station.

- (a) Any amateur station designated by the licensee of a space station is eligible to transmit as a telecommand station for that space station, subject to the privileges of the class of operator license held by the control operator.
- (b) A telecommand station may transmit special codes intended to obscure the meaning of telecommand messages to the station in space operation.
- (c) The following frequency bands and segments are authorized to telecommand stations:
- (1) The 17 m, 15 m, 12 m and 10 m bands, 6 mm, 4 mm, 2 mm and 1 mm bands; and
- (2) The 7.0–7.1 MHz, 14.00–14.25 MHz, 144–146 MHz, 435–438 MHz, 1260–1270 MHz and 2400–2450 MHz, 3.40–3.41 GHz, 5.65–5.67 GHz, 10.45–10.50 GHz and 24.00–24.05 GHz segments.
- (d) A telecommand station may transmit one-way communications.

[54 FR 25857, June 20, 1989, as amended at 54 FR 39535, Sept. 27, 1989; 56 FR 56171, Nov. 1, 1991]

§ 97.213 Telecommand of an amateur

An amateur station on or within 50 km of the Earth's surface may be under telecommand where:

(a) There is a radio or wireline control link between the control point and the station sufficient for the control operator to perform his/her duties. If radio, the control link must use an auxiliary station. A control link using a fiber optic cable or another telecommunication service is considered wireline.

- (b) Provisions are incorporated to limit transmission by the station to a period of no more than 3 minutes in the event of malfunction in the control link.
- (c) The station is protected against making, willfully or negligently, unauthorized transmissions.
- (d) A photocopy of the station license and a label with the name, address, and telephone number of the station licensee and at least one designated control operator is posted in a conspicuous place at the station location.

[54 FR 25857, June 20, 1989, as amended at 56 FR 56171, Nov. 1, 1991]

§ 97.215 Telecommand of model craft.

An amateur station transmitting signals to control a model craft may be operated as follows:

- (a) The station identification procedure is not required for transmissions directed only to the model craft, provided that a label indicating the station call sign and the station licensee's name and address is affixed to the station transmitter.
- (b) The control signals are not considered codes or ciphers intended to obscure the meaning of the communication
- (c) The transmitter power must not exceed 1 W.

[54 FR 25857, June 20, 1989, as amended at 56 FR 56171, Nov. 1, 1991]

§ 97.217 Telemetry.

Telemetry transmitted by an amateur station on or within 50 km of the Earth's surface is not considered to be codes or ciphers intended to obscure the meaning of communications.

[56 FR 56172, Nov. 1, 1991. Redesignated at 59 FR 18975, Apr. 21, 1994]

§ 97.219 Message forwarding system.

- (a) Any amateur station may participate in a message forwarding system, subject to the privileges of the class of operator license held.
- (b) For stations participating in a message forwarding system, the control operator of the station originating a message is primarily accountable for any violation of the rules in this part contained in the message.