Federal Communications Commission

- (c) Situations in which no protection is afforded. Except as provided elsewhere in this part, no protection from interference is afforded in the following situations:
- (1) Interference to base receivers from base or fixed transmitters. Licensees should attempt to resolve such interference by technical means or operating arrangements.
- (2) Integerence to mobile receivers from mobile transmitters. No protection is provided against mobile-to-mobile interference.
- (3) Interference to base receivers from mobile transmitters. No protection is provided against mobile-to-base interference.
- (4) Interference to fixed stations. Licensees should attempt to resolve such interference by technical means or operating arrangements.
- (5) Anomalous or infrequent propagation modes. No protection is provided against interference caused by tropospheric and ionospheric propagation of signals.
- (6) Facilities for which the Commission is not notified. No protection is provided against interference to the service of any additional or modified transmitter operating pursuant to §1.929 or §22.165, unless and until the licensee modifies its authorization using FCC Form 601.
- (7) In-building radiation systems. No protection is provided against interference to the service of in-building radiation systems (see § 22.383).

[59 FR 59507, Nov. 17, 1994, as amended at 62 FR 11633, Mar. 12, 1997; 63 FR 68944, Dec. 14, 1998; 70 FR 19308, Apr. 13, 2005]

$\S 22.353$ Blanketing interference.

Licensees of Public Mobile Services stations are responsible for resolving cases of blanketing interference in accordance with the provisions of this section.

(a) Except as provided in paragraph (c) of this section, licensees must resolve any cases of blanketing interference in their area of responsibility caused by operation of their transmitter(s) during a one-year period following commencement of service from new or modified transmitter(s). Interference must be resolved promptly at no cost to the complainant.

(b) The area of responsibility is that area in the immediate vicinity of the transmitting antenna of stations where the field strength of the electromagnetic radiation from such stations equals or exceeds 115 dB $\mu V/m$. To determine the radial distance to the boundary of this area, the following formula must be used:

$$d = 0.394 \times \sqrt{p}$$

where d is the radial distance to the boundary, in kilometers

p is the radial effective radiated power, in kilowatts

The maximum effective radiated power in the pertinent direction, without consideration of the antenna's vertical radiation pattern or height, must be used in the formula.

- (c) Licensees are not required to resolve blanketing interference to mobile receivers or non-RF devices or blanketing interference occurring as a result of malfunctioning or mistuned receivers, improperly installed consumer antenna systems, or the use of high gain antennas or antenna booster amplifiers by consumers.
- (d) Licensees that install transmitting antennas at a location where there are already one or more transmitting antennas are responsible for resolving any new cases of blanketing interference in accordance with this section.
- (e) Two or more licensees that concurrently install transmitting antennas at the same location are jointly responsible for resolving blanketing interference cases, unless the FCC can readily determine which station is causing the interference, in which case the licensee of that station is held fully responsible.
- (f) After the one year period of responsibility to resolve blanketing interference, licensees must provide upon request technical information to complainants on remedies for blanketing interference.

§ 22.355 Frequency tolerance.

Except as otherwise provided in this part, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table C-1 of this section.