

§ 22.905

cellular mobile radiotelephone service must—

(1) Maintain the capability to provide compatible analog service (“AMPS”) to cellular telephones designed in conformance with the specifications contained in sections 1 and 2 of the standard document ANSI TIA/EIA-553-A-1999 Mobile Station—Base Station Compatibility Standard (approved October 14, 1999); or, the corresponding portions, applicable to mobile stations, of whichever of the predecessor standard documents was in effect at the time of the manufacture of the telephone. This incorporation by reference was approved by the Director of the Federal Register in accordance with 5 U.S.C. 552(a) and 1 CFR part 51. Copies of the standard may be purchased from Global Engineering Documents, 15 Inverness Way East, Englewood, CO 80112-5704 (or via the internet at <http://global.ihs.com>). Copies are available for inspection at the Federal Communications Commission, 445 12th Street, SW, Washington, DC 20554, or at the National Archives and Records Administration (NARA). For information on the availability of this material at NARA, call 202-741-6030, or go to: http://www.archives.gov/federal_register/code_of_federal_regulations/ibr_locations.html.

(2) Provide AMPS, upon request, to subscribers and roamers using such cellular telephones while such subscribers are located in any portion of the cellular system’s CGSA where facilities have been constructed and service to subscribers has commenced. *See* also § 20.12 of this chapter. Cellular licensees must allot sufficient system resources such that the quality of AMPS provided, in terms of geographic coverage and traffic capacity, is fully adequate to satisfy the concurrent need for AMPS availability.

[67 FR 77191, Dec. 17, 2002, as amended at 69 FR 18803, Apr. 9, 2004]

§ 22.905 Channels for cellular service.

The following frequency bands are allocated for assignment to service providers in the Cellular Radiotelephone Service.

(a) Channel Block A: 869–880 MHz paired with 824–835 MHz, and 890–891.5 MHz paired with 845–846.5 MHz.

47 CFR Ch. I (10–1–13 Edition)

(b) Channel Block B: 880–890 MHz paired with 835–845 MHz, and 891.5–894 MHz paired with 846.5–849 MHz.

[67 FR 77191, Dec. 17, 2002]

§ 22.907 Coordination of channel usage.

Licensees in the Cellular Radiotelephone Service must coordinate, with the appropriate parties, channel usage at each transmitter location within 121 kilometers (75 miles) of any transmitter locations authorized to other licensees or proposed by tentative selectees or other applicants, except those with mutually exclusive applications.

(a) Licensees must cooperate and make reasonable efforts to resolve technical problems that may inhibit effective and efficient use of the cellular radio spectrum; however, licensees are not obligated to suggest extensive changes to or redesign other licensees’ cellular systems. Licensees must make reasonable efforts to avoid blocking the growth of other cellular systems that are likely to need additional capacity in the future.

(b) If technical problems are addressed by an agreement or operating agreement between the licensees that would result in a reduction of quality or capacity of either system, the licensees must notify the Commission by updating FCC Form 601.

[59 FR 59507, Nov. 17, 1994, as amended at 63 FR 68951, Dec. 14, 1998]

§ 22.909 Cellular markets.

Cellular markets are standard geographic areas used by the FCC for administrative convenience in the licensing of cellular systems. Cellular markets comprise Metropolitan Statistical Areas (MSAs) and Rural Service Areas (RSAs). All cellular markets and the counties they comprise are listed in Public Notice Report No. CL-92-40 “Common Carrier Public Mobile Services Information, Cellular MSA/RSA Markets and Counties”, dated January 24, 1992, DA 92-109, 7 FCC Rcd 742 (1992).

(a) *MSAs*. Metropolitan Statistical Areas are 306 areas, including New England County Metropolitan Areas and the Gulf of Mexico Service Area (water area of the Gulf of Mexico, border is