

Federal Communications Commission

§ 25.253

Radiocommunication Sector (available at the address in § 0.445 of this chapter).

[66 FR 10630, Feb. 16, 2001, as amended at 78 FR 8430, Feb. 6, 2013]

§ 25.252 [Reserved]

§ 25.253 Special requirements for ancillary terrestrial components operating in the 1626.5–1660.5 MHz/1525–1559 MHz bands.

(a) An ancillary terrestrial component in these bands shall:

(1) In any band segment coordinated for the exclusive use of an MSS applicant within the land area of the U.S., where there is no other L-Band MSS satellite making use of that band segment within the visible portion of the geostationary arc as seen from the ATC coverage area, the ATC system will be limited by the in-band and out-of-band emission limitations contained in this section and the requirement to maintain a substantial MSS service.

(2) In any band segment that is coordinated for the shared use of the applicant's MSS system and another MSS operator, where the coordination agreement existed prior to February 10, 2005 and permits a level of interference to the other MSS system of less than 6% $\Delta T/T$, the applicant's combined ATC and MSS operations shall increase the system noise level of the other MSS to no more than 6% $\Delta T/T$. Any future coordination agreement between the parties governing ATC operation will supersede this paragraph.

(3) In any band segment that is coordinated for the shared use of the applicant's MSS system and another MSS operator, where a coordination agreement existed prior to February 10, 2005 and permits a level of interference to the other MSS system of 6% $\Delta T/T$ or greater, the applicant's ATC operations may increase the system noise level of the other MSS system by no more than an additional 1% $\Delta T/T$. Any future coordination agreement between the parties governing ATC operations will supersede this paragraph.

(4) In a band segment in which the applicant has no rights under a coordination agreement, the applicant may not implement ATC in that band.

(b) ATC base stations shall not exceed an out-of-channel emissions meas-

urement of -57.9 dBW/MHz at the edge of a MSS licensee's authorized and internationally coordinated MSS frequency assignment.

(c) An applicant for an ancillary terrestrial component in these bands shall:

(1) Demonstrate, at the time of application, how its ATC network will comply with the requirements of footnotes US308 and US315 to the table of frequency allocations contained in § 2.106 of this chapter regarding priority and preemptive access to the L-band MSS spectrum by the aeronautical mobile-satellite en-route service (AMS(R)S) and the global maritime distress and safety system (GMDSS).

(2) Coordinate with the terrestrial CMRS operators prior to initiating ATC transmissions when co-locating ATC base stations with terrestrial commercial mobile radio service (CMRS) base stations that make use of Global Positioning System (GPS) time-based receivers.

(3) Provide, at the time of application, calculations that demonstrate the ATC system conforms to the $\Delta T/T$ requirements in paragraphs (a)(2) and (a)(3) of this section, if a coordination agreement that incorporates the ATC operations does not exist with other MSS operators.

(d) Applicants for an ancillary terrestrial component in these bands must demonstrate that ATC base stations shall not:

(1) Exceed a peak EIRP of $31.9 - 10 \cdot \log$ (number of carriers) dBW/200kHz, per sector, for each carrier in the 1525–1541.5 MHz and 1547.5–1559 MHz frequency bands;

(2) Exceed an EIRP in any direction toward the physical horizon (not to include man-made structures) of $26.9 - 10 \cdot \log$ (number of carriers) dBW/200 kHz, per sector, for each carrier in the 1525–1541.5 MHz and 1547.5–1559 MHz frequency bands;

(3) Exceed a peak EIRP of $23.9 - 10 \cdot \log$ (number of carriers) dBW/200 kHz, per sector, for each carrier in the 1541.5–1547.5 MHz frequency band;

(4) Exceed an EIRP toward the physical horizon (not to include man-made structures) of $18.9 - 10 \cdot \log$ (number of carriers) dBW/200 kHz, per sector, for