

on a third-adjacent channel to the primary station. In these circumstances, the LPFM station will not be authorized unless it is located at least 2 km from the FM translator station. In addition, in cases where an LPFM station is located within ± 30 degrees of the azimuth between the FM translator station and its primary station, the LPFM station will not be authorized unless it is located at least 10 kilometers from the FM translator station. The provisions of this subsection will not apply if the LPFM applicant:

(1) Demonstrates that no actual interference will occur due to an undesired (LPFM) to desired (primary station) ratio below 34 dB at all locations,

(2) Complies with the minimum LPFM/FM translator distance separation calculated in accordance with the following formula: $d_u = 133.5 \text{ antilog} [(P_{cu} + G_{ru} - G_{rd} - E_d)/20]$, where d_u = the minimum allowed separation in km, P_{cu} = LPFM ERP in dBW, G_{ru} = gain (dBd) of the FM translator receive antenna in the direction of the LPFM site, G_{rd} = gain (dBd) of the FM translator receive antenna in the direction of the primary station site, E_d = predicted field strength (dBu) of the primary station at the translator site, or

(3) Reaches an agreement with the licensee of the FM translator regarding an alternative technical solution.

NOTE TO PARAGRAPH (a): LPFM applicants may assume that an FM translator station's receive and transmit antennas are collocated.

(b) An authorized LPFM station will not be permitted to continue to operate if an FM translator or FM booster station demonstrates that the LPFM station is causing actual interference to the FM booster station's input signal, provided that the same input signal was in use at the time the LPFM station was authorized.

(c) Complaints of actual interference by an LPFM station subject to paragraph (b) of this section must be served on the LPFM licensee and the Federal Communications Commission, Attention: Audio Division, Media Bureau. The LPFM station must suspend operations upon the receipt of such complaint unless the interference has been resolved to the satisfaction of the com-

plainant on the basis of suitable techniques. Short test transmissions may be made during the period of suspended operations to check the efficacy of remedial measures. An LPFM station may only resume full operation at the direction of the Federal Communications Commission. If the Commission determines that the complainant has refused to permit the LPFM station to apply remedial techniques that demonstrably will eliminate the interference without impairment of the original reception, the licensee of the LPFM station is absolved of further responsibility for the complaint.

[78 FR 2106, Jan. 9, 2013]

§ 73.840 Operating power and mode tolerances.

The transmitter power output (TPO) of an LPFM station must be determined by the procedures set forth in § 73.267 of this part. The operating TPO of an LPFM station with an authorized TPO of more than ten watts must be maintained as near as practicable to its authorized TPO and may not be less than 90% of the minimum TPO nor greater than 105% of the maximum authorized TPO. An LPFM station with an authorized TPO of ten watts or less may operate with less than the authorized power, but not more than 105% of the authorized power.

§ 73.845 Transmission system operation.

Each LPFM licensee is responsible for maintaining and operating its broadcast station in a manner that complies with the technical rules set forth elsewhere in this part and in accordance with the terms of the station authorization. In the event that an LPFM station is operating in a manner that is not in compliance with the technical rules set forth elsewhere in this part or the terms of the station authorization, broadcast operation must be terminated within three hours.

§ 73.850 Operating schedule.

(a) All LPFM stations will be licensed for unlimited time operation, except those stations operating under a time sharing agreement pursuant to § 73.872.