Federal Communications Commission

§87.171 Class of station symbols.

The two or three letter symbols for the classes of station in the aviation services are:

Symbol and class of station

AX—Aeronautical fixed

AXO—Aeronautical operational fixed DGP—Differential GPS

FA—Aeronautical land (unspecified)

FAU—Aeronautical advisory (unicom)

FAC—Airport control tower

FAE—Aeronautical enroute

FAM—Aeronautical multicom

FAR—Aeronautical search and rescue

FAS—Aviation support

FAT—Flight test

FAW-Automatic weather observation

GCO—Ground Communication Outlet

MA-Aircraft (Air carrier and Private)

MA1—Air carrier aircraft only

MA2-Private aircraft only MOU—Aeronautical utility mobile MRT—ELT test

RCO—Remote Communications Outlet

RL—Radionavigation land (unspecified)

RLA—Marker beacon

RLB-Radiobeacon

RLD—RADAR/TEST RLG-Glide path

BLL-Localizer

RLO—VHF omni-range

RLS—Surveillance radar

RLT-Radionavigation land test

RLW-Microwave landing system

RNV—Radio Navigation Land/DME

RPC—Ramp Control

TJ-Aircraft earth station in the Aeronautical Mobile-Satellite Service

UAT-Universal Access Transceiver

[53 FR 28940, Aug. 1, 1988, as amended at 57 FR 45750, Oct. 5, 1992; 64 FR 27475, May 20, 1999; 69 FR 32882, June 14, 2004; 71 FR 70676, Dec. 6, 2006; 76 FR 17351, Mar. 29, 2011]

§87.173 Frequencies.

- (a) The table in paragraph (b) of this section lists assignable carrier frequencies or frequency bands.
- (1) The single letter symbol appearing in the "Subpart" column indicates the subpart of this part which contains additional applicable regulations.
- (2) The two or three letter symbol appearing in the "Class of Station" column indicates the class of station to which the frequency is assignable.
 - (b) Frequency table:

Frequency or fre- quency band	Subpart	Class of station	Remarks
90–110 kHz	Q	RL	LORAN "C".
190–285 kHz	Q	RLB	Radiobeacons.
200–285 kHz	Ö	FAC	Air traffic control.
325-405 kHz	0	FAC	Air traffic control.
325–435 kHz	Q	RLB	Radiobeacons.
410.0 kHz	F	MA	International direction-finding for use outside of United States.
457.0 kHz	F	MA	Working frequency for aircraft on over-water flights.
500.0 kHz		MA	International calling and distress frequency for ships
			and aircraft on over-water flights.
510-535 kHz	Q	RLB	Radiobeacons.
2182.0 kHz	F	MA	International distress and calling.
2648.0 kHz	1	AX	Alaska station.
2850.0-3025.0 kHz	1	MA, FAE	International HF.
2851.0 kHz	I, J	MA, FAE, FAT	International HF; Flight Test.
2866.0 kHz	Í	MA, FAE	Domestic HF; (Alaska).
2875.0 kHz	1	MA, FAE	Domestic HF.
2878.0 kHz		MA1, FAE	Domestic HF; International HF.
2911.0 kHz		MA, FAE	Domestic HF.
2956.0 kHz		MA, FAE	Domestic HF.
3004.0 kHz		MA, FAE, FAT	International HF; Flight Test.
3019.0 kHz		MA1, FAE	Domestic HF; International HF.
3023.0 kHz		MA1, FAR, FAC	Search and rescue communications.
3281.0 kHz	K	MA, FAS	Lighter-than-air craft and aeronautical stations serving
			lighter-than-air craft.
	1	MA, FAE	International HF.
3434.0 kHz		MA1, FAE	Domestic HF.
3443.0 kHz		MA, FAT	Flight Test.
3449.0 kHz		MA, FAE	Domestic HF.
3470.0 kHz		MA, FAE	Domestic HF; International HF.
4125.0 kHz		MA	Distress and safety with ships and coast stations.
4550.0 kHz		AX	Gulf of Mexico.
4645.0 kHz		AX	Alaska.
4650.0–4700.0 kHz		MA, FAE	International HF.
4672.0 kHz		MA1, FAE	Domestic HF.
	1	AX	Alaska.
5036.0 kHz	I I	AX	Gulf of Mexico.

§87.173

Frequency or fre- quency band	Subpart	Class of station	Remarks
5122.5 kHz	1	AX	Alaska.
5167.5 kHz	1	FA	Alaska emergency.
5310.0 kHz	1	AX	Alaska.
5450.0-5680.0 kHz	I	MA, FAE	International HF.
5451.0 kHz	J	MA, FAT	Flight Test.
5463.0 kHz	I	MA1, FAE	Domestic HF.
5469.0 kHz	J	MA, FAT	Flight Test.
5472.0 kHz	I	MA, FAE	Domestic HF.
5484.0 kHz	I	MA, FAE	Domestic HF.
5490.0 kHz	I	MA, FAE	Domestic HF.
5496.0 kHz 5508.0 kHz	 	MA, FAE MA1, FAE	Domestic HF. Domestic HF.
5571.0 kHz	J	MA, FAT	Flight Test.
5631.0 kHz	1	MA, FAE	Domestic HF.
5680.0 kHz	F, M, O	MA1, FAC, FAR	Search and rescue communications.
5887.5 kHz	1	AX	Alaska.
6525.0-6685.0 kHz	1	MA, FAE	International HF.
6550.0 kHz	J	MA, FAT	Flight Test.
6580.0 kHz	1	MA, FAE	Domestic HF.
6604.0 kHz	1	MA, FAE	Domestic HF.
8015.0 kHz	1	AX	Alaska.
8364.0 kHz	F	MA	Search and rescue communications.
8815.0-8965.0 kHz	1	MA, FAE	International HF.
8822.0 kHz	J	MA, FAT	Flight Test.
8855.0 kHz	1	MA, FAE	Domestic HF; international HF.
8876.0 kHz	1	MA, FAE	Domestic HF.
10005.0-10100.0 kHz	1	MA, FAE	International HF.
10045.0 kHz	J	MA, FAT	Flight Test.
10066.0 kHz	1	MA, FAE	Domestic HF; international HF.
11275.0-11400.0 kHz	1	MA, FAE	International HF.
11288.0 kHz	J	MA, FAT	Flight Test.
11306.0 kHz	J	MA, FAT	Flight Test.
11357.0 kHz	1	MA, FAE	Domestic HF.
11363.0 kHz	1	MA, FAE	Domestic HF.
13260.0-13360.0 kHz	1	MA, FAE	International HF.
13312.0 kHz	I, J	MA, FAE, FAT	International HF; Flight Test.
17900.0-17970.0 kHz	1	MA, FAE	International HF.
17964.0 kHz	J	MA, FAT	Flight Test.
21924.0-22000.0 kHz	1	MA, FAE	International HF.
21931.0 kHz	J	MA, FAT	Flight Test.
72.02–72.98 MHz	P	FA, AXO	Operational fixed.
75.000 MHz	Q	RLA	Marker beacon.
75.42–75.98 MHz	P	FA, AXO	Operational fixed.
108.000 MHz	Q	RLT	
108.000-117.950	Q	RLO	VHF omni-range.
MHz.			
108.000–117.975	Q	DGP	Differential GPS.
MHz.	_		
108.050 MHz	Q	RLT	
108.100-111.950	Q	RLL	ILS Localizer.
MHz.			
108.100 MHz	Q	RLT	
108.150 MHz	Q	RLT	OF Idda abandal anadan
118.000–121.400	O, S	MA, FAC, FAW, GCO	25 kHz channel spacing
MHz.		RCO, RPC	
121.500 MHz	G, H, I, J, K, M, O	MA, FAU, FAE, FAT,	Emergency and distress.
101 000 10:	0.1.0	FAS, FAC, FAM.	
121.600-121.925	O, L, Q	MA, FAC, MOU, RLT,	25 kHz channel spacing.
MHz.		GCO, RCO, RPC.	
121.950 MHz	K	FAS	
121.975 MHz	F, S	MA2, FAW, FAC,	Air traffic control operations.
	_	MOU.	
122.000 MHz	F	MA, FAC, MOU	Air carrier and private aircraft enroute flight advisory
100 005 141	- 0		service provided by FAA.
122.025 MHz	F, S	MA2, FAW, FAC,	Air traffic control operations.
100.050.141	_	MOU.	A
122.050 MHz	F	MA, FAC, MOU	Air traffic control operations.
122.075 MHz	F, S	MA2, FAW, FAC,	Air traffic control operations.
		MOU.	
122.100 MHz	F, O	MA, FAC, MOU	Air traffic control operations.
122.125-122.675	F	MA2, FAC, MOU	Air traffic control operations; 25 kHz spacing.
MHz.			
	0 1	LAAA EALL MACLL	I I Injaam at airparta with no control tower: Acronoutical
122.700 MHz	G, L	MA, FAU, MOU	Unicom at airports with no control tower; Aeronautical utility stations.

Federal Communications Commission

Frequency or fre- quency band	Subpart	Class of station	Remarks
122.725 MHz	G, L	MA, FAU, MOU	Unicom at airports with no control tower; Aeronautical
122.750 MHz	F	MA2	utility stations. Private fixed wing aircraft air-to-air communications.
122.775 MHz	K	MA, FAS	Triale mod ming another an to an oblimation.
122.800 MHz	G, L	MA, FAU, MOU	Unicom at airports with no control tower; Aeronautical utility stations.
122.825 MHz	I	MA, FAE	Domestic VHF.
122.850 MHz	H, K	MA, FAM, FAS	Domestic VHF.
122.875 MHz 122.900 MHz	F, H, L, M	MA, FAE MA, FAR, FAM, MOU	Domestic var.
122.925 MHz	H	MA2, FAM.	
122.950 MHz	G, L	MA, FAU, MOU	Unicom at airports with control tower; Aeronautical util-
122.975 MHz	G, L	MA, FAU, MOU	ity stations. Unicom at airports with no control tower; Aeronautical
123.000 MHz	G, L	MA, FAU, MOU	utility stations. Unicom at airports with no control tower; Aeronautical
123.025 MHz	F	MA2	utility stations. Helicopter air-to-air communications; Air traffic control
123.050 MHz	G, L	MA, FAU, MOU	operations. Unicom at airports with no control tower; Aeronautical
123.075 MHz	G, L	MA, FAU, MOU	utility stations. Unicom at airports with no control tower; Aeronautical
123.100 MHz	M, O	MA, FAC, FAR	utility stations.
123.125 MHz	J	MA, FAT	Itinerant.
123.150 MHz	J	MA, FAT	Itinerant.
123.175 MHz	J	MA, FAT	Itinerant.
123.200 MHz	J	MA, FAT	
123.225 MHz	J	MA, FAT	
123.250 MHz	J	MA, FAT	
123.275 MHz	J	MA, FAT	
123.300 MHz	K	MA, FAS	
123.325 MHz	J	MA, FAT MA, FAT	
123.350 MHz 123.375 MHz	J	MA, FAT	
123.400 MHz	J	MA, FAT	Itinerant.
123.425 MHz	J	MA, FAT	
123.450 MHz	J	MA, FAT	
123.475 MHz	J	MA, FAT	
123.500 MHz	K	MA, FAS	
123.525 MHz	J	MA, FAT	
123.550 MHz	J	MA, FAT	
123.575 MHz	J	MA, FAT	05111
123.6–128.8 MHz	O, S	MA, FAC, FAW, GCO, RCO, RPC.	25 kHz channel spacing.
128.825-132.000	0, S	MA, FAE	Domestic VHF.
132.025–135.975 MHz.	0, 3	MA, FAC, FAW, GCO RCO RPC.	25 kHz channel spacing.
136.000–136.400 MHz.	O, S	MA, FAC, FAW, GCO, RCO, RPC	Air traffic control operations; 25 kHz channel spacing.
136.425 MHz	O, S	MA, FAC, FAW, GCO, RCO, RPC	Air traffic control operations.
136.450 MHz	O, S	MA, FAC, FAW, GCO, RCO, RPC	Air traffic control operations.
136.475 MHz	O, S	MA, FAC, FAW, GCO, RCO, RPC	Air traffic control operations.
136.500–136.875 MHz.	1	MA, FAE	Domestic VHF.
136.900 MHz	I	MA, FAE	International and Domestic VHF.
136.925 MHz	1	MA, FAE	International and domestic VHF.
136.950 MHz	I	MA, FAE	International and domestic VHF.
136.975 MHz	<u>L</u>	MA, FAE	International and domestic VHF.
156.300 MHz	F	MA	For communications with ship stations under specific conditions.
156.375 MHz	F	MA	For communications with ship stations under specific conditions; Not authorized in New Orleans Vessel
156.400 MHz	F	MA	traffic service area. For communications with ship stations under specific
156.425 MHz	F	MA	conditions. For communications with ship stations under specific
156 450 MHz	F	MA	conditions. For communications with ship stations under specific

§87.185

Frequency or fre- quency band	Subpart	Class of station	Remarks
156.625 MHz	F	MA	For communications with ship stations under specific conditions.
156.800 MHz	F	MA	Distress, safety and calling frequency; For communications with ship stations under specific conditions.
156.900 MHz	F	MA	For communications with ship stations under specific conditions.
157.425 MHz	F	MA	For communications with commercial fishing vessels under specific conditions except in Great Lakes and St. Lawrence Seaway Areas.
243.000 MHz	F	MA	Emergency and distress frequency for use of survival craft and emergency locator transmitters.
328.600-335.400 MHz.	Q	RLG	ILS glide path.
334.550 MHz	Q	RLT	
334.700 MHz	Q	RLT	
406.0–406.1 MHz	F, G, H, I, J, K, M, O	MA, FAU, FAE, FAT, FAS, FAC, FAM.	Emergency and distress.
960-1215 MHz	F, Q	MA, RL, RNV	Electronic aids to air navigation.
978.000 MHz	F, L, Q UAT	MA, MOU, UAT	Universal Access Transceivers.
	Q	RLT	
979.000 MHz	Q	RLT	
1030.000 MHz	Q	RLT	
1104.000 MHz	Q	RLT	
1300-1350 MHz	F, Q	MA, RLS	Surveillance radars and transponders.
1435–1525 MHz	F, J	MA, FAT	Aeronautical telemetry and telecommand operations.
1559–1610 MHz	Q	DGP	Differential GPS.
1559–1626.5 MHz	F, Q	MA, RL	Aeronautical radionavigation.
1646.5–1660.5 MHz	F	TJ	Aeronautical Mobile-Satellite (R).
2310-2320 MHz	J	MA, FAT	Aeronautical telemetry and telecommand operations.
2345–2395 MHz	J	MA, FAT	Aeronautical telemetry and telecommand operations.
2700–2900 MHz	Q	RLS, RLD	Airport surveillance and weather radar.
4200–4400 MHz	F	MA	Radio altimeters.
5000–5250 MHz	Q	MA, RLW	Microwave landing systems.
5031.000 MHz	Q	RLT	
5350-5470 MHz	<u>F</u>	MA	Airborne radars and associated airborne beacons.
8750–8850 MHz	F	MA	Airborne doppler radar.
9000–9200 MHz	Q	RLS, RLD	Land-based radar.
9300–9500 MHz	F, Q	MA	Airborne radars and associated airborne beacons.
13250–13400 MHz	F	MA	Airborne doppler radar.
15400–15700 MHz	Q	RL	Aeronautical radionavigation.
24750–25050 MHz 32300–33400 MHz	F, Q	MA, RL MA, RL	Aeronautical radionavigation.
32300-33400 WHZ	F, &	IVIA, RL	Aeronautical radionavigation.

[53 FR 28940, Aug. 1, 1988]

EDITORIAL NOTE: For FEDERAL REGISTER citations affecting §87.183, see the List of CFR Sections Affected, which appears in the Finding Aids section of the printed volume and at www.fdsys.gov.

Subpart F—Aircraft Stations

§87.185 Scope of service.

(a) Aircraft stations must limit their communications to the necessities of safe, efficient, and economic operation of aircraft and the protection of life and property in the air, except as otherwise specifically provided in this part. Contact with an aeronautical land station must only be attempted when the aircraft is within the serivce area of the land station. however, aircraft stations may transmit advisory information on air traffic control,

unicom or aeronautical multicom frequencies for the benefit and use of other stations monitoring these frequencies in accordance with FAA recommended traffic advisory practices.

- (b) Aircraft public correspondence service must be made available to all persons without discrimination and on reasonable demand, and must communicate without discrimination with any public coast station or mobile-satellite earth station authorized to provide aircraft public correspondence service.
- (c) Aircraft public correspondence service on maritime mobile frequencies