

Federal Communications Commission

§ 90.311

§ 90.311 Frequencies.

(a) Except as provided for in § 90.315 and except for those frequencies allocated to services in part 22 of this chapter (see §§ 22.591, 22.621, 22.651, and 22.1007 of this chapter) the following frequencies in the band 470–512 MHz

may be assigned as indicated in the table below. The first and last assignable frequencies are shown. Assignable frequencies occur in increments of 6.25 kHz. The separation between base and mobile transmit frequencies is 3 MHz for two frequency operation.

| Channel Assignment | Urbanized Area | General access pool | |
|--------------------|---|------------------------------|------------------------|
| | | Base and mobile | Mobile |
| 14 | Boston, MA | 470.30625 to 472.99375 | 473.30625 to 475.99375 |
| | Chicago, IL | | |
| | Cleveland, OH | | |
| | Miami, FL | | |
| | New York/N.E. NJ | | |
| | Pittsburgh, PA | | |
| | Los Angeles, CA | 470.05625 to 472.99375 | 473.05625 to 475.99375 |
| 15 | Chicago, IL | 476.30625 to 478.99375 | 479.30625 to 481.99375 |
| | Cleveland, OH | | |
| | Detroit, MI | | |
| | New York/N.E. NJ | | |
| 16 | Boston, MA | 482.30625 to 484.99375 | 485.30625 to 487.99375 |
| | Dallas/Fort Worth, TX | | |
| | Detroit, MI | | |
| | San Francisco/Oakland, CA | | |
| | Los Angeles, CA (Use is restricted to Public Safety Pool eligibles) | 482.00625 to 484.99375 | 485.00625 to 487.99375 |
| 17 | Houston, TX | 488.30625 to 490.99375 | 491.30625 to 493.99375 |
| | San Francisco/Oakland, CA | | |
| | Washington, DC/MD/VA | | |
| 18 | Pittsburgh, PA | 494.30625 to 496.99375 | 497.30625 to 499.99375 |
| | Washington, DC/MD/VA | | |
| 19 | Philadelphia, PA | 500.30625 to 502.99375 | 503.30625 to 505.99375 |
| 20 | Los Angeles, CA | 506.13125 to 508.99375 | 509.13125 to 511.99375 |
| | Philadelphia, PA | 506.30625 to 508.99375 | 509.30625 to 511.99375 |

(1) Channel availability in the General Access Pool in any of the urbanized areas referred to in the table depends on whether that channel is presently assigned to one of the following categories of users:

- (i) Public safety (as defined in § 90.20(a));
- (ii) Power and telephone maintenance licensees (as defined in § 90.7);
- (iii) Special industrial licensees (as defined in § 90.7);
- (iv) Business licensees (as defined in § 90.35(a));
- (v) Petroleum, forest products, and manufacturers licensees (as defined in § 90.7);
- (vi) Railroad, motor carrier, and automobile emergency licensees (as defined in § 90.7); and
- (vii) Taxicab licensees (as defined in § 90.7).

(2) If assigned, subsequent authorizations will only be granted to users from the same category. If unassigned, or should a channel subsequently become

unassigned, it will be treated as available in the General Access Pool.

(3) Normally, each channel should be substantially loaded in accordance with the standards set out in § 90.313.

(4) The following frequencies will be authorized a maximum bandwidth of 6 kHz.

| Channel | Frequency |
|----------|-----------|
| 14 | 470.30625 |
| | 475.99375 |
| 15 | 476.30625 |
| | 481.99375 |
| 16 | 482.30625 |
| | 487.99375 |
| 17 | 488.30625 |
| | 493.99375 |
| 18 | 494.30625 |
| | 499.99375 |
| 19 | 500.30625 |
| | 505.99375 |
| 20 | 506.30625 |
| | 511.99375 |

§ 90.313

(b) [Reserved]

[43 FR 54791, Nov. 22, 1978, as amended at 44 FR 49692, Aug. 24, 1979; 51 FR 4362, Feb. 4, 1986; 60 FR 37272, July 19, 1995; 62 FR 2041, Jan. 15, 1997; 62 FR 18932, Apr. 17, 1997; 64 FR 36270, July 6, 1999]

§ 90.313 Frequency loading criteria.

(a) Except as provided for in paragraph (b) of this section, the maximum channel loading on frequencies in the 470–512 MHz band is as follows:

(1) 50 units for systems eligible in the Public Safety Pool (see § 90.20(a)).

(2) 90 units for systems eligible in the Industrial/Business Pool (see § 90.35(a)).

(b) If a licensee has exclusive use of a frequency, then the loading standards in paragraph (a) of this section, may be exceeded. If it is a shared channel, the loading standards can be exceeded upon submission of a signed statement by all those sharing the channel agreeing to the increase.

(c) A unit is defined as a mobile transmitter-receiver. Loading standards will be applied in terms of the number of units actually in use or to be placed in use within 8 months following authorization. A licensee will be required to show that an assigned frequency pair is at full capacity before it may be assigned a second or additional frequency pair. Channel capacity may be reached either by the requirements of a single licensee or by several users sharing a channel. Until a channel is loaded to capacity it will be available for assignment to other users in the same area. A frequency pair may be re-assigned at distances 64 km. (40 mi.), 32 km. (20 mi.) for Channel 15, Chicago; Channel 20, Philadelphia; and Channel 17, Washington, or more from the location of base stations authorized on that pair without reference to loading at the point of original installation. Following authorization, the licensee shall notify the Commission either during or at the close of the 8 month period of the number of units in operation. In the Industrial Radio Services, if the base station facility is to be used by more than a single licensee, the frequency assigned to it will not be re-assigned for use by another facility within 64 km. (40 mi.) or 32 km. (20 mi.) where applicable for a period of 12 months, *Provided*, That the facility is

47 CFR Ch. I (10–1–13 Edition)

constructed within 90 days from the date of the first grant, meets the loading standards to at least 50 percent within 9 months, and meets all loading standards within 12 months.

[43 FR 54791, Nov. 22, 1978, as amended at 47 FR 36649, Aug. 23, 1982; 62 FR 18933, Apr. 17, 1997]

§ 90.315 Special provisions governing use of frequencies in the 476–494 MHz band (TV Channels 15, 16, 17) in the Southern Louisiana-Texas Offshore Zone.

(a) The frequency bands from 490–491 and 493–494 MHz will be available for assignment to stations governed by this part within Zone A. The boundaries of Zone A are from longitude 87°45′ on the east to longitude 94°00′ on the west, and from the 3-mile limit along the Gulf of Mexico shoreline on the north to the limit of the Outer Continental Shelf on the south. The frequency bands from 484–485 and 476–488 MHz will be available for assignment to stations governed by this part within Zone B. The boundaries of Zone B are from longitude 87°45′ on the east to longitude 95°00′ on the west and from the 3-mile limit along the Gulf of Mexico shoreline on the north to the limit of the Outer Continental Shelf on the south. The frequency bands from 478–479 and 481–481 MHz will be available for assignment to stations governed by this part within Zone C. The boundaries of Zone C are from longitude 94°00′ on the east, the 3-mile limit on the north and west, a 281 km (175 mile) radius from the reference point at Linares, N.L., Mexico on the southwest, latitude 26°00′ on the south, and the limits of the Outer Continental Shelf on the southeast. These frequencies may also be assigned to fixed stations located on shore designed to provide communications service within the zone.

(b) Offshore base/mobile, and offshore and shore fixed stations may be authorized.

(c) F2, F3, F4, F9, and A2, A3, A4, and A9 emissions may be authorized.

(d) Offshore stations shall afford co-channel protection to TV stations on