## § 90.476

- (5) The system must include automatic monitoring equipment, installed at the base station transmitter site(s), which will prevent the activation of the system when signals of other co-channel stations are present.
  - (b) [Reserved]

[43 FR 54791, Nov. 22, 1978, as amended at 44 FR 67125, Nov. 23, 1979; 47 FR 17521, Apr. 23, 1982; 72 FR 35199, June 27, 2007]

## INTERCONNECTED SYSTEMS

## § 90.476 Interconnection of fixed stations and certain mobile stations.

- (a) Fixed stations and mobile stations used to provide the functions of fixed stations pursuant to the provisions of §§90.35(c)(11), 90.35(c)(42), and 90.267 are not subject to the interconnection provisions of §§90.477 and 90.483 and may be interconnected with the facilities of common carriers.
- (b) Mobile stations used to provide the functions of base and mobile relay stations pursuant to the provisions of §§90.35(c)(11), 90.35(c)(42), and 90.267 are not subject to the provisions of §90.477(d)(3) and may be interconnected with the facilities of common carriers subject to the provisions of §§90.477(d)(1), 90.477(d)(2), 90.477(e), and 90.483.
- (c) The provisions of this section do not apply to commercial mobile radio service providers, as defined in part 20 of this chapter.

[50 FR 15152, Apr. 17, 1985, as amended at 59 FR 59965, Nov. 21, 1994; 62 FR 18934, Apr. 17, 1997]

## § 90.477 Interconnected systems.

- (a) Applicants for new land stations to be interconnected with the public switched telephone network must indicate on their applications (class of station code) that their stations will be interconnected. Licensees of land stations that are not interconnected may interconnect their stations with the public switched telephone network only after modifying their license. See §1.929 of this chapter. In all cases a detailed description of how interconnection is accomplished must be maintained by licensees as part of their station records. See §90.433 of this part.
- (b) In the frequency ranges 806–824 MHz, 851–869 MHz, 896–901 MHz, and 935–

- 940 MHz, interconnection with the public switched telephone network is authorized under the following conditions:
- (1) Interconnected operation is on a secondary basis to dispatch operation. This restriction will not apply to trunked systems or on any channel assigned exclusively to one licensee.
- (2) Interconnection may be accomplished at any location through a separate or shared interconnection device. When land stations subject to this part are multiple licensed or shared by authorized users, arrangements for telephone service must be made with a duly authorized carrier by users, licensees, or their authorized agents on a non-profit cost sharing basis. When telephone service costs are shared, at least one licensee participating in the cost sharing arrangement must maintain cost sharing records and the costs must be distributed at least once a year. Licensees, users, or their authorized agents may also make joint use arrangements with a duly authorized carrier and arrange that each licensee or user pay the carrier directly for the licensee's or user's share of the joint use of the shared telephone service. A report of the cost distribution must be placed in the licensee's station records and made available to participants in the sharing and the Commission upon request. In all cases, arrangements with the duly authorized carrier must disclose the number of licensees and users and the nature of the use.
- (c) Interconnection of facilities in the Radiolocation Service (subpart F) will not be permitted.
- (d) In the frequency ranges below 800 MHz, interconnection with the public switched telephone network is authorized under the following conditions:
- (1) Interconnected operation is on a secondary basis to dispatch operation. This restriction will not apply to trunked systems or on any channel assigned exclusively to one licensee.
- (2) Interconnection may be accomplished at any location through a separate or shared interconnection device. When land stations subject to this part are multiple licensed or shared by authorized users, arrangements for telephone service must be made with a