

§ 11.41

broadcast station log as specified in §§ 73.1820 and 73.1840 of this chapter for all broadcast streams and cable system records as specified in §§ 76.1700, 76.1708, and 76.1711 of this chapter. All other EAS Participants must also keep records indicating reasons why any tests were not received and these records must be retained for two years, maintained at the EAS Participant's headquarters, and made available for public inspection upon reasonable request.

(b) If an EAS Encoder, EAS Decoder or Intermediary Device used as part of the EAS to decode and/or encode messages formatted in the EAS Protocol and/or the Common Alerting Protocol becomes defective, the EAS Participant may operate without the defective equipment pending its repair or replacement for 60 days without further FCC authority. Entries shall be made in the broadcast station log, cable system records, and records of other EAS Participants, as specified in paragraph (a) of this section, showing the date and time the equipment was removed and restored to service. For personnel training purposes, the required monthly test script must still be transmitted even though the equipment for generating the EAS message codes, Attention Signal and EOM code is not functioning.

(c) If repair or replacement of defective equipment is not completed within 60 days, an informal request shall be submitted to the District Director of the FCC field office serving the area in which the EAS Participant is located, or in the case of DBS and SDARS providers to the District Director of the FCC field office serving the area where their headquarters is located, for additional time to repair the defective equipment. This request must explain what steps have been taken to repair or replace the defective equipment, the alternative procedures being used while the defective equipment is out of service, and when the defective equipment will be repaired or replaced.

[70 FR 71034, Nov. 25, 2005, as amended at 77 FR 16704, Mar. 22, 2012]

47 CFR Ch. I (10–1–14 Edition)

Subpart C—Organization

§ 11.41 Participation in EAS.

All EAS Participants specified in § 11.11 are categorized as Participating National (PN) sources, and must have immediate access to an EAS Operating Handbook.

[77 FR 16704, Mar. 22, 2012]

§ 11.42 [Reserved]

§ 11.43 National level participation.

Entities that wish to voluntarily participate in the national level EAS may submit a written request to the Chief, Public Safety and Homeland Security Bureau.

[71 FR 69038, Nov. 29, 2006]

§ 11.44 [Reserved]

§ 11.45 Prohibition of false or deceptive EAS transmissions.

No person may transmit or cause to transmit the EAS codes or Attention Signal, or a recording or simulation thereof, in any circumstance other than in an actual National, State or Local Area emergency or authorized test of the EAS. Broadcast station licensees should also refer to § 73.1217 of this chapter.

§ 11.46 EAS public service announcements.

EAS Participants may use Public Service Announcements or obtain commercial sponsors for announcements, infomercials, or programs explaining the EAS to the public. Such announcements and programs may not be a part of alerts or tests, and may not simulate or attempt to copy alert tones or codes.

[70 FR 71034, Nov. 25, 2005]

§ 11.47 Optional use of other communications methods and systems.

(a) Analog and digital broadcast stations may additionally transmit EAS messages through other communications means. For example, on a voluntary basis, FM stations may use subcarriers to transmit the EAS codes including 57 kHz using the RBDS standard produced by the National Radio

Federal Communications Commission

§ 11.51

Systems Committee (NRSC) and television stations may use subsidiary communications services.

(b) Other technologies and public service providers, such as low earth orbiting satellites, that wish to participate in the EAS may contact the FCC's Public Safety and Homeland Security Bureau or their State Emergency Communications Committee for information and guidance.

[70 FR 71034, Nov. 25, 2005, as amended at 71 FR 76220, Dec. 20, 2006; 72 FR 62135, Nov. 2, 2007]

Subpart D—Emergency Operations

§ 11.51 EAS code and Attention Signal Transmission requirements.

(a) Analog and digital broadcast stations must transmit, either automatically or manually, national level EAS messages and required tests by sending the EAS header codes, Attention Signal, emergency message and End of Message (EOM) codes using the EAS Protocol. The Attention Signal must precede any emergency audio message.

(b) When relaying EAS messages, EAS Participants may transmit only the EAS header codes and the EOM code without the Attention Signal and emergency message for State and local emergencies. Pauses in video programming before EAS message transmission should not cause television receivers to mute EAS audio messages. No Attention Signal is required for EAS messages that do not contain audio programming, such as a Required Weekly Test.

(c) All analog and digital radio and television stations shall transmit EAS messages in the main audio channel. All DAB stations shall also transmit EAS messages on all audio streams. All DTV broadcast stations shall also transmit EAS messages on all program streams.

(d) Analog and digital television broadcast stations shall transmit a visual message containing the Originator, Event, Location and the valid time period of an EAS message. Effective June 30, 2012, visual messages derived from CAP-formatted EAS messages shall contain the Originator, Event, Location and the valid time period of the

message and shall be constructed in accordance with §3.6 of the "ECIG Recommendations for a CAP EAS Implementation Guide, Version 1.0" (May 17, 2010), except that if the EAS Participant has deployed an Intermediary Device to meet its CAP-related obligations, this requirement shall be effective June 30, 2015, and until such date shall be subject to the general requirement to transmit a visual message containing the Originator, Event, Location and the valid time period of the EAS message. If the message is a video crawl, it shall be displayed at the top of the television screen or where it will not interfere with other visual messages.

(e) Analog class D non-commercial educational FM stations as defined in §73.506 of this chapter, digital class D non-commercial educational FM stations, analog Low Power FM (LPFM) stations as defined in §§73.811 and 73.853 of this chapter, digital LPFM stations, analog low power TV (LPTV) stations as defined in §74.701(f) of this chapter, and digital LPTV stations as defined in §74.701(k) of this chapter are not required to have equipment capable of generating the EAS codes and Attention Signal specified in §11.31.

(f) Analog and digital broadcast station equipment generating the EAS codes and the Attention Signal shall modulate a broadcast station transmitter so that the signal broadcast to other EAS Participants alerts them that the EAS is being activated or tested at the National, State or Local Area level. The minimum level of modulation for EAS codes, measured at peak modulation levels using the internal calibration output required in §11.32(a)(4), shall modulate the transmitter at the maximum possible level, but in no case less than 50% of full channel modulation limits. Measured at peak modulation levels, each of the Attention Signal tones shall be calibrated separately to modulate the transmitter at no less than 40%. These two calibrated modulation levels shall have values that are within 1 dB of each other.

(g) Analog cable systems and digital cable systems with fewer than 5,000 subscribers per headend and wireline