§ 15.701

6036, Fax: (202) 267–4106, e-mail: jtaboada@comdt.uscg.mil.

TABLE 4—CONSULTATION AREA COORDINATES FOR LAND STATIONS, SET 1 (1.7-30 MHz)

Command name	Location	Latitude	Longitude
Camslant	Maspee, MA Chesapeake, VA Miami, FL Belle Chasse, IA Pt. Reyes Sta, CA Wahiawa, HI Kodiak, AK Finegayan, GU	36°33′59″ N 25°36′58″ N 29°52′40″ N 38°06′00″ N 21°31′08″ N 57°04′26′ N	70°18′57″ W 76°15′23″ W 80°23′04″ W 89°54′46″ W 122°55′48″ W 157°59′28″ W 152°28′20″ W 144°50′20″ E

NOTE: Systems of coordinates conform to NAD 83.

Point of contact: COTHEN Technical Support Center, COTHEN Program Manager, Tel: (800) 829–6336.

TABLE 5—CONSULTATION AREA COORDINATES FOR LAND STATIONS, SET 2 (1.7–30 MHz)

NOTE: Systems of coordinates conform to NAD 83.

Point Of Contact: ROTHR Deputy Program Manager, (540) 653–3624.

TABLE 6—CONSULTATION AREA COORDINATES FOR RADAR RECEIVER STATIONS (1.7–30 MHz)

Latitude/Longitude		
18°01′ N/66°30′ W		
28°05′ N/98°43′ W		
36°34′ N/76°18′ W		

NOTE: Systems of coordinates conform to NAD 83.

 $[70 \ \mathrm{FR} \ 1374, \ \mathrm{Jan.} \ 7, \ 2005, \ \mathrm{as} \ \mathrm{amended} \ \mathrm{at} \ 71 \ \mathrm{FR} \ 49379, \ \mathrm{Aug.} \ 23, \ 2006]$

Subpart H—Television Band Devices

SOURCE: 74 FR 7326, Feb. 17, 2009, unless otherwise noted.

§15.701 Scope.

This subpart sets forth the regulations for unlicensed Television Band Devices (TVBDs). These devices are unlicensed intentional radiators that operate on available TV channels in the broadcast television frequency bands at 54–60 MHz (TV channel 2), 76–88 MHz (TV channels 5 and 6), 174–216 MHz (TV channels 7–13), 470–608 MHz (TV channels 14–36) and 614–698 MHz (TV channels 38–51).

[75 FR 75835, Dec. 6, 2010]

§15.703 Definitions.

(a) Available channel. A six-megahertz television channel, as specified in §73.603 of this chapter, which is not being used by an authorized service at or near the same geographic location as the TVBD and is acceptable for use by an unlicensed device under the provisions of this subpart.

(b) Contact verification signal. An encoded signal broadcast by a fixed or Mode II device for reception by Mode I devices to which the fixed or Mode II device has provided a list of available channels for operation. Such signal is for the purpose of establishing that the Mode I device is still within the reception range of the fixed or Mode II device for purposes of validating the list of available channels used by the Mode I device and shall be encoded to ensure that the signal originates from the device that provided the list of available channels. A Mode I device may respond only to a contact verification signal from the fixed or Mode II device that provided the list of available channels on which it operates. A fixed or Mode II device shall provide the information