

Federal Communications Commission

§ 17.48

upon any then existing or authorized antenna structure or structures, unless the FAA issues a new determination of “no hazard” and associated FAA study for the particular structure.

[56986, Sept. 24, 2014]

EFFECTIVE DATE NOTE: At 79 FR 56986, Sept. 24, 2014, §17.24 was added, effective Oct. 24, 2014.

§§ 17.25–17.43 [Reserved]

§ 17.45 Temporary warning lights.

During construction of an antenna structure, for which red obstruction lighting is required, at least two 116- or 125-watt lamps (A21/TS) enclosed in aviation red obstruction light globes, shall be installed at the uppermost point of the structure. The intensity of each lamp shall not be less than 32.5 candelas. In addition, as the height of the structure exceeds each level at which permanent obstruction lights will be required, two similar lights shall be installed at each such level. These temporary warning lights shall be displayed nightly from sunset to sunrise until the permanent obstruction lights have been installed and placed in operation, and shall be positioned so as to insure unobstructed visibility of at least one of the lights at any normal angle of approach. If practical, the permanent obstruction lights may be installed and operated at each required level as construction progresses.

[32 FR 11273, Aug. 3, 1967, as amended at 39 FR 26157, July 17, 1974; 42 FR 54826, Oct. 11, 1977]

EFFECTIVE DATE NOTE: At 79 FR 56986, Sept. 24, 2014, §17.45 was removed and reserved, effective Oct. 24, 2014.

§ 17.47 Inspection of antenna structure lights and associated control equipment.

The owner of any antenna structure which is registered with the Commission and has been assigned lighting specifications referenced in this part:

(a)(1) Shall make an observation of the antenna structure’s lights at least once each 24 hours either visually or by observing an automatic properly maintained indicator designed to register any failure of such lights, to insure

that all such lights are functioning properly as required; or alternatively,

(2) Shall provide and properly maintain an automatic alarm system designed to detect any failure of such lights and to provide indication of such failure to the owner.

(b) Shall inspect at intervals not to exceed 3 months all automatic or mechanical control devices, indicators, and alarm systems associated with the antenna structure lighting to insure that such apparatus is functioning properly.

[61 FR 4363, Feb. 6, 1996]

EFFECTIVE DATE NOTE: At 79 FR 56986, Sept. 24, 2014, §17.47 was amended by adding paragraph (c), effective Oct. 24, 2014. For the convenience of the user, the added text is set forth as follows:

§ 17.47 Inspection of antenna structure lights and associated control equipment.

* * * * *

(c) Is exempt from paragraph (b) of this section for any antenna structure monitored by a system that the Wireless Telecommunications Bureau has determined includes self-diagnostic features sufficient to render quarterly inspections unnecessary, upon certification of use of such system to the Bureau.

§ 17.48 Notification of extinguishment or improper functioning of lights.

The owner of any antenna structure which is registered with the Commission and has been assigned lighting specifications referenced in this part:

(a) Shall report immediately by telephone or telegraph to the nearest Flight Service Station or office of the Federal Aviation Administration any observed or otherwise known extinguishment or improper functioning of any top steady burning light or any flashing obstruction light, regardless of its position on the antenna structure, not corrected within 30 minutes. Such reports shall set forth the condition of the light or lights, the circumstances which caused the failure, the probable date for restoration of service, the FCC Antenna Structure Registration Number, the height of the structure (AGL and AMSL if known) and the name, title, address, and telephone number of the person making the report. Further notification by telephone or telegraph